

Package ‘RBMRB’

October 14, 2026

Title Interface to the Biological Magnetic Resonance Data Bank
(‘BMRB’)

Version 3.0.0

Date 2026-10-01

Description A comprehensive interface to the Biological Magnetic Resonance Data Bank (‘BMRB’) <<https://bmr.io>>, mirroring all functionality of the ‘PyBMRB’ Python package (v3.0). Provides four modules: (1) ‘ChemicalShift’ for fetching per-entry chemical shift data from the ‘BMRB’ REST API or local ‘NMR-STAR’ files; (2) ‘ChemicalShiftStatistics’ for database-wide statistical queries; (3) Spectra for simulating ‘1H-15N’ ‘HSQC’, ‘1H-13C’ ‘HSQC’, ‘1H-1H’ ‘TOCSY’, and generic 2D ‘NMR’ spectra as interactive plots; and (4) Histogram for chemical shift distribution visualizations with optional filtering by pH, temperature, and ambiguity code. All interactive plots are rendered via ‘plotly’. Uses the ‘BMRB’ REST API v2 <<https://api.bmr.io/v2/>>.

License GPL-3

URL <https://github.com/bmr.io/RBMRB>

BugReports <https://github.com/bmr.io/RBMRB/issues>

Encoding UTF-8

Depends R (>= 4.1.0)

Imports httr2 (>= 1.0.0), jsonlite (>= 1.8.0), plotly (>= 4.10.0), cli (>= 3.4.0)

Suggests testthat (>= 3.0.0), knitr, rmarkdown, htmlwidgets, withr

Config/testthat/edition 3

VignetteBuilder knitr

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Kumaran Baskaran [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-0418-0286>>)

Maintainer Kumaran Baskaran <baskaran@uchc.edu>

Repository CRAN

Date/Publication 2026-10-14 15:22:12 UTC

Contents

bmrbs_citation	3
bmrbs_debug_entry	3
bmrbs_fetch_entry	4
bmrbs_from_pdb	4
bmrbs_list_entries	5
bmrbs_pdb_ids	6
bmrbs_search	6
bmrbs_status	7
bmrbs_test	7
bmrbs_upload_entry	8
c13hsqc	8
conditional_cs_hist	10
create_2d_peaklist	11
create_c13hsqc_peaklist	12
create_n15hsqc_peaklist	13
create_tocsy_peaklist	13
cs_from_bmrbs	14
cs_from_file	15
cs_hist	16
cs_hist2d	17
cs_peek	18
cs_stats	19
cs_summary	20
cs_table	20
cs_to_df	21
export_peak_list	21
filter_cs_outliers	22
generic_2d	23
get_2d_cs_data	24
get_cs_data	25
get_cs_from_bmrbs_db	26
n15hsqc	27
RBMRB_version	28
standard_amino_acids	29
standard_nucleic_acids	29
tocsy	30

Index

32

bmrbs_citation	<i>Get the citation for a BMRB entry</i>
----------------	--

Description

Get the citation for a BMRB entry

Usage

```
bmrbs_citation(bmrbs_id, format = "bibtex")
```

Arguments

bmrbs_id	A single BMRB entry ID.
format	Output format: "bibtex" (default), "json-ld", or "text".

Value

A character string containing the citation.

Examples

```
## Not run:  
cat(bmrbs_citation(15060, format = "text"))  
  
## End(Not run)
```

bmrbs_debug_entry	<i>Diagnose BMRB entry fetch problems</i>
-------------------	---

Description

Fetches a BMRB entry using both the zlib-compressed and plain JSON endpoints and reports what is found at each step. Run this when [cs_from_bmrbs](#) returns no data.

Usage

```
bmrbs_debug_entry(bmrbs_id)
```

Arguments

bmrbs_id	A single BMRB entry ID (integer or character).
----------	--

Value

Invisibly, the parsed entry JSON list, or NULL on failure.

Examples

```
## Not run:
bmrp_debug_entry(15060)

## End(Not run)
```

bmrp_fetch_entry	<i>Fetch raw metadata for a BMRB entry</i>
------------------	--

Description

Fetch raw metadata for a BMRB entry

Usage

```
bmrp_fetch_entry(bmrp_ids)
```

Arguments

bmrp_ids A single BMRB entry ID or a character/integer vector.

Value

A named list of raw entry metadata (API JSON as R list).

Examples

```
## Not run:
meta <- bmrp_fetch_entry(15060)
names(meta[["15060"]])

## End(Not run)
```

bmrp_from_pdb	<i>Get BMRB IDs associated with a PDB entry</i>
---------------	---

Description

Get BMRB IDs associated with a PDB entry

Usage

```
bmrp_from_pdb(pdb_id)
```

Arguments

pdb_id A PDB ID string (e.g. "2JM0").

Value

A data.frame with columns bmrblid, match_type, and comment.

Examples

```
## Not run:  
bmrbl_from_pdb("2JM0")  
  
## End(Not run)
```

bmrblistentries	<i>List all BMRB entry IDs</i>
-----------------	--------------------------------

Description

Returns all public entry IDs in the specified BMRB database.

Usage

```
bmrblistentries(database = "macromolecules")
```

Arguments

database One of "macromolecules" (default), "metabolomics", or "chemcomps".

Value

A character vector of BMRB entry IDs.

Examples

```
## Not run:  
ids <- bmrblistentries()  
length(ids)  
  
## End(Not run)
```

bmrp_pdb_ids	<i>Get PDB IDs associated with a BMRB entry</i>
--------------	---

Description

Get PDB IDs associated with a BMRB entry

Usage

```
bmrp_pdb_ids(bmrp_id)
```

Arguments

bmrp_id	A single BMRB entry ID.
---------	-------------------------

Value

A data.frame with columns pdb_id, match_type, and comment.

Examples

```
## Not run:  
bmrp_pdb_ids(15000)  
  
## End(Not run)
```

bmrp_search	<i>Search BMRB using the instant-search endpoint</i>
-------------	--

Description

Searches BMRB by title, author name, organism, amino-acid sequence, InChI string, or other terms.

Usage

```
bmrp_search(term, database = "combined")
```

Arguments

term	A search string.
database	One of "macromolecules", "metabolomics", or "combined" (default).

Value

A data.frame with columns value, label, sub_date, authors, and link.

Examples

```
## Not run:
bmrbl_search("ubiquitin human")
bmrbl_search("GB3", database = "macromolecules")

## End(Not run)
```

bmrbl_status*Get BMRB API server status*

Description

Returns current server information including entry counts and database last-update timestamps from the BMRB REST API.

Usage

```
bmrbl_status()
```

Value

A list with server status information.

Examples

```
## Not run:
bmrbl_status()

## End(Not run)
```

bmrbl_test*Run a connectivity self-test*

Description

Performs three checks: BMRB API status, entry fetch and parse for entry 15060, and the chemical shift search endpoint. Useful for verifying that the BMRB API is reachable from your network. Progress is reported with `message()`, so it can be silenced with `suppressMessages()`.

Usage

```
bmrbl_test()
```

Value

A named logical vector with elements `api_status`, `entry_fetch`, and `search_query` (invisibly).

Examples

```
## Not run:
bmr_test()

## End(Not run)
```

bmr_upload_entry	<i>Upload an NMR-STAR file to BMRB for temporary access</i>
------------------	---

Description

Uploads a local NMR-STAR file to the BMRB server. The entry is stored for 7 days. The returned token can be used as a BMRB ID in all other package functions.

Usage

```
bmr_upload_entry(file_path)
```

Arguments

file_path	Path to a local NMR-STAR .str file.
-----------	-------------------------------------

Value

A character string token usable as a BMRB ID (invisibly).

Examples

```
## Not run:
token <- bmr_upload_entry("my_protein.str")
n15hsqc(bmr_ids = token)

## End(Not run)
```

c13hsqc	<i>Simulate a $^1\text{H}-^{13}\text{C}$ HSQC spectrum</i>
---------	---

Description

Equivalent to 'pybmr.Spectra.c13hsqc()'. See [n15hsqc()] for parameter descriptions.

Usage

```
c13hsqc(
  bmrbs_ids = NULL,
  input_file_names = NULL,
  auth_tag = FALSE,
  legend = NULL,
  draw_trace = FALSE,
  peak_list = NULL,
  output_format = "html",
  output_file = NULL,
  output_image_width = 800,
  output_image_height = 600,
  show_visualization = TRUE
)
```

Arguments

bmrbs_ids	BMRB entry ID(s) – integer, character, or vector.
input_file_names	Path(s) to local NMR-STAR ‘.str’ files.
auth_tag	Use ‘Auth_seq_ID’ for sequence numbering.
legend	‘NULL’ (default), ‘“residue”’, or ‘“dataset”’.
draw_trace	Draw lines connecting same-residue peaks across datasets.
peak_list	Path to a 2-column CSV file of unassigned peaks (‘H_ppm’, ‘N_ppm’) to overlay.
output_format	‘“html”’ (default), ‘“png”’, ‘“jpg”’, ‘“pdf”’, ‘“svg”’, or ‘“webp”’.
output_file	File path to save the visualization (optional).
output_image_width, output_image_height	Image dimensions in pixels.
show_visualization	Open in browser / display inline. Default ‘TRUE’.

Value

Invisibly, a list with the simulated peak list.

Examples

```
## Not run:
c13hsqc(bmrbs_ids = 15060, legend = "residue")

## End(Not run)
```

conditional_cs_hist	<i>Plot a conditional chemical shift histogram</i>
---------------------	--

Description

Shows the CS distribution of 'atom' in 'residue' before and after filtering by known chemical shifts of other atoms in the same residue. Mirrors 'pybmrh.Histogram.conditional_hist()'.

Usage

```
conditional_cs_hist(
    residue,
    atom,
    filtering_rules,
    ph_min = NULL,
    ph_max = NULL,
    t_min = NULL,
    t_max = NULL,
    h_tolerance = 0.1,
    c_tolerance = 2,
    n_tolerance = 2,
    standard_amino_acids = TRUE,
    histnorm = NULL,
    plot_type = "histogram",
    output_format = "html",
    output_file = NULL,
    output_image_width = 800,
    output_image_height = 600,
    show_visualization = TRUE
)
```

Arguments

residue	Residue name.
atom	Atom whose distribution to plot.
filtering_rules	Named list of atom = value pairs used to filter, e.g. 'list(CA = 64.5, H = 7.8)'.
ph_min, ph_max, t_min, t_max	Condition filters.
h_tolerance	Tolerance (ppm) for H filters. Default 0.1.
c_tolerance	Tolerance (ppm) for C filters. Default 2.0.
n_tolerance	Tolerance (ppm) for N filters. Default 2.0.
standard_amino_acids	Restrict to standard amino acids. Default TRUE.
histnorm	Normalisation (see [cs_hist()]).

plot_type "histogram" (default), "box", or "violin".
 output_format, output_file, output_image_width, output_image_height,
 show_visualization
 See [cs_hist()].

Value

Invisibly, a list with 'all_values', 'filtered_values', 'labels'.

Examples

```
## Not run:
conditional_cs_hist("SER", "N",
  filtering_rules = list(CA = 55.5, HA = 4.3))

## End(Not run)
```

create_2d_peaklist	<i>Build a generic 2D peak list for any two atoms</i>
--------------------	---

Description

Equivalent to 'pybmrB.Spectra.create_2d_peaklist()'.

Usage

```
create_2d_peaklist(
  atom_x,
  atom_y,
  bmrB_ids = NULL,
  input_file_names = NULL,
  auth_tag = FALSE,
  draw_trace = FALSE,
  include_preceding = FALSE,
  include_next = FALSE
)
```

Arguments

atom_x	Atom name for the X axis.
atom_y	Atom name for the Y axis.
bmrB_ids	BMRB entry ID(s) – integer, character, or vector.
input_file_names	Path(s) to local NMR-STAR '.str' files.
auth_tag	Use 'Auth_seq_ID' for sequence numbering.
draw_trace	Draw lines connecting same-residue peaks across datasets.

include_preceding

Include preceding (i-1) residue Y-axis peaks.

include_next

Include following (i+1) residue Y-axis peaks.

Value

Same structure as [create_n15hsqc_peaklist()].

create_c13hsqc_peaklist

Build a 1H-13C HSQC peak list

Description

Equivalent to 'pybmrB.Spectra.create_c13hsqc_peaklist()'.

Usage

```
create_c13hsqc_peaklist(
    bmrB_ids = NULL,
    input_file_names = NULL,
    auth_tag = FALSE,
    draw_trace = FALSE
)
```

Arguments

bmrB_ids BMRB entry ID(s) – integer, character, or vector.

input_file_names

Path(s) to local NMR-STAR '.str' files.

auth_tag

Use 'Auth_seq_ID' for sequence numbering.

draw_trace

Draw lines connecting same-residue peaks across datasets.

Value

Same structure as [create_n15hsqc_peaklist()].

`create_n15hsqc_peaklist`*Build a 1H-15N HSQC peak list*

Description

Extracts backbone amide (and optionally sidechain NH) chemical shifts from BMRB entries / NMR-STAR files and returns the 2D peak coordinates. Equivalent to `'pybmr.Spectra.create_n15hsqc_peaklist()'`.

Usage

```
create_n15hsqc_peaklist(  
    bmr_ids = NULL,  
    input_file_names = NULL,  
    auth_tag = FALSE,  
    draw_trace = FALSE,  
    include_sidechain = TRUE  
)
```

Arguments

<code>bmr_ids</code>	BMRB entry ID(s) – integer, character, or vector.
<code>input_file_names</code>	Path(s) to local NMR-STAR <code>.str</code> files.
<code>auth_tag</code>	Use <code>'Auth_seq_ID'</code> for sequence numbering.
<code>draw_trace</code>	Draw lines connecting same-residue peaks across datasets.
<code>include_sidechain</code>	Include sidechain NH2 peaks (ASN/GLN/ARG/TRP/HIS).

Value

A list with elements: `'x'` (H ppm), `'y'` (N ppm), `'dataset'`, `'residue'`, `'info'`, `'seq_id'`, `'cs_track'` (if `'draw_trace = TRUE'`).

`create_tocsy_peaklist` *Build a 1H-1H TOCSY peak list*

Description

Pairs all protons within each residue (full spin-system). Both diagonal and off-diagonal peaks are included. Equivalent to `'pybmr.Spectra.create_tocsy_peaklist()'`.

Usage

```
create_tocsy_peaklist(
    bmrB_ids = NULL,
    input_file_names = NULL,
    auth_tag = FALSE,
    draw_trace = FALSE
)
```

Arguments

`bmrB_ids` BMRB entry ID(s) – integer, character, or vector.

`input_file_names` Path(s) to local NMR-STAR ‘.str’ files.

`auth_tag` Use ‘Auth_seq_ID’ for sequence numbering.

`draw_trace` Draw lines connecting same-residue peaks across datasets.

Value

Same structure as `[create_n15hsqc_peaklist()]`.

<code>cs_from_bmrB</code>	<i>Extract chemical shifts from BMRB database entries</i>
---------------------------	---

Description

Fetches assigned chemical shift data for one or more BMRB entries. Uses the same zlib-compressed JSON endpoint as PyBMRB / pynmrstar. Mirrors ‘pybmrB.ChemicalShift.from_bmrB()’.

Usage

```
cs_from_bmrB(bmrB_ids, auth_tag = FALSE)
```

Arguments

`bmrB_ids` A single BMRB entry ID or a vector of IDs.

`auth_tag` Logical. Use ‘Auth_seq_ID’ for sequence numbering. Default FALSE.

Value

A nested named list: ‘list(dataset_id = list(chain = list(seq_id = list(atom = cs_value), seq_ids = integer_vector)))’.

Examples

```
## Not run:
cs <- cs_from_bmrB(15060)
cs_peek(cs)
cs_from_bmrB(c(17076, 17077))

## End(Not run)
```

cs_from_file	<i>Extract chemical shifts from local NMR-STAR files</i>
--------------	--

Description

Mirrors 'pybmrB.ChemicalShift.from_file()'.

Usage

```
cs_from_file(file_paths, auth_tag = FALSE, data_set_ids = NULL)
```

Arguments

file_paths	Character vector of NMR-STAR file paths.
auth_tag	Logical. Use 'Auth_seq_ID'. Default FALSE.
data_set_ids	Optional character vector of dataset labels.

Value

Same nested-list structure as [cs_from_bmrB()].

Examples

```
## Not run:
cs <- cs_from_file("my_protein.str")

## End(Not run)
```

cs_hist

*Plot a chemical shift distribution histogram***Description**

Fetches database-wide chemical shift data and renders an interactive distribution plot. Mirrors `pybmr.Histogram.hist()`.

Usage

```
cs_hist(
    residue = NULL,
    atom = NULL,
    list_of_atoms = NULL,
    filtered = TRUE,
    sd_limit = 10,
    ambiguity = "*",
    ph_min = NULL,
    ph_max = NULL,
    t_min = NULL,
    t_max = NULL,
    standard_amino_acids = TRUE,
    histnorm = NULL,
    plot_type = "histogram",
    output_format = "html",
    output_file = NULL,
    output_image_width = 800,
    output_image_height = 600,
    show_visualization = TRUE
)
```

Arguments

residue	Residue name (IUPAC 3-letter). Use "*" for any.
atom	Atom name (e.g. "CA", "HB*", "*").
list_of_atoms	Optional character vector of "RES-ATOM" pairs (e.g. <code>'c("ALA-CB","CYS-N")'</code>). Overrides residue/atom when supplied.
filtered	Remove outliers. Default TRUE.
sd_limit	SD factor for outlier removal. Default 10.
ambiguity	Ambiguity code filter ("*" = no filter).
ph_min, ph_max	pH range filter.
t_min, t_max	Temperature range filter (Kelvin).
standard_amino_acids	Restrict to standard amino acids. Default TRUE.

histnorm NULL (count), "percent", "probability", or "probability density".
 plot_type "histogram" (default), "box", or "violin".
 output_format "html" (default), "png", "jpg", "pdf", "svg", "webp".
 output_file File path to save the plot (optional).
 output_image_width, output_image_height
 Image size in pixels.
 show_visualization
 Display the figure. Default TRUE.

Value

Invisibly, a list with elements 'values' and 'labels'.

Examples

```
## Not run:
cs_hist("ALA", "CA")
cs_hist(list_of_atoms = c("ALA-CB", "GLY-CA", "SER-CB"))
cs_hist("ALA", "CA", histnorm = "probability density",
        plot_type = "violin")

## End(Not run)
```

cs_hist2d	<i>Plot a 2D chemical shift correlation map</i>
-----------	---

Description

Mirrors 'pybmr.b.Histogram.hist2d()'.

Usage

```
cs_hist2d(
  residue,
  atom1,
  atom2,
  filtered = TRUE,
  sd_limit = 10,
  ambiguity1 = "*",
  ambiguity2 = "*",
  ph_min = NULL,
  ph_max = NULL,
  t_min = NULL,
  t_max = NULL,
  histnorm = NULL,
  plot_type = "heatmap",
  output_format = "html",
```

```

    output_file = NULL,
    output_image_width = 800,
    output_image_height = 600,
    show_visualization = TRUE
)

```

Arguments

residue	Residue name.
atom1	First atom (X axis).
atom2	Second atom (Y axis).
filtered, sd_limit	See [cs_hist()].
ambiguity1, ambiguity2	Per-atom ambiguity filters.
ph_min, ph_max, t_min, t_max	Condition filters.
histnorm	Normalisation (see [cs_hist()]).
plot_type	"heatmap" (default) or "contour".
output_format, output_file, output_image_width, output_image_height, show_visualization	See [cs_hist()].

Value

Invisibly, a list with elements 'atom1' and 'atom2'.

Examples

```

## Not run:
cs_hist2d("CYS", "CB", "N")
cs_hist2d("ALA", "CA", "CB", plot_type = "contour")

## End(Not run)

```

cs_peek

Peek at a nested CS structure

Description

Reports the first few residues of each chain with message(), so the output can be silenced with suppressMessages().

Usage

```
cs_peek(cs_data, n_res = 5L)
```

Arguments

cs_data Output of [cs_from_bmrB()] or [cs_from_file()].
n_res Number of residues to show per chain.

Value

cs_data, invisibly.

Examples

```
## Not run: cs <- cs_from_bmrB(15060); cs_peek(cs)
```

cs_stats	<i>Compute summary statistics for a set of chemical shifts</i>
----------	--

Description

Compute summary statistics for a set of chemical shifts

Usage

```
cs_stats(x)
```

Arguments

x Numeric vector of chemical shift values.

Value

A named numeric vector: n, mean, sd, median, min, max.

Examples

```
cs_stats(c(55.1, 55.3, 56.0, 54.8))
```

cs_summary	<i>Summarise a nested chemical shift list</i>
------------	---

Description

Builds a tidy summary of datasets, chains, and atom coverage. The summary is returned rather than printed, so it prints automatically at the console and can also be assigned and reused.

Usage

```
cs_summary(cs_data)
```

Arguments

cs_data Nested list from [cs_from_bmrbs()] or [cs_from_file()].

Value

A data.frame with one row per dataset and chain.

Examples

```
## Not run: cs <- cs_from_bmrbs(15060); cs_summary(cs)
```

cs_table	<i>Get a flat data.frame of chemical shifts for one or more BMRB entries</i>
----------	--

Description

Get a flat data.frame of chemical shifts for one or more BMRB entries

Usage

```
cs_table(bmrbs_ids, auth_tag = FALSE)
```

Arguments

bmrbs_ids A single BMRB entry ID or a vector of IDs.
auth_tag Logical. Use 'Auth_seq_ID' for sequence numbering. Default FALSE.

Value

A data.frame suitable for use with ggplot2 or dplyr.

Examples

```
## Not run: df <- cs_table(c(15060, 17076))
```

`cs_to_df`*Convert a nested CS list to a tidy data.frame*

Description

Convert a nested CS list to a tidy data.frame

Usage

```
cs_to_df(cs_data)
```

Arguments

`cs_data` Nested list from `[cs_from_bmrbs()]` or `[cs_from_file()]`.

Value

A data.frame with columns Dataset, Chain, Seq_ID, Atom_ID, Val.

Examples

```
## Not run: cs <- cs_from_bmrbs(15060); df <- cs_to_df(cs)
```

`export_peak_list`*Export a peak list to CSV or Sparky format*

Description

Converts the output of any 'create_*_peaklist()' function to a file or a data.frame. Equivalent to 'pybmrbs.Spectra.export_peak_list()'.

Usage

```
export_peak_list(  
  peak_list,  
  output_file_name = NULL,  
  output_format = "csv",  
  include_side_chain = TRUE  
)
```

Arguments

peak_list List returned by any 'create_*_peaklist()' function.
 output_file_name Path to write the output file. 'NULL' returns only the data.frame without writing to disk.
 output_format "csv" (default) or "sparky".
 include_side_chain Include sidechain peaks. Default 'TRUE'.

Value

Invisibly, a data.frame with the exported peak list.

Examples

```
## Not run:
pl <- create_n15hsqc_peaklist(bmrbs_ids = 15060)
export_peak_list(pl, "peaks.csv", output_format = "csv")
export_peak_list(pl, "peaks.sparky", output_format = "sparky")

## End(Not run)
```

filter_cs_outliers	<i>Remove outliers from a numeric vector</i>
--------------------	--

Description

Remove outliers from a numeric vector

Usage

```
filter_cs_outliers(x, sd_limit = 10)
```

Arguments

x Numeric vector.
 sd_limit Number of standard deviations beyond which to remove.

Value

Numeric vector with outliers removed.

Examples

```
filter_cs_outliers(c(52, 55, 56, 54, 300), sd_limit = 2)
```

generic_2d

*Plot a generic 2D NMR correlation spectrum***Description**

Generates a 2D spectrum for any two atom types. Supports sequence-walk tracing, preceding/next-residue peaks, and all the same overlay options as the other spectrum functions. Equivalent to `pybmrB.Spectra.generic_2d()`.

Usage

```
generic_2d(
    atom_x,
    atom_y,
    bmrB_ids = NULL,
    input_file_names = NULL,
    auth_tag = FALSE,
    legend = NULL,
    draw_trace = FALSE,
    peak_list = NULL,
    include_preceding = FALSE,
    include_next = FALSE,
    seq_walk = FALSE,
    full_walk = FALSE,
    output_format = "html",
    output_file = NULL,
    output_image_width = 800,
    output_image_height = 600,
    show_visualization = TRUE
)
```

Arguments

<code>atom_x</code>	Atom name for the X axis (IUPAC, e.g. <code>"N"</code> , <code>"CA"</code>).
<code>atom_y</code>	Atom name for the Y axis.
<code>bmrB_ids</code>	BMRB entry ID(s) – integer, character, or vector.
<code>input_file_names</code>	Path(s) to local NMR-STAR <code>.str</code> files.
<code>auth_tag</code>	Use <code>'Auth_seq_ID'</code> for sequence numbering.
<code>legend</code>	<code>'NULL'</code> (default), <code>"residue"</code> , or <code>"dataset"</code> .
<code>draw_trace</code>	Draw lines connecting same-residue peaks across datasets.
<code>peak_list</code>	Path to a 2-column CSV file of unassigned peaks (<code>'H_ppm'</code> , <code>'N_ppm'</code>) to overlay.

include_preceding	Include chemical shifts from the preceding (i-1) residue on the Y axis. Default 'FALSE'.
include_next	Include chemical shifts from the following (i+1) residue on the Y axis. Default 'FALSE'.
seq_walk	Draw a trace connecting sequential i->i+/-1 pairs for continuous sequence segments. Default 'FALSE'.
full_walk	Like 'seq_walk' but ignores missing residues. Default 'FALSE'.
output_format	"html" (default), "png", "jpg", "pdf", "svg", or "webp".
output_file	File path to save the visualization (optional).
output_image_width, output_image_height	Image dimensions in pixels.
show_visualization	Open in browser / display inline. Default 'TRUE'.

Value

Invisibly, the peak list.

Examples

```
## Not run:
generic_2d("N", "CA", bmr_ids = 15000, legend = "residue")
generic_2d("N", "CA", bmr_ids = 15000, include_next = TRUE,
           seq_walk = TRUE)

## End(Not run)
```

get_2d_cs_data	<i>Fetch paired 2D chemical shift data for two atoms in the same residue</i>
----------------	--

Description

Mirrors 'pybmr.ChemicalShiftStatistics.get_2d_chemical_shifts()'.

Usage

```
get_2d_cs_data(
  residue,
  atom1,
  atom2,
  filtered = TRUE,
  sd_limit = 10,
  ambiguity1 = "*",
  ambiguity2 = "*",
  ph_min = NULL,
```

```

    ph_max = NULL,
    t_min = NULL,
    t_max = NULL
  )

```

Arguments

residue	Residue name (IUPAC 3-letter).
atom1	First atom (X axis).
atom2	Second atom (Y axis).
filtered, sd_limit	See [get_cs_data()].
ambiguity1, ambiguity2	Per-atom ambiguity filters.
ph_min, ph_max, t_min, t_max	Condition filters.

Value

Named list with 'atom1' and 'atom2' numeric vectors.

Examples

```
## Not run: paired <- get_2d_cs_data("ALA", "CA", "CB")
```

get_cs_data

Fetch chemical shift data from the BMRB database

Description

Downloads chemical shifts for the given residue and atom combination from the BMRB database. Mirrors 'pybmr.ChemicalShiftStatistics.get_data()'.

Usage

```

get_cs_data(
  residue = "*",
  atom = "*",
  filtered = TRUE,
  sd_limit = 10,
  ambiguity = "*",
  ph_min = NULL,
  ph_max = NULL,
  t_min = NULL,
  t_max = NULL,
  standard_amino_acids = TRUE,
  database = "macromolecules"
)

```

Arguments

residue	Residue in IUPAC 3-letter format (e.g. "ALA"). "*" = any.
atom	Atom name (e.g. "CA", "HB*"). "*" = any.
filtered	Remove outliers beyond sd_limit * SD. Default TRUE.
sd_limit	SD factor for outlier removal. Default 10.
ambiguity	Ambiguity code filter ("*" = no filter; 1 = unambiguous).
ph_min, ph_max	pH range filter (optional).
t_min, t_max	Temperature range in Kelvin (optional).
standard_amino_acids	Restrict to standard amino acids. Default TRUE.
database	"macromolecules" (default) or "metabolomics".

Value

A data.frame with columns Val, Comp_ID, Atom_ID, Ambiguity_code, Entry_ID, Comp_index_ID, pH, Temperature_K and others.

Examples

```
## Not run:
df <- get_cs_data("ALA", "CA")
df <- get_cs_data("*", "HB*")

## End(Not run)
```

get_cs_from_bmrdb	<i>Fetch raw BMRB chemical shift data (no outlier filtering)</i>
-------------------	--

Description

Mirrors 'pybmr.ChemicalShiftStatistics.get_data_from_bmrdb()'.

Usage

```
get_cs_from_bmrdb(
  residue = "*",
  atom = "*",
  list_of_atoms = NULL,
  ambiguity = "*",
  ph_min = NULL,
  ph_max = NULL,
  t_min = NULL,
  t_max = NULL,
  standard_amino_acids = TRUE,
  database = "macromolecules"
)
```

Arguments

residue	Residue in IUPAC 3-letter format (e.g. "ALA"). "*" = any.
atom	Atom name (e.g. "CA", "HB*"). "*" = any.
list_of_atoms	Optional "RES-ATOM" vector, e.g. 'c("ALA-CB","GLY-CA")'.
ambiguity	Ambiguity code filter ("*" = no filter; 1 = unambiguous).
ph_min, ph_max	pH range filter (optional).
t_min, t_max	Temperature range in Kelvin (optional).
standard_amino_acids	Restrict to standard amino acids. Default TRUE.
database	"macromolecules" (default) or "metabolomics".

Value

A data.frame of raw chemical shift records.

Examples

```
## Not run:
df <- get_cs_from_bmrdb("ALA", "CB")
df2 <- get_cs_from_bmrdb(list_of_atoms = c("ALA-CB", "GLY-CA"))

## End(Not run)
```

n15hsqc

*Simulate a $^1\text{H}-^{15}\text{N}$ HSQC spectrum***Description**

Plots an interactive ^1H - ^{15}N HSQC spectrum for one or more BMRB entries and/or NMR-STAR files. Overlay multiple datasets as scatter plots; optionally draw trace lines connecting peaks from the same residue position across datasets. Equivalent to 'pybmrdb.Spectra.n15hsqc()'.

Usage

```
n15hsqc(
  bmrdb_ids = NULL,
  input_file_names = NULL,
  auth_tag = FALSE,
  legend = NULL,
  draw_trace = FALSE,
  include_sidechain = TRUE,
  peak_list = NULL,
  output_format = "html",
  output_file = NULL,
  output_image_width = 800,
  output_image_height = 600,
  show_visualization = TRUE
)
```

Arguments

bmrbs_ids	BMRB entry ID(s) – integer, character, or vector.
input_file_names	Path(s) to local NMR-STAR ‘.str’ files.
auth_tag	Use ‘Auth_seq_ID’ for sequence numbering.
legend	‘NULL’ (default), ‘“residue”’, or ‘“dataset”’.
draw_trace	Draw lines connecting same-residue peaks across datasets.
include_sidechain	Include sidechain NH2 peaks (ASN/GLN/ARG/TRP/HIS).
peak_list	Path to a 2-column CSV file of unassigned peaks (‘H_ppm’, ‘N_ppm’) to overlay.
output_format	‘“html”’ (default), ‘“png”’, ‘“jpg”’, ‘“pdf”’, ‘“svg”’, or ‘“webp”’.
output_file	File path to save the visualization (optional).
output_image_width, output_image_height	Image dimensions in pixels.
show_visualization	Open in browser / display inline. Default ‘TRUE’.

Value

Invisibly, a list with elements ‘x’ (H ppm), ‘y’ (N ppm), ‘dataset’, ‘residue’, ‘info’, and (when ‘draw_trace = TRUE’) ‘cs_track’.

Examples

```
## Not run:
# Single entry
n15hsqc(bmrbs_ids = 15060, legend = "residue")

# Compare two entries with trace lines
n15hsqc(bmrbs_ids = c(17076, 17077), legend = "dataset", draw_trace = TRUE)

# Overlay user's own NMR-STAR file with BMRB entry
n15hsqc(bmrbs_ids = 15060, input_file_names = "MyData.str",
        legend = "dataset")

## End(Not run)
```

RBMRB_version

Get the installed RBMRB version

Description

Returns the version of the installed RBMRB package as a string.

Usage

```
RBMRB_version()
```

Value

A character string with the package version.

Examples

```
RBMRB_version()
```

```
standard_amino_acids
```

List the 20 standard amino acid codes

Description

List the 20 standard amino acid codes

Usage

```
standard_amino_acids()
```

Value

Character vector of 3-letter amino acid codes.

Examples

```
standard_amino_acids()
```

```
standard_nucleic_acids
```

List standard nucleic acid residue codes

Description

List standard nucleic acid residue codes

Usage

```
standard_nucleic_acids()
```

Value

Character vector of RNA and DNA residue codes.

Examples

```
standard_nucleic_acids()
```

tocsy

*Simulate a $^1\text{H}-^1\text{H}$ TOCSY spectrum***Description**

Equivalent to `pybmrB.Spectra.tocsy()`. See `[n15hsqc()]` for shared parameter descriptions.

Usage

```
tocsy(
    bmrB_ids = NULL,
    input_file_names = NULL,
    auth_tag = FALSE,
    legend = NULL,
    draw_trace = FALSE,
    peak_list = NULL,
    output_format = "html",
    output_file = NULL,
    output_image_width = 800,
    output_image_height = 600,
    show_visualization = TRUE
)
```

Arguments

<code>bmrB_ids</code>	BMRB entry ID(s) – integer, character, or vector.
<code>input_file_names</code>	Path(s) to local NMR-STAR ‘.str’ files.
<code>auth_tag</code>	Use ‘Auth_seq_ID’ for sequence numbering.
<code>legend</code>	‘NULL’ (default), ‘“residue”’, or ‘“dataset”’.
<code>draw_trace</code>	Draw lines connecting same-residue peaks across datasets.
<code>peak_list</code>	Path to a 2-column CSV file of unassigned peaks (‘H_ppm’, ‘N_ppm’) to overlay.
<code>output_format</code>	“html” (default), “png”, “jpg”, “pdf”, “svg”, or “webp”.
<code>output_file</code>	File path to save the visualization (optional).
<code>output_image_width, output_image_height</code>	Image dimensions in pixels.
<code>show_visualization</code>	Open in browser / display inline. Default ‘TRUE’.

Value

Invisibly, a list with the simulated peak list.

Examples

```
## Not run:
tocsy(bmrbs_ids = 15060, legend = "residue")
tocsy(bmrbs_ids = c(17074, 17076, 17077), legend = "dataset",
      draw_trace = TRUE)

## End(Not run)
```

Index

[bmr_b_citation](#), [3](#)
[bmr_b_debug_entry](#), [3](#)
[bmr_b_fetch_entry](#), [4](#)
[bmr_b_from_pdb](#), [4](#)
[bmr_b_list_entries](#), [5](#)
[bmr_b_pdb_ids](#), [6](#)
[bmr_b_search](#), [6](#)
[bmr_b_status](#), [7](#)
[bmr_b_test](#), [7](#)
[bmr_b_upload_entry](#), [8](#)

[c13hsqc](#), [8](#)
[conditional_cs_hist](#), [10](#)
[create_2d_peaklist](#), [11](#)
[create_c13hsqc_peaklist](#), [12](#)
[create_n15hsqc_peaklist](#), [13](#)
[create_tocsy_peaklist](#), [13](#)
[cs_from_bmr_b](#), [3](#), [14](#)
[cs_from_file](#), [15](#)
[cs_hist](#), [16](#)
[cs_hist2d](#), [17](#)
[cs_peek](#), [18](#)
[cs_stats](#), [19](#)
[cs_summary](#), [20](#)
[cs_table](#), [20](#)
[cs_to_df](#), [21](#)

[export_peak_list](#), [21](#)

[filter_cs_outliers](#), [22](#)

[generic_2d](#), [23](#)
[get_2d_cs_data](#), [24](#)
[get_cs_data](#), [25](#)
[get_cs_from_bmr_b_db](#), [26](#)

[n15hsqc](#), [27](#)

[RBMRB_version](#), [28](#)

[standard_amino_acids](#), [29](#)

[standard_nucleic_acids](#), [29](#)

[tocsy](#), [30](#)