# Package 'hdcuremodels'

December 3, 2025

Title High-Dimensional Cure Models

```
Version 0.0.6
Date 2025-12-01
Description Provides functions for fitting various penalized parametric and semi-parametric mix-
      ture cure models with different penalty functions, testing for a significant cure fraction, and test-
      ing for sufficient follow-up as de-
      scribed in Fu et al (2022)<doi:10.1002/sim.9513> and Archer et al (2024)<doi:10.1186/s13045-
      024-01553-6>. False discovery rate controlled variable selection is provided using model-
      X knock-offs.
License MIT + file LICENSE
Encoding UTF-8
Depends R (>= 4.2.0)
Imports doParallel, flexsurv, flexsurvcure, foreach, ggplot2, ggpubr,
      glmnet, knockoff, mvnfast, parallel, plyr, methods, survival,
      withr
RoxygenNote 7.3.3
Suggests knitr, Rdsdp, rmarkdown, roxygen2, testthat (>= 3.0.0)
VignetteBuilder knitr
LazyData true
URL https://github.com/ropensci/hdcuremodels
BugReports https://github.com/ropensci/hdcuremodels/issues
Config/testthat/edition 3
NeedsCompilation no
Author Han Fu [aut],
      Kellie J. Archer [aut, cre] (ORCID:
       <a href="https://orcid.org/0000-0003-1555-5781">https://orcid.org/0000-0003-1555-5781</a>),
      Tung Lam Nguyen [rev] (Reviewed the package for ROpenSci),
      Panagiotis Papastamoulis [rev] (Reviewed the package for ROpenSci)
Maintainer Kellie J. Archer <archer.43@osu.edu>
Repository CRAN
Date/Publication 2025-12-03 17:50:02 UTC
```

# **Contents**

Index		61
	summary.mixturecure	60
	sufficient_fu_test	59
	print.mixturecure	
	predict.mixturecure	
	plot.mixturecure	
	pediatric_flt3	
	npar_mixturecure	
	nonzerocure_test	
	nobs.mixturecure	
	logLik.mixturecure	
	generate_cure_data	
	formula.mixturecure	
	family.mixturecure	
	dim.mixturecure	
	cv_curegmifs	
	cv_cureem	
	cure_estimate	
	curegmifs	
	cureem	
	concordance_mcm	
	coef.mixturecure	
	auc_mcm	
	amltrain	
	amltest	2

# Description

Duration of complete response for 40 cytogenetically normal AML patients and a subset of 320 transcript expression from RNA-sequencing.

# Usage

amltest

# **Format**

A data frame with 40 rows (subjects) and 322 columns:

cryr duration of complete response in years

**relapse.death** censoring indicator: 1 = relapsed or died; 0 = alive at last follow=up

ENSG0000001561 normalized expression for indicated transcript

ENSG0000005249 normalized expression for indicated transcript ENSG00000006757 normalized expression for indicated transcript **ENSG0000007062** normalized expression for indicated transcript **ENSG0000007968** normalized expression for indicated transcript **ENSG00000008283** normalized expression for indicated transcript ENSG00000008405 normalized expression for indicated transcript **ENSG0000008441** normalized expression for indicated transcript ENSG0000010295 normalized expression for indicated transcript **ENSG0000011028** normalized expression for indicated transcript ENSG0000011198 normalized expression for indicated transcript ENSG0000012779 normalized expression for indicated transcript ENSG00000012817 normalized expression for indicated transcript ENSG00000013306 normalized expression for indicated transcript ENSG00000013725 normalized expression for indicated transcript **ENSG00000018189** normalized expression for indicated transcript ENSG00000022267 normalized expression for indicated transcript ENSG00000023171 normalized expression for indicated transcript ENSG00000023909 normalized expression for indicated transcript ENSG00000029639 normalized expression for indicated transcript ENSG00000047634 normalized expression for indicated transcript ENSG00000049192 normalized expression for indicated transcript ENSG00000053524 normalized expression for indicated transcript ENSG00000058056 normalized expression for indicated transcript ENSG00000060138 normalized expression for indicated transcript ENSG00000061918 normalized expression for indicated transcript ENSG00000065809 normalized expression for indicated transcript ENSG00000065923 normalized expression for indicated transcript ENSG00000068489 normalized expression for indicated transcript ENSG00000069020 normalized expression for indicated transcript ENSG0000070404 normalized expression for indicated transcript ENSG00000071894 normalized expression for indicated transcript ENSG00000072422 normalized expression for indicated transcript ENSG00000073605 normalized expression for indicated transcript ENSG00000076555 normalized expression for indicated transcript ENSG00000080823 normalized expression for indicated transcript ENSG00000089723 normalized expression for indicated transcript ENSG00000090382 normalized expression for indicated transcript

ENSG00000090975	normalized expression for indicated transcript
ENSG0000100068	normalized expression for indicated transcript
ENSG0000100077	normalized expression for indicated transcript
ENSG00000100299	normalized expression for indicated transcript
ENSG0000100376	normalized expression for indicated transcript
ENSG00000100418	normalized expression for indicated transcript
ENSG00000100448	normalized expression for indicated transcript
ENSG00000100596	normalized expression for indicated transcript
ENSG00000100916	normalized expression for indicated transcript
ENSG00000102409	normalized expression for indicated transcript
ENSG00000102760	normalized expression for indicated transcript
ENSG00000104689	normalized expression for indicated transcript
ENSG00000104946	normalized expression for indicated transcript
ENSG00000105518	normalized expression for indicated transcript
ENSG00000105808	normalized expression for indicated transcript
ENSG00000106367	normalized expression for indicated transcript
ENSG00000106526	normalized expression for indicated transcript
ENSG00000106546	normalized expression for indicated transcript
ENSG00000106780	normalized expression for indicated transcript
ENSG00000107104	normalized expression for indicated transcript
ENSG00000107742	normalized expression for indicated transcript
ENSG00000107798	normalized expression for indicated transcript
ENSG00000107816	normalized expression for indicated transcript
ENSG00000107957	normalized expression for indicated transcript
ENSG00000109674	normalized expression for indicated transcript
ENSG00000110076	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000110492	normalized expression for indicated transcript
ENSG00000110799	normalized expression for indicated transcript
ENSG00000111275	normalized expression for indicated transcript
ENSG00000112773	normalized expression for indicated transcript
ENSG00000113504	normalized expression for indicated transcript
ENSG00000114268	normalized expression for indicated transcript
ENSG00000114737	normalized expression for indicated transcript
	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000115457	normalized expression for indicated transcript

ENSG00000115525 normalized expression for indicated transcript ENSG00000116574 normalized expression for indicated transcript **ENSG00000117480** normalized expression for indicated transcript **ENSG00000119280** normalized expression for indicated transcript **ENSG00000120594** normalized expression for indicated transcript ENSG00000120675 normalized expression for indicated transcript ENSG00000120832 normalized expression for indicated transcript ENSG00000120913 normalized expression for indicated transcript **ENSG00000121005** normalized expression for indicated transcript ENSG00000121039 normalized expression for indicated transcript ENSG00000121274 normalized expression for indicated transcript ENSG00000123080 normalized expression for indicated transcript ENSG00000123836 normalized expression for indicated transcript ENSG00000124019 normalized expression for indicated transcript **ENSG00000124882** normalized expression for indicated transcript ENSG00000126822 normalized expression for indicated transcript **ENSG00000127152** normalized expression for indicated transcript ENSG00000129824 normalized expression for indicated transcript ENSG00000130702 normalized expression for indicated transcript ENSG00000131188 normalized expression for indicated transcript ENSG00000131370 normalized expression for indicated transcript ENSG00000132122 normalized expression for indicated transcript ENSG00000132530 normalized expression for indicated transcript ENSG00000132819 normalized expression for indicated transcript ENSG00000132849 normalized expression for indicated transcript ENSG00000133401 normalized expression for indicated transcript ENSG00000133619 normalized expression for indicated transcript ENSG00000134531 normalized expression for indicated transcript ENSG00000134897 normalized expression for indicated transcript ENSG00000135074 normalized expression for indicated transcript ENSG00000135245 normalized expression for indicated transcript ENSG00000135272 normalized expression for indicated transcript ENSG00000135362 normalized expression for indicated transcript ENSG00000135363 normalized expression for indicated transcript ENSG00000135916 normalized expression for indicated transcript ENSG00000136026 normalized expression for indicated transcript ENSG00000136193 normalized expression for indicated transcript

ENSG00000136231	normalized expression for indicated transcript
ENSG00000136997	normalized expression for indicated transcript
ENSG00000137193	normalized expression for indicated transcript
ENSG00000137198	normalized expression for indicated transcript
ENSG00000138722	normalized expression for indicated transcript
ENSG00000139318	normalized expression for indicated transcript
ENSG00000140287	normalized expression for indicated transcript
ENSG00000144036	normalized expression for indicated transcript
ENSG00000144647	normalized expression for indicated transcript
ENSG00000144677	normalized expression for indicated transcript
ENSG00000145476	normalized expression for indicated transcript
ENSG00000145545	normalized expression for indicated transcript
ENSG00000146243	normalized expression for indicated transcript
ENSG00000146373	normalized expression for indicated transcript
ENSG00000147044	normalized expression for indicated transcript
ENSG00000147180	normalized expression for indicated transcript
ENSG00000148444	normalized expression for indicated transcript
ENSG00000148484	normalized expression for indicated transcript
ENSG00000149131	normalized expression for indicated transcript
ENSG00000150760	normalized expression for indicated transcript
ENSG00000150782	normalized expression for indicated transcript
ENSG00000151135	normalized expression for indicated transcript
ENSG00000151208	normalized expression for indicated transcript
ENSG00000151458	normalized expression for indicated transcript
ENSG00000152409	normalized expression for indicated transcript
ENSG00000152580	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000152778	normalized expression for indicated transcript
ENSG00000153563	normalized expression for indicated transcript
ENSG00000154217	normalized expression for indicated transcript
ENSG00000154743	normalized expression for indicated transcript
ENSG00000154760	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000157873	normalized expression for indicated transcript

ENSG00000157978	normalized expression for indicated transcript
ENSG00000158691	normalized expression for indicated transcript
ENSG00000159339	normalized expression for indicated transcript
ENSG00000159403	normalized expression for indicated transcript
ENSG00000159788	normalized expression for indicated transcript
ENSG00000160685	normalized expression for indicated transcript
ENSG00000160781	normalized expression for indicated transcript
ENSG00000161509	normalized expression for indicated transcript
ENSG00000162433	normalized expression for indicated transcript
ENSG00000162614	normalized expression for indicated transcript
ENSG00000162676	normalized expression for indicated transcript
ENSG00000163412	normalized expression for indicated transcript
ENSG00000163702	normalized expression for indicated transcript
ENSG00000163814	normalized expression for indicated transcript
ENSG00000164086	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000164442	normalized expression for indicated transcript
ENSG00000165272	normalized expression for indicated transcript
ENSG00000166165	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000166987	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000170522	normalized expression for indicated transcript

ENSG00000170909	normalized expression for indicated transcript
ENSG00000171121	normalized expression for indicated transcript
ENSG00000171222	normalized expression for indicated transcript
ENSG00000171476	normalized expression for indicated transcript
ENSG00000171813	normalized expression for indicated transcript
ENSG00000171962	normalized expression for indicated transcript
ENSG00000172197	normalized expression for indicated transcript
ENSG00000172236	normalized expression for indicated transcript
ENSG00000173083	normalized expression for indicated transcript
ENSG00000173530	normalized expression for indicated transcript
ENSG00000173926	normalized expression for indicated transcript
ENSG00000174059	normalized expression for indicated transcript
ENSG00000174080	normalized expression for indicated transcript
ENSG00000174130	normalized expression for indicated transcript
ENSG00000174738	normalized expression for indicated transcript
ENSG00000175265	normalized expression for indicated transcript
ENSG00000175352	normalized expression for indicated transcript
ENSG00000176597	normalized expression for indicated transcript
ENSG00000179222	normalized expression for indicated transcript
ENSG00000179630	normalized expression for indicated transcript
ENSG00000179639	normalized expression for indicated transcript
ENSG00000179820	normalized expression for indicated transcript
ENSG00000180096	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000180902	normalized expression for indicated transcript
	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000182871	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000185710	normalized expression for indicated transcript

ENSG00000185883 normalized expression for indicated transcript ENSG00000185986 normalized expression for indicated transcript **ENSG00000186130** normalized expression for indicated transcript **ENSG00000186854** normalized expression for indicated transcript **ENSG00000187010** normalized expression for indicated transcript **ENSG00000187627** normalized expression for indicated transcript **ENSG00000187653** normalized expression for indicated transcript ENSG00000187837 normalized expression for indicated transcript **ENSG00000188002** normalized expression for indicated transcript ENSG00000188107 normalized expression for indicated transcript ENSG00000188211 normalized expression for indicated transcript ENSG00000188636 normalized expression for indicated transcript ENSG00000188738 normalized expression for indicated transcript ENSG00000188856 normalized expression for indicated transcript **ENSG00000189164** normalized expression for indicated transcript ENSG00000189223 normalized expression for indicated transcript **ENSG00000196155** normalized expression for indicated transcript ENSG00000196189 normalized expression for indicated transcript ENSG00000196415 normalized expression for indicated transcript ENSG00000196565 normalized expression for indicated transcript ENSG00000197081 normalized expression for indicated transcript ENSG00000197121 normalized expression for indicated transcript ENSG00000197253 normalized expression for indicated transcript ENSG00000197256 normalized expression for indicated transcript ENSG00000197321 normalized expression for indicated transcript ENSG00000197561 normalized expression for indicated transcript ENSG00000197728 normalized expression for indicated transcript **ENSG00000197860** normalized expression for indicated transcript ENSG00000197937 normalized expression for indicated transcript ENSG00000197951 normalized expression for indicated transcript ENSG00000198743 normalized expression for indicated transcript ENSG00000198838 normalized expression for indicated transcript ENSG00000199347 normalized expression for indicated transcript ENSG00000200243 normalized expression for indicated transcript ENSG00000201801 normalized expression for indicated transcript ENSG00000203872 normalized expression for indicated transcript ENSG00000204172 normalized expression for indicated transcript

ENSG00000205571	normalized expression for indicated transcript
ENSG00000205593	normalized expression for indicated transcript
ENSG00000208772	normalized expression for indicated transcript
ENSG00000213085	normalized expression for indicated transcript
ENSG00000213261	normalized expression for indicated transcript
ENSG00000213626	normalized expression for indicated transcript
ENSG00000213722	normalized expression for indicated transcript
ENSG00000213906	normalized expression for indicated transcript
ENSG00000213967	normalized expression for indicated transcript
ENSG00000214016	normalized expression for indicated transcript
ENSG00000214425	normalized expression for indicated transcript
ENSG00000216316	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000220008	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000223345	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000224080	normalized expression for indicated transcript
	normalized expression for indicated transcript normalized expression for indicated transcript
	•
E/15G00000244405	normalized expression for indicated transcript

amItrain 11

ENSG00000247627 normalized expression for indicated transcript ENSG00000249592 normalized expression for indicated transcript ENSG00000250116 normalized expression for indicated transcript ENSG00000250251 normalized expression for indicated transcript ENSG00000251079 normalized expression for indicated transcript ENSG00000253210 normalized expression for indicated transcript ENSG00000253276 normalized expression for indicated transcript **ENSG00000254415** normalized expression for indicated transcript **ENSG00000259276** normalized expression for indicated transcript ENSG00000260727 normalized expression for indicated transcript ENSG00000261377 normalized expression for indicated transcript ENSG00000264885 normalized expression for indicated transcript ENSG00000264895 normalized expression for indicated transcript **ENSG00000267136** normalized expression for indicated transcript ENSG00000267551 normalized expression for indicated transcript **ENSG00000267702** normalized expression for indicated transcript ENSG00000268001 normalized expression for indicated transcript ENSG00000268573 normalized expression for indicated transcript ENSG00000270554 normalized expression for indicated transcript ENSG00000270562 normalized expression for indicated transcript ENSG00000271646 normalized expression for indicated transcript ENSG00000273018 normalized expression for indicated transcript ENSG00000273033 normalized expression for indicated transcript

## Source

doi:10.1186/s13045-024-01553-6

amltrain

AML training data

#### **Description**

Duration of complete response for 306 cytogenetically normal AML patients and a subset of 320 transcript expression from RNA-sequencing.

#### Usage

#### **Format**

A data frame with 306 rows (subjects) and 322 columns:

cryr duration of complete response in years

**relapse.death** censoring indicator: 1 = relapsed or died; 0 = alive at last follow=up

ENSG00000001561 normalized expression for indicated transcript

ENSG0000005249 normalized expression for indicated transcript

ENSG0000006757 normalized expression for indicated transcript

ENSG0000007062 normalized expression for indicated transcript

ENSG0000007968 normalized expression for indicated transcript

ENSG00000008283 normalized expression for indicated transcript

ENSG00000008405 normalized expression for indicated transcript

ENSG0000008441 normalized expression for indicated transcript

ENSG0000010295 normalized expression for indicated transcript

ENSG0000011028 normalized expression for indicated transcript

ENSG0000011198 normalized expression for indicated transcript

ENSG00000012779 normalized expression for indicated transcript

ENSG00000012817 normalized expression for indicated transcript

ENSG0000013306 normalized expression for indicated transcript

ENSG0000013725 normalized expression for indicated transcript

ENSG00000018189 normalized expression for indicated transcript

ENSG00000022267 normalized expression for indicated transcript

ENSG00000023171 normalized expression for indicated transcript

ENSG00000023909 normalized expression for indicated transcript

ENSG00000029639 normalized expression for indicated transcript

ENSG0000047634 normalized expression for indicated transcript

ENSG00000049192 normalized expression for indicated transcript

**ENSG00000053524** normalized expression for indicated transcript

ENSG00000058056 normalized expression for indicated transcript

ENSG00000060138 normalized expression for indicated transcript

ENSG00000061918 normalized expression for indicated transcript

ENSG00000065809 normalized expression for indicated transcript

ENSG00000065923 normalized expression for indicated transcript

ENSG00000068489 normalized expression for indicated transcript

ENSG00000069020 normalized expression for indicated transcript

ENSG0000070404 normalized expression for indicated transcript

ENSG0000071894 normalized expression for indicated transcript

ENSG0000072422 normalized expression for indicated transcript

ENSC0000073605	normalized expression for indicated transcript
	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000100376	normalized expression for indicated transcript
ENSG00000100418	normalized expression for indicated transcript
ENSG00000100448	normalized expression for indicated transcript
ENSG00000100596	normalized expression for indicated transcript
ENSG00000100916	normalized expression for indicated transcript
ENSG00000102409	normalized expression for indicated transcript
ENSG00000102760	normalized expression for indicated transcript
ENSG00000104689	normalized expression for indicated transcript
ENSG00000104946	normalized expression for indicated transcript
ENSG00000105518	normalized expression for indicated transcript
ENSG00000105808	normalized expression for indicated transcript
ENSG00000106367	normalized expression for indicated transcript
ENSG00000106526	normalized expression for indicated transcript
ENSG00000106546	normalized expression for indicated transcript
ENSG00000106780	normalized expression for indicated transcript
ENSG00000107104	normalized expression for indicated transcript
ENSG00000107742	normalized expression for indicated transcript
ENSG00000107798	normalized expression for indicated transcript
ENSG00000107816	normalized expression for indicated transcript
ENSG00000107957	normalized expression for indicated transcript
ENSG00000109674	normalized expression for indicated transcript
ENSG00000110076	normalized expression for indicated transcript
ENSG00000110237	normalized expression for indicated transcript
	1

ENSG00000114268	normalized expression for indicated transcript
ENSG00000114737	normalized expression for indicated transcript
ENSG00000115183	normalized expression for indicated transcript
ENSG00000115414	normalized expression for indicated transcript
ENSG00000115457	normalized expression for indicated transcript
ENSG00000115525	normalized expression for indicated transcript
ENSG00000116574	normalized expression for indicated transcript
ENSG00000117480	normalized expression for indicated transcript
ENSG00000119280	normalized expression for indicated transcript
ENSG00000120594	normalized expression for indicated transcript
ENSG00000120675	normalized expression for indicated transcript
ENSG00000120832	normalized expression for indicated transcript
ENSG00000120913	normalized expression for indicated transcript
ENSG00000121005	normalized expression for indicated transcript
ENSG00000121039	normalized expression for indicated transcript
ENSG00000121274	normalized expression for indicated transcript
ENSG00000123080	normalized expression for indicated transcript
ENSG00000123836	normalized expression for indicated transcript
ENSG00000124019	normalized expression for indicated transcript
ENSG00000124882	normalized expression for indicated transcript
ENSG00000126822	normalized expression for indicated transcript
ENSG00000127152	normalized expression for indicated transcript
ENSG00000129824	normalized expression for indicated transcript
ENSG00000130702	normalized expression for indicated transcript
ENSG00000131188	normalized expression for indicated transcript
ENSG00000131370	normalized expression for indicated transcript
ENSG00000132122	normalized expression for indicated transcript
ENSG00000132530	normalized expression for indicated transcript
ENSG00000132819	normalized expression for indicated transcript
ENSG00000132849	normalized expression for indicated transcript
ENSG00000133401	normalized expression for indicated transcript
ENSG00000133619	normalized expression for indicated transcript
ENSG00000134531	normalized expression for indicated transcript
ENSG00000134897	normalized expression for indicated transcript
ENSG00000135074	normalized expression for indicated transcript
ENSG00000135245	normalized expression for indicated transcript
ENSG00000135272	normalized expression for indicated transcript

ENSG00000135362	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000148444	normalized expression for indicated transcript
ENSG00000148484	normalized expression for indicated transcript
ENSG00000149131	normalized expression for indicated transcript
ENSG00000150760	normalized expression for indicated transcript
ENSG00000150782	normalized expression for indicated transcript
ENSG00000151135	normalized expression for indicated transcript
ENSG00000151208	normalized expression for indicated transcript
ENSG00000151458	normalized expression for indicated transcript
ENSG00000152409	normalized expression for indicated transcript
ENSG00000152580	normalized expression for indicated transcript
ENSG00000152767	normalized expression for indicated transcript
ENSG00000152778	normalized expression for indicated transcript
ENSG00000153563	normalized expression for indicated transcript
ENSG00000154217	normalized expression for indicated transcript
ENSG00000154743	normalized expression for indicated transcript
ENSG00000154760	normalized expression for indicated transcript

ENSG00000154874	normalized expression for indicated transcript
ENSG00000156381	normalized expression for indicated transcript
ENSG00000157107	normalized expression for indicated transcript
ENSG00000157240	normalized expression for indicated transcript
ENSG00000157873	normalized expression for indicated transcript
ENSG00000157978	normalized expression for indicated transcript
ENSG00000158691	normalized expression for indicated transcript
ENSG00000159339	normalized expression for indicated transcript
ENSG00000159403	normalized expression for indicated transcript
ENSG00000159788	normalized expression for indicated transcript
ENSG00000160685	normalized expression for indicated transcript
ENSG00000160781	normalized expression for indicated transcript
ENSG00000161509	normalized expression for indicated transcript
ENSG00000162433	normalized expression for indicated transcript
ENSG00000162614	normalized expression for indicated transcript
ENSG00000162676	normalized expression for indicated transcript
ENSG00000163412	normalized expression for indicated transcript
ENSG00000163702	normalized expression for indicated transcript
ENSG00000163814	normalized expression for indicated transcript
ENSG00000164086	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000164442	normalized expression for indicated transcript
ENSG00000165272	normalized expression for indicated transcript
ENSG00000166165	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000168026	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000168502	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000169860	normalized expression for indicated transcript

FNSC00000160001	normalized expression for indicated transcript
	normalized expression for indicated transcript
	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000173083	normalized expression for indicated transcript
	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000174059	normalized expression for indicated transcript
ENSG00000174080	normalized expression for indicated transcript
ENSG00000174130	normalized expression for indicated transcript
ENSG00000174738	normalized expression for indicated transcript
ENSG00000175265	normalized expression for indicated transcript
ENSG00000175352	normalized expression for indicated transcript
ENSG00000176597	normalized expression for indicated transcript
ENSG00000179222	normalized expression for indicated transcript
ENSG00000179630	normalized expression for indicated transcript
ENSG00000179639	normalized expression for indicated transcript
ENSG00000179820	normalized expression for indicated transcript
ENSG00000180096	normalized expression for indicated transcript
ENSG00000180596	normalized expression for indicated transcript
ENSG00000180902	normalized expression for indicated transcript
ENSG00000181104	normalized expression for indicated transcript
ENSG00000182866	normalized expression for indicated transcript
ENSG00000182871	normalized expression for indicated transcript
ENSG00000183087	normalized expression for indicated transcript
ENSG00000183091	normalized expression for indicated transcript
ENSG00000184371	normalized expression for indicated transcript
ENSG00000185129	normalized expression for indicated transcript

ENSG00000185201	normalized expression for indicated transcript
ENSG00000185245	normalized expression for indicated transcript
ENSG00000185291	normalized expression for indicated transcript
ENSG00000185304	normalized expression for indicated transcript
ENSG00000185710	normalized expression for indicated transcript
ENSG00000185883	normalized expression for indicated transcript
ENSG00000185986	normalized expression for indicated transcript
ENSG00000186130	normalized expression for indicated transcript
ENSG00000186854	normalized expression for indicated transcript
ENSG00000187010	normalized expression for indicated transcript
ENSG00000187627	normalized expression for indicated transcript
ENSG00000187653	normalized expression for indicated transcript
ENSG00000187837	normalized expression for indicated transcript
ENSG00000188002	normalized expression for indicated transcript
ENSG00000188107	normalized expression for indicated transcript
ENSG00000188211	normalized expression for indicated transcript
ENSG00000188636	normalized expression for indicated transcript
ENSG00000188738	normalized expression for indicated transcript
ENSG00000188856	normalized expression for indicated transcript
ENSG00000189164	normalized expression for indicated transcript
ENSG00000189223	normalized expression for indicated transcript
ENSG00000196155	normalized expression for indicated transcript
ENSG00000196189	normalized expression for indicated transcript
ENSG00000196415	normalized expression for indicated transcript
ENSG00000196565	normalized expression for indicated transcript
ENSG00000197081	normalized expression for indicated transcript
ENSG00000197121	normalized expression for indicated transcript
ENSG00000197253	normalized expression for indicated transcript
ENSG00000197256	normalized expression for indicated transcript
ENSG00000197321	normalized expression for indicated transcript
ENSG00000197561	normalized expression for indicated transcript
ENSG00000197728	normalized expression for indicated transcript
ENSG00000197860	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000197951	normalized expression for indicated transcript
ENSG00000198743	normalized expression for indicated transcript
ENSG00000198838	normalized expression for indicated transcript

ENSC0000100347	normalized expression for indicated transcript
	normalized expression for indicated transcript
	normalized expression for indicated transcript
ENSG00000213261	normalized expression for indicated transcript
ENSG00000213626	normalized expression for indicated transcript
ENSG00000213722	normalized expression for indicated transcript
ENSG00000213906	normalized expression for indicated transcript
ENSG00000213967	normalized expression for indicated transcript
ENSG00000214016	normalized expression for indicated transcript
ENSG00000214425	normalized expression for indicated transcript
ENSG00000216316	normalized expression for indicated transcript
ENSG00000220008	normalized expression for indicated transcript
ENSG00000223345	normalized expression for indicated transcript
ENSG00000224080	normalized expression for indicated transcript
ENSG00000225138	normalized expression for indicated transcript
ENSG00000226471	normalized expression for indicated transcript
ENSG00000227097	normalized expression for indicated transcript
ENSG00000227191	normalized expression for indicated transcript
ENSG00000227615	normalized expression for indicated transcript
ENSG00000228049	normalized expression for indicated transcript
ENSG00000229153	normalized expression for indicated transcript
ENSG00000230076	normalized expression for indicated transcript
ENSG00000231160	normalized expression for indicated transcript
ENSG00000231721	normalized expression for indicated transcript
ENSG00000233927	normalized expression for indicated transcript
ENSG00000233974	normalized expression for indicated transcript
	T I I I I I I I I I I I I I I I I I I I

ENSG00000239437	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000241399	normalized expression for indicated transcript
ENSG00000241489	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000241529	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000244405	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000247627	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000249592	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000250116	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000250251	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000251079	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000253210	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000253276	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000254415	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000259276	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000260727	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000261377	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000264885	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000264895	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000267136	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000267551	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000267702	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000268001	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000268573	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000270554	normalized expression for indicated transcript
ENSG00000270562	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000271646	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000273018	$normalized\ expression\ for\ indicated\ transcript$
ENSG00000273033	$normalized\ expression\ for\ indicated\ transcript$

# Source

doi:10.1186/s13045-024-01553-6

auc\_mcm 21

auc\_mcm

AUC for cure prediction using mean score imputation

#### **Description**

This function calculates the AUC for cure prediction using the mean score imputation (MSI) method proposed by Asano et al (2014).

## Usage

```
auc_mcm(object, newdata, cure_cutoff = 5, model_select = "AIC")
```

#### **Arguments**

model\_select

object a mixturecure object resulting from curegmifs, cureem, cv\_curegmifs, or

cv\_cureem.

newdata an optional data.frame that minimally includes the incidence and/or latency variables to use for predicting the response. If omitted, the training data are used.

cure\_cutoff cutoff value for cure, used to produce a proxy for the unobserved cure status

(default is 5 representing 5 years). Users should be careful to note the time scale of their data and adjust this according to the time scale and clinical application.

of their data and adjust this according to the time scale and clinical application.

either a case-sensitive parameter for models fit using curegmifs or cureem or any numeric step along the solution path can be selected. The default is model\_select = "AIC" which calculates the predicted values using the coefficients from the model achieving the minimum AIC. The complete list of options are:

• "AIC" for the minimum AIC (default).

- "mAIC" for the minimum modified AIC.
- "cAIC" for the minimum corrected AIC.
- "BIC", for the minimum BIC.
- "mBIC" for the minimum modified BIC.
- "EBIC" for the minimum extended BIC.
- "logLik" for the step that maximizes the log-likelihood.
- n where n is any numeric value from the solution path.

This option has no effect for objects fit using cv\_curegmifs or cv\_cureem.

#### Value

Returns the AUC value for cure prediction using the mean score imputation (MSI) method.

#### References

Asano, J., Hirakawa, H., Hamada, C. (2014) Assessing the prediction accuracy of cure in the Cox proportional hazards cure model: an application to breast cancer data. *Pharmaceutical Statistics*, **13**:357–363.

22 coef.mixturecure

## See Also

concordance\_mcm

#### **Examples**

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
testing <- temp$testing
fit <- curegmifs(Surv(Time, Censor) ~ .,
   data = training, x_latency = training,
   model = "weibull", thresh = 1e-4, maxit = 2000,
   epsilon = 0.01, verbose = FALSE
)
auc_mcm(fit, model_select = "cAIC")
auc_mcm(fit, newdata = testing)</pre>
```

coef.mixturecure

Extract model coefficients from a fitted mixturecure object

# **Description**

coef.mixturecure is a generic function which extracts the model coefficients from a fitted mixturecure model object fit using curegmifs, cureem, cv\_curegmifs, or cv\_cureem.

## Usage

```
## S3 method for class 'mixturecure'
coef(object, model_select = "AIC", ...)
```

#### **Arguments**

object

a mixturecure object resulting from curegmifs, cureem,  $cv\_curegmifs$ , or  $cv\_cureem$ .

model\_select

either a case-sensitive parameter for models fit using curegmifs or cureem or any numeric step along the solution path can be selected. The default is model\_select = "AIC" which calculates the predicted values using the coefficients from the model achieving the minimum AIC. The complete list of options are:

- "AIC" for the minimum AIC (default).
- "mAIC" for the minimum modified AIC.
- "cAIC" for the minimum corrected AIC.
- "BIC", for the minimum BIC.
- "mBIC" for the minimum modified BIC.
- "EBIC" for the minimum extended BIC.

concordance\_mcm 23

- "logLik" for the step that maximizes the log-likelihood.
- n where n is any numeric value from the solution path.

This option has no effect for objects fit using  $cv\_curegmifs$  or  $cv\_cureem$ .

.. other arguments.

#### Value

rate	estimated rate parameter when fitting a Weibull or exponential mixture cure model.
shape	estimated shape parameter when fitting a Weibull mixture cure model.
b0	estimated intercept for the incidence portion of the mixture cure model.
beta_inc	the vector of coefficient estimates for the incidence portion of the mixture cure model.
beta_lat	the vector of coefficient estimates for the latency portion of the mixture cure model.
p_uncured	a vector of probabilities from the incidence portion of the fitted model representing the P(uncured).

#### See Also

curegmifs, cureem, summary.mixturecure, plot.mixturecure, predict.mixturecure

# **Examples**

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
fit <- curegmifs(Surv(Time, Censor) ~ .,
   data = training, x_latency = training,
   model = "weibull", thresh = 1e-4, maxit = 2000,
   epsilon = 0.01, verbose = FALSE
)
coef(fit)</pre>
```

concordance\_mcm

C-statistic for mixture cure models

## **Description**

This function calculates the C-statistic using the cure status weighting (CSW) method proposed by Asano and Hirakawa (2017).

#### Usage

```
concordance_mcm(object, newdata, cure_cutoff = 5, model_select = "AIC")
```

24 concordance\_mcm

## Arguments

object a mixturecure object resulting from curegmifs, cureem, cv\_curegmifs, or

cv\_cureem.

newdata an optional data.frame that minimally includes the incidence and/or latency vari-

ables to use for predicting the response. If omitted, the training data are used.

cure\_cutoff cutoff value for cure, used to produce a proxy for the unobserved cure status (default is 5 representing 5 years). Users should be careful to note the time scale

of their data and adjust this according to the time scale and clinical application.

model\_select either a case-sensitive parameter for models fit using curegmifs or cureem

or any numeric step along the solution path can be selected. The default is model\_select = "AIC" which calculates the predicted values using the coefficients from the model achieving the minimum AIC. The complete list of options are:

• "AIC" for the minimum AIC (default).

• "mAIC" for the minimum modified AIC.

• "cAIC" for the minimum corrected AIC.

• "BIC", for the minimum BIC.

• "mBIC" for the minimum modified BIC.

• "EBIC" for the minimum extended BIC.

• "logLik" for the step that maximizes the log-likelihood.

• model\_select = n where n is any numeric value from the solution path.

This option has no effect for objects fit using cv\_curegmifs or cv\_cureem.

## Value

value of C-statistic for the cure models.

#### References

Asano, J. and Hirakawa, H. (2017) Assessing the prediction accuracy of a cure model for censored survival data with long-term survivors: Application to breast cancer data. *Journal of Biopharmaceutical Statistics*, **27**:6, 918–932.

# See Also

```
auc_mcm
```

#### **Examples**

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
testing <- temp$testing
fit <- curegmifs(Surv(Time, Censor) ~ .,
   data = training, x_latency = training,
   model = "weibull", thresh = 1e-4, maxit = 2000,</pre>
```

cureem 25

```
epsilon = 0.01, verbose = FALSE
)
concordance_mcm(fit, model_select = "cAIC")
concordance_mcm(fit, newdata = testing, model_select = "cAIC")
```

cureem

Fit penalized mixture cure model using the E-M algorithm

# Description

Fits penalized parametric and semi-parametric mixture cure models (MCM) using the E-M algorithm with user-specified penalty parameters. The lasso (L1), MCP, and SCAD penalty are supported for the Cox MCM while only lasso is currently supported for parametric MCMs.

#### Usage

```
cureem(
  formula,
  data,
  subset,
  x_{latency} = NULL,
 model = c("cox", "weibull", "exponential"),
 penalty = c("lasso", "MCP", "SCAD"),
  penalty_factor_inc = NULL,
  penalty_factor_lat = NULL,
  thresh = 0.001,
  scale = TRUE,
 maxit = NULL,
  inits = NULL,
  lambda_inc = 0.1,
  lambda_lat = 0.1,
  gamma_inc = 3,
  gamma_lat = 3,
  na.action = na.omit,
)
```

#### **Arguments**

formula

an object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted. The response must be a survival object as returned by the Surv function while the variables on the right side of the formula are the covariates that are included in the incidence portion of the model.

data

a data.frame in which to interpret the variables named in the formula or in the subset argument. Rows with missing data are omitted (only na.action = na.omit is operational) therefore users may want to impute missing data prior to calling this function.

26 cureem

subset an optional expression indicating which subset of observations to be used in the

fitting process, either a numeric or factor variable should be used in subset, not

a character variable. All observations are included by default.

specifies the variables to be included in the latency portion of the model and can x\_latency

> be either a matrix of predictors, a model formula with the right hand side specifying the latency variables, or the same data.frame passed to the data parameter. Note that when using the model formula syntax for x\_latency it cannot handle

 $x_latency = \sim ...$ 

type of regression model to use for the latency portion of mixture cure model. model

Can be "cox", "weibull", or "exponential" (default is "cox").

type of penalty function. Can be "lasso", "MCP", or "SCAD" (default is "lasso"). penalty

penalty\_factor\_inc

vector of binary indicators representing the penalty to apply to each incidence coefficient: 0 implies no shrinkage and 1 implies shrinkage. If not supplied, 1 is

applied to all incidence variables.

penalty\_factor\_lat

vector of binary indicators representing the penalty to apply to each latency coefficient: 0 implies no shrinkage and 1 implies shrinkage. If not supplied, 1 is

applied to all latency variables.

small numeric value. The iterative process stops when the differences between

successive expected penalized complete-data log-likelihoods for both incidence and latency components are less than this specified level of tolerance (default is

10^-3).

scale logical, if TRUE the predictors are centered and scaled.

maxit integer specifying the maximum number of passes over the data for each lambda.

If not specified, 100 is applied when penalty = "lasso" and 1000 is applied

when penalty = "MCP" or penalty = "SCAD".

inits an optional list specifiying the initial values. This includes:

• itct the incidence intercept.

- b\_u a numeric vector for the unpenalized incidence coefficients for the incidence portion of the model.
- beta\_u a numeric vector for unpenalized latency coefficients in the incidence portion of the model.
- lambda a numeric value for the rate parameter when fitting either a Weibull or exponential MCM using model = "weibull" or model = "exponential".
- alpha a numeric value for the shape parameter when fitting a Weibull MCM using model = "weibull".
- survprob a numeric vector for the latency survival probabilities  $S_u(t_i|w_i)$ for i=1,...,N when fitting a Cox MCM model = "cox".

Penalized coefficients are initialized to zero. If inits is not specified or improperly specified, initialization is automatically provided by the function.

lambda\_inc numeric value for the penalization parameter  $\lambda$  for variables in the incidence portion of the model.

lambda\_lat numeric value for the penalization parameter  $\lambda$  for variables in the latency portion of the model.

thresh

cureem 27

gamma_inc	numeric value for the penalization parameter $\gamma$ for variables in the incidence portion of the model when penalty = "MCP" or penalty = "SCAD" (default is 3).
gamma_lat	numeric value for the penalization parameter $\gamma$ for variables in the latency portion of the model when penalty = "MCP" or penalty = "SCAD" (default is 3).
na.action	this function requires complete data so "na.omit" is invoked. Users can impute missing data as an alternative prior to model fitting.
	additional arguments.

## Value

b_path	Matrix representing the solution path of the coefficients in the incidence portion of the model. Row is step and column is variable.
beta_path	Matrix representing the solution path of the coefficients in the latency portion of the model. Row is step and column is variable.
b0_path	Vector representing the solution path of the intercept in the incidence portion of the model.
logLik_inc	Vector representing the expected penalized complete-data log-likelihood for the incidence portion of the model for each step in the solution path.
logLik_lat	Vector representing the expected penalized complete-data log-likelihood for the latency portion of the model for each step in the solution path.
x_incidence	Matrix representing the design matrix of the incidence predictors.
x_latency	Matrix representing the design matrix of the latency predictors.
у	Vector representing the survival object response as returned by the Surv function
mode1	Character string indicating the type of regression model used for the latency portion of mixture cure model ("weibull" or "exponential").
scale	Logical value indicating whether the predictors were centered and scaled.
method	Character string indicating the EM algorithm was used in fitting the mixture cure model.
rate_path	Vector representing the solution path of the rate parameter for the Weibull or exponential density in the latency portion of the model.
alpha_path	Vector representing the solution path of the shape parameter for the Weibull density in the latency portion of the model.
call	the matched call.

#### References

Archer, K. J., Fu, H., Mrozek, K., Nicolet, D., Mims, A. S., Uy, G. L., Stock, W., Byrd, J. C., Hiddemann, W., Braess, J., Spiekermann, K., Metzeler, K. H., Herold, T., Eisfeld, A.-K. (2024) Identifying long-term survivors and those at higher or lower risk of relapse among patients with cytogenetically normal acute myeloid leukemia using a high-dimensional mixture cure model. *Journal of Hematology & Oncology*, **17**:28.

28 curegmifs

## See Also

cv\_cureem

## **Examples**

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 80, j = 100, n_true = 10, a = 1.8)
training <- temp$training
fit <- cureem(Surv(Time, Censor) ~ .,
   data = training, x_latency = training,
   model = "cox", penalty = "lasso", lambda_inc = 0.1,
   lambda_lat = 0.1, gamma_inc = 6, gamma_lat = 10
)</pre>
```

curegmifs

Fit penalized parametric mixture cure model using the GMIFS algorithm

# **Description**

Fits a penalized Weibull or exponential mixture cure model using the generalized monotone incremental forward stagewise (GMIFS) algorithm (Hastie et al 2007) and yields solution paths for parameters in the incidence and latency portions of the model.

# Usage

```
curegmifs(
  formula,
  data,
  subset,
  x_{latency} = NULL,
 model = c("weibull", "exponential"),
 penalty_factor_inc = NULL,
  penalty_factor_lat = NULL,
  epsilon = 0.001,
  thresh = 1e-05,
  scale = TRUE,
 maxit = 10000,
  inits = NULL,
  verbose = TRUE,
  suppress_warning = FALSE,
 na.action = na.omit,
)
```

curegmifs 29

#### **Arguments**

formula an object of class "formula" (or one that can be coerced to that class): a sym-

bolic description of the model to be fitted. The response must be a survival object as returned by the Surv function while the variables on the right side of the formula are the covariates that are included in the incidence portion of the

model.

data a data frame in which to interpret the variables named in the formula or in

the subset argument. Rows with missing data are omitted (only na.action = na.omit is operational) therefore users may want to impute missing data prior

to calling this function.

subset an optional expression indicating which subset of observations to be used in the

fitting process, either a numeric or factor variable should be used in subset, not

a character variable. All observations are included by default.

x\_latency specifies the variables to be included in the latency portion of the model and can

be either a matrix of predictors, a model formula with the right hand side specifying the latency variables, or the same data.frame passed to the data parameter. Note that when using the model formula syntax for x\_latency it cannot handle

 $x_latency = \sim ...$ 

model type of regression model to use for the latency portion of mixture cure model.

Can be "weibull" or "exponential"; default is "weibull".

penalty\_factor\_inc

vector of binary indicators representing the penalty to apply to each incidence coefficient: 0 implies no shrinkage and 1 implies shrinkage. If not supplied, 1 is

applied to all incidence variables.

penalty\_factor\_lat

vector of binary indicators representing the penalty to apply to each latency coefficient: 0 implies no shrinkage and 1 implies shrinkage. If not supplied, 1 is

applied to all latency variables.

epsilon small numeric value reflecting the incremental value used to update a coefficient

at a given step (default is 0.001).

thresh small numeric value. The iterative process stops when the differences between

successive expected penalized log-likelihoods for both incidence and latency components are less than this specified level of tolerance (default is 10^-5).

scale logical, if TRUE the predictors are centered and scaled.

maxit integer specifying the maximum number of steps to run in the iterative algorithm

(default is 10<sup>4</sup>).

inits an optional list specifying the initial values as follows:

• itct a numeric value for the unpenalized incidence intercept.

- b\_u a numeric vector for the unpenalized incidence coefficients.
- beta\_u a numeric vector for unpenalized latency coefficients.
- lambda a numeric value for the rate parameter.
- alpha a numeric value for the shape parameter when model = "weibull".

If not supplied or improperly supplied, initialization is automatically provided by the function.

30 curegmifs

verbose logical, if TRUE running information is printed to the console (default is FALSE).

suppress\_warning

logical, if TRUE, suppresses echoing the warning that the maximum number of iterations was reached so that the algorithm may not have converged. Instead,

warning is returned as part of the output with this message.

na.action this function requires complete data so "na.omit" is invoked. Users can impute

missing data as an alternative prior to model fitting.

... additional arguments.

#### Value

b\_path Matrix representing the solution path of the coefficients in the incidence portion of the model. Row is step and column is variable.

beta\_path Matrix representing the solution path of the coefficients in the latency portion of

the model. Row is step and column is variable.

b0\_path Vector representing the solution path of the intercept in the incidence portion of

the model.

rate\_path Vector representing the solution path of the rate parameter for the Weibull or

exponential density in the latency portion of the model.

logLik Vector representing the log-likelihood for each step in the solution path.

x\_incidence Matrix representing the design matrix of the incidence predictors.

x\_latency Matrix representing the design matrix of the latency predictors.

y Vector representing the survival object response as returned by the Surv function

model Character string indicating the type of regression model used for the latency

portion of mixture cure model ("weibull" or "exponential").

scale Logical value indicating whether the predictors were centered and scaled.

alpha\_path Vector representing the solution path of the shape parameter for the Weibull

density in the latency portion of the model.

call the matched call.

warning message indicating whether the maximum number of iterations was achieved

which may indicate the model did not converge.

#### References

Fu, H., Nicolet, D., Mrozek, K., Stone, R. M., Eisfeld, A. K., Byrd, J. C., Archer, K. J. (2022) Controlled variable selection in Weibull mixture cure models for high-dimensional data. *Statistics in Medicine*, **41**(22), 4340–4366.

Hastie, T., Taylor J., Tibshirani R., Walther G. (2007) Forward stagewise regression and the monotone lasso. *Electron J Stat*, **1**:1–29.

#### See Also

cv\_curegmifs

cure\_estimate 31

#### **Examples**

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training

fit <- curegmifs(Surv(Time, Censor) ~ .,
   data = training, x_latency = training,
   model = "weibull", thresh = 1e-4, maxit = 2000, epsilon = 0.01,
   verbose = FALSE
)</pre>
```

cure\_estimate

Estimate cured fraction

# **Description**

Estimates the cured fraction using a Kaplan-Meier fitted object.

# Usage

```
cure_estimate(object)
```

# Arguments

object

a survfit object.

## Value

estimated proportion of cured observations

# See Also

```
survfit, sufficient_fu_test, nonzerocure_test
```

# **Examples**

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
km_fit <- survfit(Surv(Time, Censor) ~ 1, data = training)
cure_estimate(km_fit)</pre>
```

cv\_cureem

Fit penalized mixture cure model using the E-M algorithm with cross-validation for parameter tuning

# Description

Fits penalized parametric and semi-parametric mixture cure models (MCM) using the E-M algorithm with with k-fold cross-validation for parameter tuning. The lasso (L1), MCP and SCAD penalty are supported for the Cox MCM while only lasso is currently supported for parametric MCMs. When FDR controlled variable selection is used, the model-X knockoffs method is applied and indices of selected variables are returned.

#### Usage

```
cv_cureem(
  formula,
  data,
  subset,
  x_{latency} = NULL
 model = c("cox", "weibull", "exponential"),
  penalty = c("lasso", "MCP", "SCAD"),
  penalty_factor_inc = NULL,
  penalty_factor_lat = NULL,
  fdr_control = FALSE,
  fdr = 0.2,
  grid_tuning = FALSE,
  thresh = 0.001,
  scale = TRUE,
 maxit = NULL,
  inits = NULL,
  lambda_inc_list = NULL,
  lambda_lat_list = NULL,
  nlambda_inc = NULL,
  nlambda_lat = NULL,
  gamma_inc = 3,
  gamma_lat = 3,
  lambda_min_ratio_inc = 0.1,
  lambda_min_ratio_lat = 0.1,
  n_folds = 5,
 measure_inc = c("c", "auc"),
  one_se = FALSE,
  cure_cutoff = 5,
  parallel = FALSE,
  seed = NULL,
  verbose = TRUE,
  na.action = na.omit,
```

)

# **Arguments**

formula an object of class "formula" (or one that can be coerced to that class): a sym-

bolic description of the model to be fitted. The response must be a survival object as returned by the Surv function while the variables on the right side of the formula are the covariates that are included in the incidence portion of the

model.

data a data.frame in which to interpret the variables named in the formula or in

the subset argument. Rows with missing data are omitted (only na.action = na.omit is operational) therefore users may want to impute missing data prior

to calling this function.

subset an optional expression indicating which subset of observations to be used in the

fitting process, either a numeric or factor variable should be used in subset, not

a character variable. All observations are included by default.

x\_latency specifies the variables to be included in the latency portion of the model and can

be either a matrix of predictors, a model formula with the right hand side specifying the latency variables, or the same data.frame passed to the data parameter. Note that when using the model formula syntax for x\_latency it cannot handle

 $x_latency = \sim ...$ 

model type of regression model to use for the latency portion of mixture cure model.

Can be "cox", "weibull", or "exponential" (default is "cox").

penalty type of penalty function. Can be "lasso", "MCP", or "SCAD" (default is "lasso").

penalty\_factor\_inc

vector of binary indicators representing the penalty to apply to each incidence coefficient: 0 implies no shrinkage and 1 implies shrinkage. If not supplied, 1 is

applied to all incidence variables.

penalty\_factor\_lat

vector of binary indicators representing the penalty to apply to each latency coefficient: 0 implies no shrinkage and 1 implies shrinkage. If not supplied, 1 is

applied to all latency variables.

fdr\_control logical, if TRUE, model-X knockoffs are used for FDR-controlled variable se-

lection and indices of selected variables are returned (default is FALSE).

fdr numeric value in (0, 1) range specifying the target FDR level to use for variable

selection when  $fdr_control = TRUE$  (default is 0.2).

grid\_tuning logical, if TRUE a 2-D grid tuning approach is used to select the optimal pair

of  $\lambda_b$  and  $\lambda_\beta$  penalty parameters for the incidence and latency portions of the model, respectively. Otherwise the  $\lambda_b$  and  $\lambda_\beta$  are selected from a 1-D sequence

and are equal to one another (default is FALSE).

thresh small numeric value. The iterative process stops when the differences between

successive expected penalized complete-data log-likelihoods for both incidence and latency components are less than this specified level of tolerance (default is

10^-3).

scale logical, if TRUE the predictors are centered and scaled.

maxit

maximum number of passes over the data for each lambda. If not specified, 100 is applied when penalty = "lasso" and 1000 is applied when penalty = "MCP" or penalty = "SCAD".

inits

an optional list specifiying the initial values to be used for model fitting as follows:

- itct the incidence intercept.
- b\_u a numeric vector for the unpenalized. incidence coefficients for the incidence portion of the model.
- beta\_u a numeric vector for unpenalized latency coefficients in the incidence portion of the model.
- lambda a numeric value for the rate parameter when fitting either a Weibull or exponential MCM using model = "weibull" or model = "exponential".
- alpha a numeric value for the shape parameter when fitting a Weibull MCM using model = "weibull".
- survprob a numeric vector for the latency survival probabilities  $S_u(t_i|w_i)$  for i=1,...,N when fitting a Cox MCM model = "cox".

Penalized coefficients are initialized to zero. If inits is not specified or improperly specified, initialization is automatically provided by the function.

#### lambda\_inc\_list

a numeric vector used to search for the optimal  $\lambda_b$  tuning parameter. If not supplied, the function computes a  $\lambda_b$  sequence based on nlambda\_inc and lambda\_min\_ratio\_inc. If grid\_tuning = FALSE, the same sequence should be used for both  $\lambda_b$  and  $\lambda_\beta$ .

#### lambda\_lat\_list

a numeric vector used to search for the optimal  $\lambda_{\beta}$  tuning parameter. If not supplied, the function computes a  $\lambda_{\beta}$  sequence based on nlambda\_lat and lambda\_min\_ratio\_lat. If grid\_tuning = FALSE, the same sequence should be used for both  $\lambda_b$  and  $\lambda_{\beta}$ .

nlambda\_inc

an integer specifying the number of values to search for the optimal  $\lambda_b$  tuning parameter; default is 10 if grid\_tuning = TRUE and 50 otherwise.

nlambda\_lat

an integer specifying the number of values to search for the optimal  $\lambda_{\beta}$  tuning parameter; default is 10 if grid\_tuning = TRUE and 50 otherwise.

gamma\_inc

numeric value for the penalization parameter  $\gamma$  for variables in the incidence portion of the model when penalty = "MCP" or penalty = "SCAD" (default is 3).

gamma\_lat

numeric value for the penalization parameter  $\gamma$  for variables in the latency portion of the model when penalty = "MCP" or penalty = "SCAD" (default is 3).

lambda\_min\_ratio\_inc

numeric value in (0,1) representing the smallest value for  $\lambda_b$  as a fraction of lambda.max\_inc, the data-derived entry value at which essentially all penalized variables in the incidence portion of the model have a coefficient estimate of 0 (default is 0.1).

#### lambda\_min\_ratio\_lat

numeric value in (0.1) representing the smallest value for  $\lambda_{\beta}$  as a fraction of lambda.max\_lat, the data-derived entry value at essentially all penalized variables in the latency portion of the model have a coefficient estimate of 0 (default is 0.1).

n\_folds an integer specifying the number of folds for the k-fold cross-valiation procedure (default is 5).

character string specifying the evaluation criterion used in selecting the optimal measure\_inc  $\lambda_b$  which can be either

- "c" specifying to use the C-statistic for cure status weighting (CSW) method proposed by Asano and Hirakawa (2017) to select both  $\lambda_b$  and  $\lambda_\beta$
- "auc" specifying to use the AUC for cure prediction using the mean score imputation (MSI) method proposed by Asano et al. (2014) to select  $\lambda_b$ while the C-statistic with CSW is used for  $\lambda_{\beta}$ .

logical, if TRUE then the one standard error rule is applied for selecting the optimal parameters. The one standard error rule selects the most parsimonious model having evaluation criterion no more than one standard error worse than that of the best evaluation criterion (default is FALSE).

numeric value representing the cutoff time value that represents subjects not experiencing the event by this time are cured. This value is used to produce a proxy for the unobserved cure status when calculating C-statistic and AUC (default is 5 representing 5 years). Users should be careful to note the time scale of their data and adjust this according to the time scale and clinical application.

logical. If TRUE, parallel processing is performed for K-fold CV using foreach and the **doParallel** package is required.

optional integer representing the random seed. Setting the random seed fosters reproducibility of the results.

logical, if TRUE running information is printed to the console (default is FALSE). na.action this function requires complete data so "na.omit" is invoked. Users can impute missing data as an alternative prior to model fitting.

additional arguments. . . .

## Value

one se

cure\_cutoff

parallel

seed

verbose

b0 Estimated intercept for the incidence portion of the model. h Estimated coefficients for the incidence portion of the model. beta Estimated coefficients for the latency portion of the model. alpha Estimated shape parameter if the Weibull model is fit.

rate Estimated rate parameter if the Weibull or exponential model is fit.

Expected penalized complete-data log-likelihood for the incidence portion of logLik\_inc

the model.

logLik\_lat Expected penalized complete-data log-likelihood for the latency portion of the

selected\_lambda\_inc

Value of  $\lambda_b$  selected using cross-validation. NULL when fdr\_control is TRUE.

selected\_lambda\_lat

Value of  $\lambda_{\beta}$  selected using cross-validation. NULL when fdr\_control is TRUE.

Maximum C-statistic achieved. max\_c

max\_auc Maximum AUC for cure prediction achieved; only output when measure\_inc="auc".

selected\_index\_inc

Indices of selected variables for the incidence portion of the model when fdr\_control=TRUE. If no variables are selected, int(0) will be returned.

selected\_index\_lat

Indices of selected variables for the latency portion of the model when fdr\_control=TRUE. If no variables are selected, int(0) will be returned.

call the matched call.

#### References

Archer, K. J., Fu, H., Mrozek, K., Nicolet, D., Mims, A. S., Uy, G. L., Stock, W., Byrd, J. C., Hiddemann, W., Braess, J., Spiekermann, K., Metzeler, K. H., Herold, T., Eisfeld, A.-K. (2024) Identifying long-term survivors and those at higher or lower risk of relapse among patients with cytogenetically normal acute myeloid leukemia using a high-dimensional mixture cure model. *Journal of Hematology & Oncology*, **17**:28.

#### See Also

cureem

#### **Examples**

```
## Not run:
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 200, j = 25, n_true = 5, a = 1.8, rho = 0.2)
training <- temp$training
# Fit a penalized Cox MCM selecting parameters using 2-fold CV
fit.cv <- cv_cureem(Surv(Time, Censor) ~ .,</pre>
  data = training,
  x_latency = training, fdr_control = FALSE,
  grid_tuning = FALSE, nlambda_inc = 10, nlambda_lat = 10,
  n_folds = 2, seed = 23, verbose = FALSE
fit.cv.fdr <- cv_cureem(Surv(Time, Censor) ~ .,</pre>
   data = training,
   x_latency = training, model = "weibull", penalty = "lasso",
   fdr_control = TRUE, grid_tuning = FALSE, nlambda_inc = 10,
   nlambda_lat = 10, n_folds = 2, seed = 23, verbose = TRUE
## End(Not run)
```

cv\_curegmifs 37

cv\_curegmifs

Fit a penalized parametric mixture cure model using the generalized monotone incremental forward stagewise (GMIFS) algorithm (Hastie et al 2007) with cross-validation for model selection

# **Description**

Fits a penalized Weibull or exponential mixture cure model using the generalized monotone incremental forward stagewise (GMIFS) algorithm with k-fold cross-validation to select the optimal iteration step along the solution path. When FDR controlled variable selection is used, the model-X knockoffs method is applied and indices of selected variables are returned.

# Usage

```
cv_curegmifs(
  formula,
  data,
  subset,
  x_{latency} = NULL,
 model = c("weibull", "exponential"),
 penalty_factor_inc = NULL,
  penalty_factor_lat = NULL,
  fdr_control = FALSE,
  fdr = 0.2,
  epsilon = 0.001,
  thresh = 1e-05,
  scale = TRUE,
 maxit = 10000,
  inits = NULL,
 n_folds = 5,
 measure_inc = c("c", "auc"),
 one_se = FALSE,
  cure_cutoff = 5,
  parallel = FALSE,
  seed = NULL,
  verbose = TRUE,
  na.action = na.omit,
)
```

# **Arguments**

formula

an object of class "formula" (or one that can be coerced to that class): a symbolic description of the model to be fitted. The response must be a survival object as returned by the Surv function while the variables on the right side of the formula are the covariates that are included in the incidence portion of the model.

38 cv\_curegmifs

data a data.frame in which to interpret the variables named in the formula or in

> the subset argument. Rows with missing data are omitted (only na.action = na.omit is operational) therefore users may want to impute missing data prior

to calling this function.

subset an optional expression indicating which subset of observations to be used in the

fitting process, either a numeric or factor variable should be used in subset, not

a character variable. All observations are included by default.

x\_latency specifies the variables to be included in the latency portion of the model and can

> be either a matrix of predictors, a model formula with the right hand side specifying the latency variables, or the same data.frame passed to the data parameter. Note that when using the model formula syntax for x\_latency it cannot handle

 $x_latency = \sim ...$ 

mode1 type of regression model to use for the latency portion of mixture cure model.

Can be "weibull" or "exponential"; default is "weibull".

penalty\_factor\_inc

vector of binary indicators representing the penalty to apply to each incidence coefficient: 0 implies no shrinkage and 1 implies shrinkage. If not supplied, 1 is

applied to all incidence variables.

penalty\_factor\_lat

vector of binary indicators representing the penalty to apply to each latency coefficient: 0 implies no shrinkage and 1 implies shrinkage. If not supplied, 1 is

applied to all latency variables.

fdr\_control logical, if TRUE, model-X knockoffs are used for FDR-controlled variable se-

lection and indices of selected variables are returned (default is FALSE).

fdr numeric value in (0, 1) range specifying the target FDR level to use for variable

selection when fdr\_control = TRUE (default is 0.2).

epsilon small numeric value reflecting incremental value used to update a coefficient at

a given step (default is 0.001).

thresh small numeric value. The iterative process stops when the differences between

> successive expected penalized complete-data log-likelihoods for both incidence and latency components are less than this specified level of tolerance (default is

10^-5).

scale logical, if TRUE the predictors are centered and scaled.

integer specifying the maximum number of steps to run in the iterative algorithm maxit

(default is 10<sup>4</sup>).

inits an optional list specifying the initial values as follows:

• itct a numeric value for the unpenalized incidence intercept.

• b\_u a numeric vector for the unpenalized incidence coefficients.

• beta\_u a numeric vector for unpenalized latency coefficients.

• lambda a numeric value for the rate parameter.

• alpha a numeric value for the shape parameter when model = "weibull".

If inits is not specified or improperly supplied, initialization is automatically provided by the function.

cv\_curegmifs 39

n\_folds an integer specifying the number of folds for the k-fold cross-validation proce-

dure (default is 5).

measure\_inc character string specifying the evaluation criterion used in selecting the optimal  $\lambda_b$  which can be either

• "c" specifying to use the C-statistic for cure status weighting (CSW) method proposed by Asano and Hirakawa (2017) to select both  $\lambda_b$  and  $\lambda_\beta$ 

• "auc" specifying to use the AUC for cure prediction using the mean score imputation (MSI) method proposed by Asano et al. (2014) to select  $\lambda_b$  while the C-statistic with CSW is used for  $\lambda_\beta$ .

one\_se logical, if TRUE then the one standard error rule is applied for selecting the

optimal parameters. The one standard error rule selects the most parsimonious model having evaluation criterion no more than one standard error worse than

that of the best evaluation criterion (default is FALSE).

cure\_cutoff numeric value representing the cutoff time value that represents subjects not

experiencing the event by this time are cured. This value is used to produce a proxy for the unobserved cure status when calculating C-statistic and AUC (default is 5 representing 5 years). Users should be careful to note the time scale of their data and adjust this according to the time scale and clinical application.

parallel logical. If TRUE, parallel processing is performed for K-fold CV using foreach

and the **doParallel** package is required.

seed optional integer representing the random seed. Setting the random seed fosters

reproducibility of the results.

verbose logical, if TRUE running information is printed to the console (default is FALSE).

na.action this function requires complete data so "na.omit" is invoked. Users can impute

missing data as an alternative prior to model fitting.

... additional arguments.

#### Value

b0 Estimated intercept for the incidence portion of the model.
b Estimated coefficients for the incidence portion of the model.
beta Estimated coefficients for the latency portion of the model.
alpha Estimated shape parameter if the Weibull model is fit.

rate Estimated rate parameter if the Weibull or exponential model is fit.

logLik Log-likelihood value.

selected\_step\_inc

Iteration step selected for the incidence portion of the model using cross-validation.

NULL when fdr\_control is TRUE.

selected\_step\_lat

Iteration step selected for the latency portion of the model using cross-validation.

NULL when fdr control is TRUE.

max\_c Maximum C-statistic achieved

max\_auc Maximum AUC for cure prediction achieved; only output when measure\_inc =

"auc".

40 dim.mixturecure

#### References

Fu, H., Nicolet, D., Mrozek, K., Stone, R. M., Eisfeld, A. K., Byrd, J. C., Archer, K. J. (2022) Controlled variable selection in Weibull mixture cure models for high-dimensional data. *Statistics in Medicine*, **41**(22), 4340–4366.

Hastie, T., Taylor J., Tibshirani R., Walther G. (2007) Forward stagewise regression and the monotone lasso. *Electron J Stat*, **1**:1–29.

#### See Also

curegmifs

# **Examples**

```
library(survival)
withr::local_seed(123)
temp <- generate_cure_data(n = 100, j = 15, n_true = 3, a = 1.8, rho = 0.2)
training <- temp$training

fit.cv <- cv_curegmifs(Surv(Time, Censor) ~ .,
   data = training,
   x_latency = training, fdr_control = FALSE,
   maxit = 450, epsilon = 0.01, n_folds = 2,
   seed = 23, verbose = TRUE
)</pre>
```

dim.mixturecure

Dimension method for mixturecure objects

## **Description**

Dimension method for mixturecure objects.

# Usage

```
## S3 method for class 'mixturecure'
dim(x)
```

## **Arguments**

x An object of class mixturecure.

family.mixturecure 41

#### Value

```
nobs number of subjects in the dataset.

p_incidence number of variables in the incidence portion of the model.

p_latency number of variables in the latency portion of the model.
```

# **Examples**

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
fit <- curegmifs(Surv(Time, Censor) ~ .,
   data = training, x_latency = training,
   model = "weibull", thresh = 1e-4, maxit = 2000,
   epsilon = 0.01, verbose = FALSE
)
dim(fit)</pre>
```

family.mixturecure

Return model family and fitting algorithm for mixturecure model fits

# **Description**

Return model family and fitting algorithm formixturecure model fits.

#### Usage

```
## S3 method for class 'mixturecure'
family(object, ...)
```

## Arguments

```
object an object of class mixturecure ... other arguments.
```

#### Value

the parametric or semi-parametric model fit and the fitting algorithm.

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
fit <- curegmifs(Surv(Time, Censor) ~ .,
   data = training, x_latency = training,
   model = "weibull", thresh = 1e-4, maxit = 2000,</pre>
```

42 formula.mixturecure

```
epsilon = 0.01, verbose = FALSE
)
family(fit)
```

formula.mixturecure

Extract model formula for mixturecure object

# **Description**

Extract the model formula for mixturecure object

# Usage

```
## S3 method for class 'mixturecure'
formula(x, ...)
```

#### **Arguments**

- x an object from class mixturecure.
- ... other arguments.

#### Value

a formula representing the incidence and variables for the latency portion of the model

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
fit <- curegmifs(Surv(Time, Censor) ~ .,
   data = training, x_latency = training,
   model = "weibull", thresh = 1e-4, maxit = 2000,
   epsilon = 0.01, verbose = FALSE
)
formula(fit)</pre>
```

generate\_cure\_data 43

generate\_cure\_data

Simulate data under a mixture cure model

# Description

Simulate data under a mixture cure model.

# Usage

```
generate_cure_data(
    n = 400,
    j = 500,
    nonp = 2,
    train_prop = 0.75,
    n_true = 10,
    a = 1,
    rho = 0.5,
    itct_mean = 0.5,
    cens_ub = 20,
    alpha = 1,
    lambda = 2,
    same_signs = FALSE,
    model = "weibull"
)
```

# Arguments

n	an integer denoting the total sample size.
j	an integer denoting the number of penalized predictors which is the same for both the incidence and latency portions of the model.
nonp	an integer denoting the number of unpenalized predictors (which is the same for both the incidence and latency portions of the model).
train_prop	a numeric value in $[0, 1)$ representing the fraction of n to be used in forming the training dataset.
n_true	an integer less than j denoting the number of variables truly associated with the outcome (i.e., the number of covariates with nonzero parameter values) among the penalized predictors.
a	a numeric value denoting the effect size (signal amplitude) which is the same for both the incidence and latency portions of the model.
rho	a numeric value in $[0, 1)$ representing the correlation between adjacent covariates in the same block.
itct_mean	a numeric value representing the expectation of the incidence intercept which controls the cure rate.
cens_ub	a numeric value representing the upper bound on the censoring time distribution which follows a uniform distribution on (0, cens_ub].

44 generate\_cure\_data

alpha lambda a numeric value representing the shape parameter in the Weibull density. a numeric value representing the rate parameter in the Weibull density.

same\_signs

logical, if TRUE the incidence and latency coefficients have the same signs.

model type of regression model to use for the latency portion of mixture cure model.

Can be one of the following:

• "weibull" to generate times from a Weibull distribution.

- "GG" to generate times from a generalized gamma distribution.
- "Gompertz" to generate times from a Gomertz distribution.
- "nonparametric" to generate times non-parametrically.
- "GG\_baseline" to generate times from a generalized gamma baseline distribution.

## Value

training

training data.frame which includes Time, Censor, and covariates. Variables prefixed with "U" indicates unpenalized covariates and is equal to the value passed to nonp (default is 2). Variables prefixed with "X" indicates penalized covariates and is equal to the value passed to j.

training\_y

the true status for the training set: uncured = 1; cured = 0

testing

testing data.frame which includes Time, Censor, Y (the true uncured = 1; cured = 0 status), and covariates. Variables prefixed with "U" indicates unpenalized covariates and is equal to the value passed to nonp (default is 2). Variables prefixed with "X" indicates penalized covariates and is equal to the value passed to j.

testing\_y

the true status for the testing set: uncured = 1; cured = 0

parameters

a list including: the indices of true incidence signals (nonzero\_b), indices of true latency signals (nonzero\_beta), unpenalized incidence parameter values (b\_u), unpenalized latency parameter values (beta\_u), parameter values for the true incidence signals among penalized covariates (b\_p\_nz), parameter values for the true latency signals among penalized covariates (beta\_p\_nz), parameter value for the incidence intercept (itct)

```
library(survival)
withr::local_seed(1234)
# This dataset has 2 penalized features associated with the outcome,
# 3 penalized features not associated with the outcome (noise features), and 1
# unpenalized noise feature.
data <- generate_cure_data(n = 1000, j = 5, n_true = 2, nonp = 1, a = 2)
# Extract the training data
training <- data$training
# Extract the testing data
testing <- data$testing
# To identify the features truly associated with incidence
names(training)[grep("^X", names(training))][data$parameters$nonzero_b]
# To identify the features truly associated with latency</pre>
```

logLik.mixturecure 45

```
names(training)[grep("^X", names(training))][data$parameters$nonzero_beta]
# Fit the model to the training data
fitem <- cureem(Surv(Time, Censor) ~ ., data = training,
    x_latency = training)
# Examine the estimated coefficients at the (default) minimum AIC
coef(fitem)
# As the penalty increases, the coefficients for the noise variables shrink
# to or remain at zero, while the truly associated features have coefficient
# paths that depart from zero. This shows the model's ability to distinguish
# signal from noise.
plot(fitem, label = TRUE)</pre>
```

logLik.mixturecure

Log-likelihood for fitted mixture cure model

# Description

This function returns the log-likelihood for a user-specified model criterion or step for a curegmifs, cureem, cv\_curegmifs or cv\_cureem fitted object.

#### Usage

```
## S3 method for class 'mixturecure'
logLik(object, model_select = "AIC", ...)
```

# **Arguments**

object model select

 $a\, \texttt{mixture} cure\, object\, resulting\, from\, \texttt{curegmifs}, \, \texttt{cureem}, \, \texttt{cv\_cureem}.$ 

either a case-sensitive parameter for models fit using curegmifs or cureem or any numeric step along the solution path can be selected. The default is model\_select = "AIC" which calculates the predicted values using the coefficients from the model achieving the minimum AIC. The complete list of options are:

- "AIC" for the minimum AIC (default).
- "mAIC" for the minimum modified AIC.
- "cAIC" for the minimum corrected AIC.
- "BIC", for the minimum BIC.
- "mBIC" for the minimum modified BIC.
- "EBIC" for the minimum extended BIC.
- "logLik" for the step that maximizes the log-likelihood.
- n where n is any numeric value from the solution path.

This option has no effect for objects fit using cv\_curegmifs or cv\_cureem. other arguments.

## Value

log-likelihood of the fitted mixture cure model using the specified criteria.

46 nobs.mixturecure

## **Examples**

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
fit <- curegmifs(Surv(Time, Censor) ~ .,
   data = training, x_latency = training,
   model = "weibull", thresh = 1e-4, maxit = 2000,
   epsilon = 0.01, verbose = FALSE
)
logLik(fit, model_select = "AIC")</pre>
```

nobs.mixturecure

Number of observations in mixturecure object

# **Description**

Number of observations in fitted mixturecure object.

# Usage

```
## S3 method for class 'mixturecure'
nobs(object, ...)
```

#### **Arguments**

```
object An object of class mixturecure.
... other arguments.
```

## Value

number of subjects in the dataset.

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
fit <- curegmifs(Surv(Time, Censor) ~ .,
   data = training, x_latency = training,
   model = "weibull", thresh = 1e-4, maxit = 2000,
   epsilon = 0.01, verbose = FALSE
)
nobs(fit)</pre>
```

nonzerocure\_test 47

nonzerocure_test	Non-parametric test for a non-zero cured fraction
------------------	---

# Description

Tests the null hypothesis that the proportion of observations susceptible to the event = 1 against the alternative that the proportion of observations susceptible to the event is < 1. If the null hypothesis is rejected, there is a significant cured fraction.

## Usage

```
nonzerocure_test(object, reps = 1000, seed = NULL, plot = FALSE, b = NULL)
```

#### **Arguments**

object

reps

number of simulations on which to base the p-value (default = 1000).

seed

optional random seed.

plot

logical. If TRUE a histogram of the estimated susceptible proportions over all simulations is produced.

b

optional. If specified the maximum observed time for the uniform distribution for generating the censoring times. If not specified, an exponential model is used for generating the censoring times (default).

#### Value

#### References

Maller, R. A. and Zhou, X. (1996) Survival Analysis with Long-Term Survivors. John Wiley & Sons.

#### See Also

```
survfit, cure_estimate, sufficient_fu_test
```

48 npar\_mixturecure

#### **Examples**

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
km_fit <- survfit(Surv(Time, Censor) ~ 1, data = training)
nonzerocure_test(km_fit)</pre>
```

npar\_mixturecure

Number of parameters in fitted mixture cure model

#### **Description**

This function returns the number of parameters in a user-specified model criterion or step for a curegmifs, cureem, cv\_curegmifs or cv\_cureem fitted object.

#### Usage

```
npar_mixturecure(object, model_select = "AIC")
```

## **Arguments**

object

a mixturecure object resulting from curegmifs, cureem, cv\_curegmifs, cv\_cureem.

model\_select

either a case-sensitive parameter for models fit using curegmifs or cureem or any numeric step along the solution path can be selected. The default is model\_select = "AIC" which calculates the predicted values using the coefficients from the model achieving the minimum AIC. The complete list of options are:

- "AIC" for the minimum AIC (default).
- "mAIC" for the minimum modified AIC.
- "cAIC" for the minimum corrected AIC.
- "BIC", for the minimum BIC.
- "mBIC" for the minimum modified BIC.
- "EBIC" for the minimum extended BIC.
- "logLik" for the step that maximizes the log-likelihood.
- n where n is any numeric value from the solution path.

This option has no effect for objects fit using cv\_curegmifs or cv\_cureem.

#### Value

number of paramaters of the fitted mixture cure model using the specified criteria.

pediatric\_flt3 49

pediatric_flt3	Pediatric acute myeloid leukemia patients with FLT3-ITD rearrange- ment data

#### **Description**

Event-free survival for 246 pediatric acute myeloid leukemia patients having a FLT3-ITD rearrangement along with expression of 200 transcripts from RNA-sequencing.

#### Usage

```
pediatric_flt3
```

#### **Format**

A data frame with 246 rows (subjects) and 202 columns:

efs event-free survival

**status** censoring indicator: 1 = event; 0 = censored

ENSG00000229807.12 normalized expression for indicated transcript

**ENSG00000211459.2** normalized expression for indicated transcript

ENSG00000264063.1 normalized expression for indicated transcript

ENSG00000264462.1 normalized expression for indicated transcript

ENSG00000227195.11 normalized expression for indicated transcript

ENSG00000198795.11 normalized expression for indicated transcript

ENSG00000177133.11 normalized expression for indicated transcript

ENSG00000257883.1 normalized expression for indicated transcript

ENSG00000189223.15 normalized expression for indicated transcript

ENSG00000210082.2 normalized expression for indicated transcript

ENSG00000142611.17 normalized expression for indicated transcript

ENSG00000054598.9 normalized expression for indicated transcript

ENSG00000147180.17 normalized expression for indicated transcript

ENSG00000275708.1 normalized expression for indicated transcript

ENSG00000227063.5 normalized expression for indicated transcript

ENSG00000179455.10 normalized expression for indicated transcript

ENSG00000243478.9 normalized expression for indicated transcript

ENSG00000239839.7 normalized expression for indicated transcript

ENSG00000274253.5 normalized expression for indicated transcript

ENSG00000198840.2 normalized expression for indicated transcript

ENSG00000186407.7 normalized expression for indicated transcript

50 pediatric\_flt3

ENSG00000198763.3 normalized expression for indicated transcript ENSG00000107562.16 normalized expression for indicated transcript ENSG00000188536.13 normalized expression for indicated transcript **ENSG00000164821.5** normalized expression for indicated transcript **ENSG00000255833.2** normalized expression for indicated transcript **ENSG0000107447.8** normalized expression for indicated transcript ENSG00000237541.4 normalized expression for indicated transcript **ENSG00000274618.2** normalized expression for indicated transcript **ENSG00000206172.8** normalized expression for indicated transcript ENSG00000198886.2 normalized expression for indicated transcript ENSG00000122592.8 normalized expression for indicated transcript ENSG00000038427.16 normalized expression for indicated transcript ENSG00000134755.17 normalized expression for indicated transcript ENSG00000248527.1 normalized expression for indicated transcript **ENSG00000273018.7** normalized expression for indicated transcript **ENSG00000261377.5** normalized expression for indicated transcript ENSG0000074964.17 normalized expression for indicated transcript ENSG00000118113.12 normalized expression for indicated transcript ENSG00000086548.9 normalized expression for indicated transcript ENSG00000172037.14 normalized expression for indicated transcript ENSG00000198744.5 normalized expression for indicated transcript ENSG00000198899.2 normalized expression for indicated transcript ENSG00000186818.12 normalized expression for indicated transcript ENSG00000154864.13 normalized expression for indicated transcript **ENSG00000227081.5** normalized expression for indicated transcript ENSG00000101425.14 normalized expression for indicated transcript ENSG00000158473.8 normalized expression for indicated transcript ENSG00000102362.15 normalized expression for indicated transcript **ENSG00000212907.2** normalized expression for indicated transcript ENSG00000121807.6 normalized expression for indicated transcript ENSG00000138829.12 normalized expression for indicated transcript ENSG00000185052.12 normalized expression for indicated transcript ENSG00000111057.11 normalized expression for indicated transcript **ENSG00000228253.1** normalized expression for indicated transcript ENSG00000188153.14 normalized expression for indicated transcript ENSG00000166681.14 normalized expression for indicated transcript ENSG00000198888.2 normalized expression for indicated transcript

pediatric\_flt3 51

ENSG00000276141.4 normalized expression for indicated transcript ENSG00000230076.1 normalized expression for indicated transcript **ENSG00000260314.3** normalized expression for indicated transcript ENSG00000187164.20 normalized expression for indicated transcript **ENSG00000212443.1** normalized expression for indicated transcript ENSG00000251692.8 normalized expression for indicated transcript **ENSG00000198727.2** normalized expression for indicated transcript **ENSG00000131401.11** normalized expression for indicated transcript **ENSG00000225345.3** normalized expression for indicated transcript ENSG00000197253.13 normalized expression for indicated transcript ENSG00000163737.4 normalized expression for indicated transcript **ENSG00000204010.3** normalized expression for indicated transcript ENSG00000174403.16 normalized expression for indicated transcript ENSG00000249790.3 normalized expression for indicated transcript **ENSG00000239559.2** normalized expression for indicated transcript ENSG00000142192.21 normalized expression for indicated transcript **ENSG00000151650.8** normalized expression for indicated transcript **ENSG00000198712.1** normalized expression for indicated transcript ENSG00000124469.12 normalized expression for indicated transcript ENSG00000105854.13 normalized expression for indicated transcript ENSG00000197629.6 normalized expression for indicated transcript ENSG00000278588.2 normalized expression for indicated transcript ENSG00000196565.15 normalized expression for indicated transcript ENSG00000241743.4 normalized expression for indicated transcript ENSG00000174059.17 normalized expression for indicated transcript ENSG00000150760.13 normalized expression for indicated transcript ENSG00000133742.14 normalized expression for indicated transcript ENSG00000210196.2 normalized expression for indicated transcript **ENSG00000204860.5** normalized expression for indicated transcript ENSG00000131398.15 normalized expression for indicated transcript ENSG00000106080.11 normalized expression for indicated transcript **ENSG00000198786.2** normalized expression for indicated transcript ENSG00000248334.6 normalized expression for indicated transcript ENSG00000169908.12 normalized expression for indicated transcript ENSG00000171509.16 normalized expression for indicated transcript ENSG0000008438.5 normalized expression for indicated transcript ENSG00000130147.16 normalized expression for indicated transcript

52 pediatric\_flt3

ENSG00000180071.20 normalized expression for indicated transcript ENSG00000168329.14 normalized expression for indicated transcript **ENSG00000147689.16** normalized expression for indicated transcript **ENSG00000136193.17** normalized expression for indicated transcript ENSG00000170180.22 normalized expression for indicated transcript ENSG00000146373.16 normalized expression for indicated transcript ENSG00000172236.18 normalized expression for indicated transcript **ENSG00000244734.4** normalized expression for indicated transcript **ENSG00000239552.2** normalized expression for indicated transcript ENSG00000125618.17 normalized expression for indicated transcript ENSG00000273983.1 normalized expression for indicated transcript ENSG00000250361.9 normalized expression for indicated transcript ENSG00000277775.2 normalized expression for indicated transcript ENSG00000138119.17 normalized expression for indicated transcript ENSG00000128422.17 normalized expression for indicated transcript ENSG00000160883.11 normalized expression for indicated transcript **ENSG00000275895.7** normalized expression for indicated transcript ENSG00000169877.10 normalized expression for indicated transcript ENSG00000163736.4 normalized expression for indicated transcript ENSG00000161944.16 normalized expression for indicated transcript ENSG00000095917.14 normalized expression for indicated transcript ENSG00000022556.16 normalized expression for indicated transcript ENSG00000152078.10 normalized expression for indicated transcript ENSG00000165092.13 normalized expression for indicated transcript ENSG00000170458.14 normalized expression for indicated transcript ENSG0000070182.21 normalized expression for indicated transcript ENSG00000157445.15 normalized expression for indicated transcript **ENSG00000206737.1** normalized expression for indicated transcript ENSG00000225217.1 normalized expression for indicated transcript ENSG00000198336.9 normalized expression for indicated transcript ENSG00000177469.13 normalized expression for indicated transcript ENSG00000198695.2 normalized expression for indicated transcript ENSG00000113763.12 normalized expression for indicated transcript ENSG00000223609.11 normalized expression for indicated transcript **ENSG00000206177.7** normalized expression for indicated transcript ENSG00000164684.13 normalized expression for indicated transcript ENSG00000197632.9 normalized expression for indicated transcript

pediatric\_flt3 53

ENSG00000177575.13 normalized expression for indicated transcript ENSG0000004939.15 normalized expression for indicated transcript ENSG00000121053.6 normalized expression for indicated transcript **ENSG00000259207.9** normalized expression for indicated transcript ENSG00000158352.16 normalized expression for indicated transcript ENSG00000198046.12 normalized expression for indicated transcript **ENSG00000225630.1** normalized expression for indicated transcript ENSG0000070808.16 normalized expression for indicated transcript ENSG00000012223.13 normalized expression for indicated transcript ENSG00000085265.11 normalized expression for indicated transcript ENSG00000158578.21 normalized expression for indicated transcript ENSG00000112077.17 normalized expression for indicated transcript **ENSG00000272398.6** normalized expression for indicated transcript **ENSG00000116667.15** normalized expression for indicated transcript **ENSG00000101916.12** normalized expression for indicated transcript ENSG00000184293.7 normalized expression for indicated transcript **ENSG00000244040.7** normalized expression for indicated transcript ENSG00000229344.1 normalized expression for indicated transcript ENSG00000142405.22 normalized expression for indicated transcript ENSG00000171051.9 normalized expression for indicated transcript ENSG00000183023.18 normalized expression for indicated transcript ENSG00000257178.5 normalized expression for indicated transcript ENSG00000244682.7 normalized expression for indicated transcript ENSG00000166025.18 normalized expression for indicated transcript ENSG00000204613.11 normalized expression for indicated transcript ENSG00000214188.9 normalized expression for indicated transcript ENSG00000179869.15 normalized expression for indicated transcript ENSG00000136315.4 normalized expression for indicated transcript ENSG00000119919.11 normalized expression for indicated transcript ENSG00000123384.14 normalized expression for indicated transcript ENSG00000104918.8 normalized expression for indicated transcript **ENSG00000287431.1** normalized expression for indicated transcript ENSG00000227827.3 normalized expression for indicated transcript ENSG00000164047.6 normalized expression for indicated transcript ENSG00000137571.11 normalized expression for indicated transcript ENSG00000143416.21 normalized expression for indicated transcript ENSG00000253578.1 normalized expression for indicated transcript

54 pediatric\_flt3

ENSG00000120708.17 normalized expression for indicated transcript **ENSG00000220842.6** normalized expression for indicated transcript ENSG00000110077.14 normalized expression for indicated transcript ENSG00000198722.14 normalized expression for indicated transcript ENSG00000121316.11 normalized expression for indicated transcript ENSG00000123689.6 normalized expression for indicated transcript ENSG00000198938.2 normalized expression for indicated transcript ENSG00000163430.12 normalized expression for indicated transcript **ENSG00000258227.7** normalized expression for indicated transcript **ENSG00000233101.10** normalized expression for indicated transcript ENSG00000163220.11 normalized expression for indicated transcript ENSG00000100985.7 normalized expression for indicated transcript ENSG00000166947.15 normalized expression for indicated transcript ENSG00000275713.2 normalized expression for indicated transcript ENSG00000143546.10 normalized expression for indicated transcript ENSG00000136929.13 normalized expression for indicated transcript ENSG00000103313.13 normalized expression for indicated transcript ENSG00000186529.16 normalized expression for indicated transcript ENSG00000109321.11 normalized expression for indicated transcript ENSG00000104177.18 normalized expression for indicated transcript ENSG00000257335.8 normalized expression for indicated transcript ENSG00000197993.9 normalized expression for indicated transcript ENSG00000134460.18 normalized expression for indicated transcript ENSG00000211892.4 normalized expression for indicated transcript ENSG00000180044.5 normalized expression for indicated transcript ENSG00000268555.2 normalized expression for indicated transcript ENSG00000266402.3 normalized expression for indicated transcript ENSG00000163221.9 normalized expression for indicated transcript ENSG00000225101.6 normalized expression for indicated transcript ENSG00000197249.14 normalized expression for indicated transcript ENSG00000093134.15 normalized expression for indicated transcript

#### Source

https://www.cancer.gov/ccg/research/genome-sequencing/target/studied-cancers/acute-myeloid-leukemiatargets-aml-project

plot.mixturecure 55

plot.mixturecure

Plot fitted mixture cure model

## Description

This function plots either the coefficient path, the AIC, the cAIC, the BIC, or the log-likelihood for a fitted curegmifs or cureem object. This function produces a lollipop plot of the coefficient estimates for a fitted cv\_curegmifs or cv\_cureem object.

# Usage

```
## S3 method for class 'mixturecure'
plot(
    x,
    type = c("trace", "AIC", "BIC", "logLik", "cAIC", "mAIC", "mBIC", "EBIC"),
    xlab = NULL,
    ylab = NULL,
    label = FALSE,
    main = NULL,
    ...
)
```

#### **Arguments**

Χ

a mixturecure object resulting from curegmifs or cureem, cv\_curegmifs or cv\_cureem.

type

a case-sensitive parameter indicating what to plot on the y-axis. The complete list of options are:

- "trace" plots the coefficient path for the fitted object (default).
- "AIC" plots the AIC against step of model fit.
- "mAIC" plots the modified AIC against step of model fit.
- "cAIC" plots the corrected AIC against step of model fit.
- "BIC", plots the BIC against step of model fit.
- "mBIC" plots the modified BIC against step of model fit.
- "EBIC" plots the extended BIC against step of model fit.
- "logLik" plots the log-likelihood against step of model fit.

This option has no effect for objects fit using cv\_curegmifs or cv\_cureem.

xlab

a default x-axis label will be used which can be changed by specifying a user-defined x-axis label.

ylab

a default y-axis label will be used which can be changed by specifying a user-defined y-axis label.

label

logical. If TRUE the variable names will appear in a legend. Applicable only when type = "trace". Be reminded that this works well only for small to moderate numbers of variables. For many predictors, the plot will be cluttered. The

56 predict.mixturecure

variables may be more easily identified using the coef function indicating the step of interest.

main

a default main title will be used which can be changed by specifying a user-defined main title. This option is not used for cv\_curegmifs or cv\_cureem fitted objects.

... other arguments.

#### Value

this function has no returned value but is called for its side effects

#### See Also

```
curegmifs, cureem, coef.mixturecure, summary.mixturecure, predict.mixturecure
```

## **Examples**

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
fit <- curegmifs(Surv(Time, Censor) ~ .,
   data = training, x_latency = training,
   model = "weibull", thresh = 1e-4, maxit = 2000,
   epsilon = 0.01, verbose = FALSE
)
plot(fit)</pre>
```

predict.mixturecure

Predicted probabilities for susceptibles, linear predictor for latency, and risk class for latency for mixture cure fit

# **Description**

This function returns a list that includes the predicted probabilities for susceptibles as well as the linear predictor for the latency distribution and a dichotomous risk for latency for a curegmifs, cureem, cv\_curegmifs or cv\_cureem fitted object.

## Usage

```
## S3 method for class 'mixturecure'
predict(object, newdata, model_select = "AIC", ...)
```

predict.mixturecure 57

#### **Arguments**

object a mixturecure object resulting from curegmifs, cureem, cv\_curegmifs, or

cv\_cureem.

newdata an optional data.frame that minimally includes the incidence and/or latency vari-

ables to use for predicting the response. If omitted, the training data are used.

model\_select either a case-sensitive parameter for models fit using curegmifs or cureem

or any numeric step along the solution path can be selected. The default is model\_select = "AIC" which calculates the predicted values using the coefficients from the model achieving the minimum AIC. The complete list of options

are:

• "AIC" for the minimum AIC (default).

- "mAIC" for the minimum modified AIC.
- "cAIC" for the minimum corrected AIC.
- "BIC", for the minimum BIC.
- "mBIC" for the minimum modified BIC.
- "EBIC" for the minimum extended BIC.
- "logLik" for the step that maximizes the log-likelihood.
- n where n is any numeric value from the solution path.

This option has no effect for objects fit using cv\_curegmifs or cv\_cureem.

.. other arguments

#### Value

p\_uncured a vector of probabilities from the incidence portion of the fitted model represent-

ing the P(uncured).

linear\_latency a vector for the linear predictor from the latency portion of the model.

latency\_risk a dichotomous class representing low (below the median) versus high risk for

the latency portion of the model.

#### See Also

curegmifs, cureem, coef.mixturecure, summary.mixturecure, plot.mixturecure

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
fit <- curegmifs(Surv(Time, Censor) ~ .,
   data = training, x_latency = training,
   model = "weibull", thresh = 1e-4, maxit = 2000,
   epsilon = 0.01, verbose = FALSE
)
predict_train <- predict(fit)
names(predict_train)
testing <- temp$testing
predict_test <- predict(fit, newdata = testing)</pre>
```

58 print.mixturecure

print.mixturecure

Print the contents of a mixture cure fitted object

#### **Description**

This function prints the first several incidence and latency coefficients, the rate (when fitting an exponential or Weibull mixture cure model), and alpha (when fitting a Weibull mixture cure model). This function returns the fitted object invisible to the user.

#### Usage

```
## S3 method for class 'mixturecure'
print(x, max = 6, ...)
```

## **Arguments**

x a mixturecure object resulting from curegmifs, cureem, cv\_cureem, or cv\_curegmifs.

max maximum number of rows in a matrix or elements in a vector to display

other arguments.

#### Value

prints coefficient estimates for the incidence portion of the model and if included, prints the coefficient estimates for the latency portion of the model. Also prints rate for exponential and Weibull models and scale (alpha) for the Weibull mixture cure model. Returns all objects fit using cureem, curegmifs, cv\_cureem, or cv\_curegmifs.

#### Note

The contents of a mixturecure fitted object differ depending upon whether the EM (cureem) or GMIFS (curegmifs) algorithm is used for model fitting or if cross-validation is used. Also, the output differs depending upon whether x\_latency is specified in the model (i.e., variables are included in the latency portion of the model fit) or only terms on the right hand side of the equation are included (i.e., variables are included in the incidence portion of the model).

#### See Also

curegmifs, cureem, coef.mixturecure, summary.mixturecure, plot.mixturecure, predict.mixturecure

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
fit <- curegmifs(Surv(Time, Censor) ~ .,
   data = training, x_latency = training,
   model = "weibull", thresh = 1e-4, maxit = 2000,</pre>
```

sufficient\_fu\_test 59

```
epsilon = 0.01, verbose = FALSE
)
print(fit)
```

```
sufficient_fu_test
```

Test for sufficient follow-up

# Description

Tests for sufficient follow-up using a Kaplan-Meier fitted object.

# Usage

```
sufficient_fu_test(object)
```

# **Arguments**

object a survfit object.

#### Value

p_value	p-value from testing the null hypothesis that there was not sufficient follow-up against the alternative that there was sufficient follow-up
n_n	total number of events that occurred at time > $pmax(0, 2*(last observed event time)-(last observed time))$ and < the last observed event time

N number of observations in the dataset

#### References

Maller, R. A. and Zhou, X. (1996) Survival Analysis with Long-Term Survivors. John Wiley & Sons.

# See Also

```
survfit, cure_estimate, nonzerocure_test
```

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
km_fit <- survfit(Surv(Time, Censor) ~ 1, data = training)
sufficient_fu_test(km_fit)</pre>
```

60 summary.mixturecure

summary.mixturecure Summariz

Summarize a fitted mixture cure object

## Description

summary method for a mixturecure object fit using curegmifs, cureem, cv\_curegmifs, or cv\_cureem.

# Usage

```
## S3 method for class 'mixturecure'
summary(object, ...)
```

# Arguments

```
object a mixturecure object resulting from curegmifs, cureem, cv_curegmifs, or cv_cureem.
... other arguments.
```

#### Value

prints the number of non-zero coefficients from the incidence and latency portions of the fitted mixture cure model when using the minimum AIC to select the final model. When fitting a model using curegmifs or cureem the summary function additionally prints results associated with the following model selection methods: the step and value that maximizes the log-likelihood; the step and value that minimizes the AIC, modified AIC (mAIC), corrected AIC (cAIC), BIC, modified BIC (mBIC), and extended BIC (EBIC). This information can be used to guide the user in the selection of a final model from the solution path.

#### See Also

curegmifs, cureem, coef.mixturecure, plot.mixturecure, predict.mixturecure

```
library(survival)
withr::local_seed(1234)
temp <- generate_cure_data(n = 100, j = 10, n_true = 10, a = 1.8)
training <- temp$training
fit <- curegmifs(Surv(Time, Censor) ~ .,
   data = training, x_latency = training,
   model = "weibull", thresh = 1e-4, maxit = 2000,
   epsilon = 0.01, verbose = FALSE
)
summary(fit)</pre>
```

# **Index**

* datasets	cure_estimate, 31, 47, 59			
	cureem, 23, 25, 36, 56–58, 60			
amltest, 2				
amltrain, 11	curegmifs, 23, 28, 40, 56–58, 60			
pediatric_flt3, 49	cv_cureem, 28, 32			
* htest	$cv\_curegmifs, 30, 37$			
nonzerocure_test, 47	dim mintura 2002 10			
sufficient_fu_test, 59	dim.mixturecure, 40			
* methods	family.mixturecure, 41			
coef.mixturecure, 22	•			
dim.mixturecure, 40	formula.mixturecure, 42			
family.mixturecure, 41	ganamata auma data 12			
formula.mixturecure, 42	generate_cure_data, 43			
logLik.mixturecure, 45	logLik.mixturecure, 45			
nobs.mixturecure, 46	TOGETK. IIITX tull ecul e, 43			
plot.mixturecure, 55	nobs.mixturecure, 46			
predict.mixturecure, 56	nonzerocure_test, 31, 47, 59			
print.mixturecure, 58	npar_mixturecure, 48			
summary.mixturecure, 60	npar_mixturecure, 46			
* models	pediatric_flt3,49			
	plot.mixturecure, 23, 55, 57, 58, 60			
cureem, 25	· · · · · · · · · · · · · · · · · · ·			
curegmifs, 28	predict.mixturecure, 23, 56, 56, 58, 60			
cv_cureem, 32	print.mixturecure, 58			
cv_curegmifs, 37	sufficient fu test 21 47 50			
* regression	sufficient_fu_test, 31, 47, 59			
cureem, 25	summary.mixturecure, 23, 56–58, 60			
curegmifs, 28	survfit, <i>31</i> , <i>47</i> , <i>59</i>			
cv_cureem, 32				
cv_curegmifs, 37				
* univar				
auc_mcm, 21				
concordance_mcm, 23				
cure_estimate, 31				
54. 5_55 52.ma 55, <i>5</i> 2				
amltest, 2				
amltrain, 11				
auc_mcm, 21, 24				
auc_iiiciii, 21, 27				
coef.mixturecure, 22, 56-58, 60				
coefficients (coef.mixturecure), 22				
concordance_mcm, 22, 23				
concordance_incii, 22, 23				