

The `tabularht` package

Heiko Oberdiek*

2019/12/29 v2.7

Abstract

This package defines some environments that adds a height specification to tabular and array.

Contents

1 Usage	2
1.1 Option <code>vlines</code>	2
1.2 Limitations	3
1.3 Compatibility	3
1.4 Examples	3
1.4.1 Example 1	3
1.4.2 Example 2	3
2 Implementation	4
2.1 Environments	4
2.2 Options	6
2.3 Option <code>vlines</code> , driver independent stuff	7
2.4 Driver pdftex	7
2.5 DVI drivers	11
3 Installation	13
3.1 Download	13
3.2 Bundle installation	13
3.3 Package installation	14
3.4 Refresh file name databases	14
3.5 Some details for the interested	14
4 History	14
[2005/09/22 v1.0]	14
[2005/10/16 v2.0]	15
[2005/10/18 v2.1]	15
[2006/02/20 v2.2]	15
[2006/12/22 v2.3]	15
[2007/03/21 v2.4]	15
[2007/04/11 v2.5]	15
[2016/05/16 v2.6]	15
[2019/12/29 v2.7]	15
5 Index	15

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

1 Usage

```
\usepackage{tabularht}
```

The package provides the following environments that extend the tabular/array environment by a height specification as first argument:

- `tabularht`, `tabularht*`
- `arrayht`
- `tabularhtx` (if package `tabularx` is loaded)

The height argument allows a length specification, package `calc` is supported if used. This means, the tabular will have the specified height. You can also use the prefixes `to=` and `spread=`. `to=` is the default, `spread=` means, the natural height of the tabular box is changed by the length after `spread=`.

Examples:

```
\begin{tabularht}{1in}           → height is 1in  
\begin{tabularht}{to=1in}      → height is 1in  
\begin{tabularht}{spread=0pt} → natural height, same as \begin{tabular}  
\begin{tabularht}{spread=1in}  → natural height increased by 1in
```

Hint: See also package `tabularkv`, it provides an interface, where most parameters for the environments can be given by key-value pairs.

```
\interrowspace{...}
```

Adds space between table rows. It is essentially the same as `\noalign{\vspace{...}}`.

```
\interrowfill
```

Short for `\interrowspace{\fill}`

```
\interrowstart ... \interrowstop
```

Marker commands, useful for option `vlines`.

1.1 Option `vlines`

Warning: This stuff is experimental.

Vertical lines are interrupted, if space is inserted in `\noalign`, `\interrowspace`, `\addlinespace` (`booktabs`), between double `\hlines`. This option tries to detect and add the vertical lines. The lines in a tabular with `tabularht` support (environments of this package) are numbered from left to right. The gap that is controlled by `\interrowspace` or in between `\interrowstart` and `\interrowstop` is then filled with the detected vertical lines.

If only a limited selection of the lines should be drawn, the commands know an optional argument with a list of line numbers, e.g.

```
\begin{tabularht}{50mm}{|1|1|}  
Hello & World\\  
\interrowfill[1,3]  
Foo & Bar  
\end{tabularht}
```

There are three lines, but the middle line is not drawn in the gap between the first and second row. Zero can be used to suppress all lines:

```
\interrowspace[0]{10mm}
```

The syntax of the commands with the optional argument with the line number list $\langle list \rangle$. $\langle list \rangle$ is a comma separated list of numbers, $\langle height \rangle$ means the height specification described above with the optional prefixes `to=` or `spread=`.

```
\interrowspace [⟨list⟩] {⟨height⟩}  
\interrowfill [⟨list⟩]  
\interrowstart [⟨list⟩] ... \interrowstop
```

Option `vlines` is driver dependent and uses ε - \TeX features.

pdftex: pdft \TeX in PDF mode. Here the positions of the lines are written with the help of the `\pdfsavepos` feature into the `.aux` file(s). Therefore you need two La \TeX runs to get the lines.

dvips: Here, PostScript's currentpoint is used to get the line positions. The lines are then drawn at the end of the page. Thus one $\text{\LaTeX}/\text{dvips}$ run is sufficient for this option.

Other drivers:

PostScript drivers: probably possible, an end of page hook would be nice.

V \TeX : with GeX (PostScript interpreter) probably possible.

dvipdfm: no idea. The big problem is, how to get the current position?

1.2 Limitations

- Vertical lines are interrupted by `\noalign{\vfill}`.

1.3 Compatibility

- `array`, `delarray`, `tabularx` are supported.
- There can be problems with packages that redefine `\@array` (or `\@@array`, `\@tabarray`) and `\@arrayrule` (for option `vlines`).
- `colortbl`: it should at least work, but there isn't support for filling the gaps with color, neither the rules nor the backgrounds.

1.4 Examples

1.4.1 Example 1

```
1 (*example1)  
2 \documentclass{article}  
3 \usepackage{tabularht}  
4  
5 \begin{document}  
6 \fbox{  
7   \begin{tabularht}{1in}{4in}{@{}l@{\extracolsep{\fill}}r@{}}  
8     upper left corner & upper right corner \\%  
9     \noalign{\vfill}%  
10    \multicolumn{2}{c}{bounding box} \\%  
11    \noalign{\vfill}%  
12    lower left corner & lower right corner \\%  
13  \end{tabularht}  
14 }  
15 \end{document}  
16 
```

1.4.2 Example 2

```

17 <*example2>
18 \documentclass{article}
19 \usepackage{booktabs}
20 \usepackage[dvips,vlines]{tabularht}
21
22 \begin{document}
23
24 \begin{tabularht}{spread=0pt}{|1|1|}%
25   \hline
26   First&Line\\%
27   \hline
28 \interrowstart
29   \addlinespace[10mm]\\%
30 \interrowstop
31   \hline
32   Second&Line\\%
33 \interrowstart
34   \hline
35   \hline
36 \interrowstop
37   Third&Line\\%
38   \hline
39 \interrowspace{10mm}\\%
40   \hline
41   Fourth&Line\\%
42   \hline
43 \end{tabularht}
44
45 \end{document}
46 </example2>

```

2 Implementation

```

47 <*package>
Package identification.
48 \NeedsTeXFormat{LaTeX2e}
49 \ProvidesPackage{tabularht}%
50 [2019/12/29 v2.7 Tabular with height specified (HO)]

```

2.1 Environments

```

51 \let\@toarrayheight\@empty
52 \let\tabH@array@init\@empty
53
54 \toks@=%
55 \begingroup
56   \long\def\x{\vcenter{#1}\fi\fi\bgroup\#2\sharp\#3\#4\@nil}%
57   \endgroup
58   \gdef\@array[##1]##2{%
59     \tabH@array@init
60     #1%
61     \vcenter{#1}\fi\fi
62     \@toarrayheight
63     \bgroup
64     \let\@toarrayheight\@empty
65     #2\sharp\#3\#4%
66   }%
67   }%
68 \expandafter\x\@array[#1]{#2}\@nil % hash-ok
69 }
70 \edef\tabH@patch@array{\the\toks@}
71 \def\tabH@patch@array{%
72   \ifx\@array\@array

```

```

73      \def\reserved@a{\let\@@array\@array}%
74  \else
75      \let\reserved@a\relax
76  \fi
77  \tabH@patch@array
78  \reserved@a
79 }
80 \tabH@patch@array
81
82 \@ifpackageloaded{array}{}{%
83   \AtBeginDocument{%
84     \ifpackageloaded{array}{}{%
85       \tabH@patch@array
86     }{}%
87   }%
88 }
89
90 \def\tabH@setheight#1{%
91   \tabH@setheight#1==\@nil
92 }
93 \def\tabH@setheight#1=#2=#3\@nil{%
94   \ifx\#2\#\%
95     \setlength{\dimen0}{#1}%
96     \edef\@toarrayheight{to\the\dimen0}%
97   \else
98     \edef\tabH@temp{\zap@space#1 \empty}%
99     \ifx\tabH@temp\tabH@to
100    \else
101      \ifx\tabH@temp\tabH@spread
102    \else
103      \PackageError{tabularht}{%
104        Unknown height specifier %
105        '\expandafter\strip@prefix\meaning\tabH@temp'%
106      }{%
107        The height dimension for tabular height can be prefixed%
108        \MessageBreak
109        with 'to=' or 'spread=', default is 'to='.%%
110      }%
111      \let\tabH@temp\tabH@to
112    \fi
113  \fi
114  \setlength{\dimen0}{#2}%
115  \edef\@toarrayheight{\tabH@temp\the\dimen0}%
116 \fi
117 }
118 \def\tabH@to{to}
119 \def\tabH@spread{spread}

```

First argument is the height of the table, then the original arguments for tabular follow.

```

120 \newenvironment{tabularht}[1]{%
121   \tabH@setheight{#1}%
122   \tabular
123 }{%
124   \endtabular
125 }
126
127 \newenvironment{tabularht*}[1]{%
128   \tabH@setheight{#1}%
129   \nameuse{tabular*}%
130 }{%
131   \nameuse{endtabular*}%
132 }

```

```

133
134 \newenvironment{tabularhtx}[1]{%
135   \tabH@setheight{#1}%
136   \tabularx
137 }{%
138   \endtabularx
139 }
140
141 \newenvironment{arrayht}[1]{%
142   \tabH@setheight{#1}%
143   \array
144 }{%
145   \endarray
146 }
147
148 \def\interrowspace{%
149   \noalign\bgroup
150   \tabH@interrowspace
151 }
152 \newcommand*\tabH@interrowspace[2][]{%
153   \tabH@vspace{#1}{#2}%
154   \egroup
155 }
156 \def\interrowfill{%
157   \noalign\bgroup
158   \tabH@interrowfill
159 }
160 \newcommand*\tabH@interrowfill[1][]{%
161   \tabH@vspace{#1}{\fill}%
162   \egroup
163 }
164 \def\tabH@vspace#1#2{%
165   \tabH@vspace@start{#1}%
166   \vspace{#2}%
167   \tabH@vspace@stop
168 }
169 \let\tabH@vspace@start\gobble
170 \let\tabH@vspace@stop\empty
171
172 \newcommand*\interrowstart{%
173   \noalign\bgroup
174   \tabH@interrowstart
175 }
176 \newcommand*\tabH@interrowstart[1][]{%
177   \tabH@vspace@start{#1}%
178   \egroup
179 }
180 \newcommand*\interrowstop{%
181   \noalign{\tabH@vspace@stop}%
182 }

```

2.2 Options

```

183 \providecommand*\tabH@driver{}%
184
185 \DeclareOption{vlines}{%
186   \let\tabH@temp\relax
187 }
188 \DeclareOption{pdftex}{}
189 \DeclareOption{dvips}{%
190   \def\tabH@driver{dvips}%
191 }
192 \ProcessOptions*\relax

```

```

193
194 \ifx\tabH@temp\relax
195 \else
196   \expandafter\endinput
197 \fi
198
199 \begingroup
200   \@ifundefined{eTeXversion}%
201     \PackageError{tabularht}{%
202       Option 'vlines' requires eTeX%
203     }{%
204       Use of eTeX is recommended for LaTeX, see ltnews16.%%
205     }%
206   \endgroup
207   \endinput
208 }{%
209 \endgroup

```

2.3 Option vlines, driver independent stuff

```

210 \begingroup
211   \let\@addtoreset\gobbletwo
212   \newcounter{tabH@unique}%
213 \endgroup
214 \let\tabH@currenttab\empty
215
216 \def\tabH@array@init{%
217   \ifx\@toarrayheight\empty
218     % ignore vertical lines of nested tabular environments
219     \let\tabH@currenttab\empty
220   \else
221     \stepcounter{tabH@unique}%
222     \edef\tabH@currenttab{\the\c@tabH@unique}%
223   \fi
224 }
225
226 \renewcommand*\{@arrayrule}{%
227   \@addtopreamble{%
228     \hskip -.5\arrayrulewidth
229     \ifx\tabH@currenttab\empty
230     \else
231       \tabH@vrule{\tabH@currenttab}%
232     \fi
233   \begingroup
234     \expandafter\ifx\csname CT@arc@\endcsname\relax
235     \else
236       \expandafter\CT@arc@
237     \fi
238     \vline
239   \endgroup
240   \hskip -.5\arrayrulewidth
241 }%
242 }
243 \let\tabH@arrayrule\@arrayrule
244 \AtBeginDocument{%
245   \@ifpackageloaded{colortbl}{%
246     \let\@arrayrule\tabH@arrayrule
247   }{%
248   }%
249
250 \let\tabH@vrule\@gobble

```

2.4 Driver pdftex

```

251 \RequirePackage{iftex}[2019/11/07]
252 \ifpdf
253   \begingroup
254     \@ifundefined{pdfsavepos}{%
255       \PackageError{tabularht}{%
256         Your pdfTeX is too old%
257       }{%
258         \string\pdfsavepos\space is missing.%}
259     }%
260   \endgroup
261   \csname fi\endcsname
262   \endinput
263 }{}%
264
265 \let\on@line\empty
266 \PackageInfo{tabularht}{%
267   Using driver 'pdftex' because of pdfTeX in PDF mode%
268 }%
269 \endgroup
270
271 \protected\def\tabH@vrule#1{%
272   \if@filesw
273     \pdfsavepos
274     \protected@write\@auxout{%
275       \let\tabH@lastxpos\relax
276     }{%
277       \tabH@aux@vrule{\#1}{\tabH@lastxpos}%
278     }%
279   \fi
280 }%
281
282 \def\tabH@lastxpos{\the\pdflastxpos}%
283 \def\tabH@lastypos{\the\pdflastypos}%
284
285 % The .aux file contains three commands:
286 % \tabH@aux@vrule{tabular id}{x position}
287 % \tabH@aux@vstart{tabular id}{row id}{x position}{y position}
288 % \tabH@aux@vstop{y position}
289 %
290 \AtBeginDocument{%
291   % The .aux files are read the first time before
292   % \AtBeginDocument and later at \end{document}.
293   % \tabH@aux@done is a marker to distinguish
294   % between these two readings. Only in the first
295   % case we need the \tabH@aux@... commands.
296   \let\tabH@aux@done\empty
297   \if@filesw
298     \immediate\write\@mainaux{%
299       \percentchar\percentchar BeginProlog: tabularht%
300     }%
301     % items in the aux file are executed,
302     % if tabularht is loaded
303     % and during the aux file read at \begin{document} only
304     \immediate\write\@mainaux{%
305       \detokenize{%
306         % the \tabH@aux@... commands are needed only if
307         % tabularht is loaded with driver pdftex.
308         \@ifundefined{tabH@aux@vrule}{\secondoftwo\firstofone
309         }{%
310           % disable commands except for the first .aux files reading
311           \@ifundefined{tabH@aux@done}{\gobble\firstofone
312         }%
313       }%
314     }%
315   }%
316 }

```

```

313      }%
314      \let\tabH@aux@vrule\@gobbletwo
315      \let\tabH@aux@vstart\@gobblefour
316      \let\tabH@aux@vstop\@gobble
317      }%
318      }%
319  }%
320  \immediate\write\@mainaux{%
321    \percentchar\percentchar EndProlog: tabularht%
322  }%
323  \fi
324 }%
325
326 % the x positions of vrules are stored in
327 % \tabH@<tabcount>list with distinct values
328 \protected\def\tabH@aux@vrule#1#2{%
329   \@ifundefined{tabH@#1list}{%
330     \expandafter\xdef\csname tabH@#1list\endcsname{%
331       \noexpand\do{\#2}%
332     }%
333   }{%
334     \begingroup
335       \def\x{\#2}%
336       \let\y\undefined
337       \let\do\tabH@do@add
338       \expandafter\xdef\csname tabH@#1list\endcsname{%
339         \csname tabH@#1list\endcsname\empty
340         \ifx\y\undefined
341           \noexpand\do{\x}%
342         \fi
343       }%
344     \endgroup
345   }%
346 }%
347 \def\tabH@do@add#1{%
348   \ifx\y\undefined
349     \ifnum#1<\x\space
350     \else
351       \expandafter\ifx\csname y\endcsname\relax\fi
352       \ifnum#1>\x\space
353         \noexpand\do{\x}%
354       \fi
355     \fi
356   \fi
357   \noexpand\do{\#1}%
358 }%
359
360 \def\tabH@vspace@start#1{%
361   \if@filesw
362     \stepcounter{tabH@unique}%
363     \edef\tabH@currentrow{\the\c@tabH@unique}%
364     \pdfsavepos
365     \protected@write\@auxout{%
366       \let\tabH@lastxpos\relax
367       \let\tabH@lastypos\relax
368     }{%
369       \tabH@aux@vstart{\tabH@currenttab}{\tabH@currentrow}%
370       {\tabH@lastxpos}{\tabH@lastypos}%
371     }%
372   \fi
373   \begingroup
374     \edef\@tabH@\tabH@currenttab\row\tabH@currentrow}%

```

```

375      \expandafter\let\expandafter\x\csname a x\endcsname
376      \ifx\x\relax
377      \else
378          \expandafter\let\expandafter\y\csname a y\endcsname
379          \expandafter\let\expandafter\l
380              \csname tabH@\tabH@currenttab list\endcsname
381          \ifx\l\relax
382          \else
383              \def\f{\#1}%
384              \ifx\f\empty
385                  \let\do\tabH@do@set
386              \else
387                  \count@=\z@
388                  \let\do\tabH@do@filter
389                  \fi
390                  \setbox\z@=\hbox{\l}%
391                  \wd\z@=\z@
392                  \dp\z@=\z@
393                  \copy\z@
394                  \fi
395                  \fi
396          \endgroup
397      }%
398 \def\tabH@vspace@stop{%
399     \if@filesw
400         \pdfsavepos
401         \protected@write\@auxout{%
402             \let\tabH@lastypos\relax
403         }{%
404             \tabH@aux@vstop{\tabH@lastypos}%
405         }%
406     \fi
407 }%
408 \def\tabH@do@set#1{%
409     \hbox to \z@{%
410         \hskip \dimexpr #1sp - \x sp\relax
411         \vrule \@width\arrayrulewidth
412             \@depth\dimexpr \y sp\relax
413         \hss
414     }%
415 }%
416 \def\tabH@do@filter{%
417     \tempswafalse
418     \advance\count@\@ne
419     \for\e:=\f\do{%
420         \ifnum\c=\count@
421             \tempswatrue
422         \fi
423     }%
424     \if@tempswa
425         \expandafter\tabH@do@set
426     \else
427         \expandafter\@gobble
428     \fi
429 }%
430
431 \protected\def\tabH@aux@vstart#1#2#3#4{%
432     \def\tabH@current@vstart{{#1}{#2}{#3}{#4}}%
433 }%
434 \protected\def\tabH@aux@vstop{%
435     \expandafter\tabH@aux@v\tabH@current@vstart
436 }%

```

```

437  \def\tabH@aux@v#1#2#3#4#5{%
438      \expandafter\gdef\csname tabH@#1row#2x\endcsname{#3}%
439      \expandafter\xdef\csname tabH@#1row#2y\endcsname{%
440          \the\numexpr #4 - #5\relax
441      }%
442  }%
443
444  \csname fi\endcsname
445  \endinput
446
447 \fi

```

2.5 DVI drivers

```

448 \ifx\tabH@driver\empty
449   \PackageError{tabularht}{%
450     Missing DVI driver, option ‘vlines’ disabled%
451   }%
452   Supported DVI drivers: dvips.%
453 }%
454 \expandafter\endinput
455 \fi
456
457 \def\tabH@driver@dvips{%
458   \def\tabH@literalps##1{\special{ps:SDict begin ##1 end}}%
459   \def\tabH@headerps##1{\special{! ##1}}%
460 }
461
462 \@onelvel@sanitize\tabH@driver
463 \@ifundefined\tabH@driver@\tabH@driver}{%
464   \PackageError{tabularht}{%
465     Unsupported driver ‘\tabH@driver’%
466   }%
467   Supported DVI drivers: dvips.%
468 }%
469 \endinput
470 }{}%
471
472 \begingroup
473   \let\on@line\empty
474   \PackageInfo{tabularht}{%
475     Using driver ‘\tabH@driver’%
476   }%
477 \endgroup
478 \csname tabH@driver@\tabH@driver\endcsname
479
480 \protected\def\tabH@vrule#1#2\vrule#3\arrayrulewidth{%
481   #2% \fi or empty
482   % hack to get rid of maxdrift rounding of dvips,
483   % thus simulate a large motion
484   \kern1in\relax
485   \tabH@literalps{%
486     #1 tabH.vrule %
487     Resolution neg 0 translate%
488   }%
489   \vrule#3\arrayrulewidth
490   \tabH@literalps{Resolution 0 translate}%
491   \kern-1in\relax
492 }
493
494 \def\tabH@vspace@start#1{%
495   \begingroup
496     \let\y\empty

```

```

497      \@for\x:=#1\do{%
498          \ifx\y\@empty
499              \edef\y{\x}%
500          \else
501              \edef\y{\y\space\x}%
502          \fi
503      }%
504      \tabH@literalps{\tabH@currenttab[\y]currentpoint exch pop}%
505  \endgroup
506 }
507 \def\tabH@vspace@stop{%
508   \tabH@literalps{%
509     currentpoint exch pop %
510     \number\dimexpr\arrayrulewidth\relax\space
511     tabH.vspace%
512   }%
513 }
514
515 \tabH@headerps{%
516   userdict begin%
517     /tabH.list 10 dict def%
518     /tabH.job [] def %
519   end%
520   /tabH.vrule{%
521     10 string cvs cvn dup tabH.list exch known{%
522       tabH.list exch dup [ exch tabH.list exch get %
523       currentpoint pop round exch true exch{%
524         % tabH.list key [ ... x true i
525         % tabH.list key [ ... false i
526         exch{%
527           % ... [ ... x i
528           2 copy lt{false}{%
529             2 copy eq{pop false}{exch true}ifelse%
530             }ifelse%
531             }{false}ifelse%
532           }forall %
533           pop%
534           ]put%
535         }{%
536           tabH.list exch[currentpoint pop round]put%
537         }ifelse%
538   }bind def%
539   % <tab num> <cols array> <ytop> <ybottom> <rulerwidth[sp]>
540   /tabH.vspace{%
541     userdict begin %
542       10 dict dup begin %
543         exch 65536 div Resolution mul 72.27 div %
544         % dvips uses a poor man's ceil function
545         % see dopage.c before "drawrule": (int)(... + 0.9999999)
546         0.9999999 add truncate%
547         /rulerwidth exch def %
548         exch/ybottom exch def %
549         exch/ytop exch def %
550         exch/cols exch def %
551         exch/tabkey exch 10 string cvs cvn def %
552       end%
553       /tabH.job exch[exch userdict/tabH.job getaload pop]def %
554     end%
555   }bind def %
556   % Now we do the work at the end of the page.
557   % Unhappily "eop-hook" cannot be used, because "eop"
558   % executes "restore" before, so that all data are lost.

```

```

559 TeXDict begin%
560   /eop%
561   [%
562   {%
563     tabH.job{%
564       begin%
565         /colarray %
566         tabH.list tabkey known{tabH.list tabkey get}{[]}ifelse %
567         def %
568         cols length 0 eq not{%
569           /colarray[%
570             cols{1 sub %
571               dup 0 lt{pop}{%
572                 dup colarray length ge{pop}{%
573                   colarray exch get%
574                 }ifelse%
575               }ifelse%
576             }forall%
577           ]def%
578         }if %
579         colarray{%
580           % (rulewidth) == rulewidth == % debug
581           Resolution sub %
582           ytop rulewidth ytop ybottom sub v%
583         }forall %
584         end%
585       }forall%
586       % tabH.list{== ==}forall % debug
587     }bind aload pop %
588     TeXDict /eop get aload pop%
589   ]cvx def %
590 end%
591 }
592 </package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/tabularht.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/tabularht.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for T_EX Files” ([CTAN:pkg/tds](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

`unzip oberdiek.tds.zip -d ~/texmf`

¹[CTAN:pkg/tabularht](#)

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain `TEX`:

```
tex tabularht.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

<code>tabularht.sty</code>	→ <code>tex/latex/oberdiek/tabularht.sty</code>
<code>tabularht.pdf</code>	→ <code>doc/latex/oberdiek/tabularht.pdf</code>
<code>tabularht-example1.tex</code>	→ <code>doc/latex/oberdiek/tabularht-example1.tex</code>
<code>tabularht-example2.tex</code>	→ <code>doc/latex/oberdiek/tabularht-example2.tex</code>
<code>tabularht.dtx</code>	→ <code>source/latex/oberdiek/tabularht.dtx</code>

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your `TEX` distribution (`TEX Live`, `MiKETEX`, ...) relies on file name databases, you must refresh these. For example, `TEX Live` users run `texhash` or `mktexlsr`.

3.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain T_EX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{tabularht.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with `pdflatATEX`:

```
pdflatex tabularht.dtx
makeindex -s gind.ist tabularht.idx
pdflatex tabularht.dtx
makeindex -s gind.ist tabularht.idx
pdflatex tabularht.dtx
```

4 History

[2005/09/22 v1.0]

- First public version.

[2005/10/16 v2.0]

- Height specification allows `to=...` or `spread=...`, default is `to=`.
- Option `vlines` added, drivers `pdftex` and `dvi`.
- `\interrowspace`, `\interrowfil`, and `\interrowstart...\\interrowstop` added.

[2005/10/18 v2.1]

- Fix for package `colortbl`, but the colors of `colortbl` remain unsupported.

[2006/02/20 v2.2]

- Code is not changed.
- DTX framework.

[2006/12/22 v2.3]

- Documentation fix.
- Fix in code of option `vlines`.

[2007/03/21 v2.4]

- Fix: Counter `tabh@unique` must not be changed by `\include`.

[2007/04/11 v2.5]

- Line ends sanitized.

[2016/05/16 v2.6]

- Documentation updates.

[2019/12/29 v2.7]

- Use `\iftex` package.

5 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	
<code>\@array</code>	72, 73
<code>\@addtopreamble</code>	227
<code>\@addtoreset</code>	211
<code>\@array</code>	58, 68, 72, 73
<code>\@arrayrule</code>	226, 243, 246
<code>\@auxout</code>	274, 365, 401
<code>\@depth</code>	412
<code>\@empty</code>	51, 52, 64, 98, 170, 214, 217, 219, 229, 265, 296, 339, 384, 448, 473, 496, 498
<code>\@firstofone</code>	308, 311
<code>\@for</code>	419, 497
<code>\@gobble</code>	169, 250, 311, 316, 427
<code>\@gobblefour</code>	315
<code>\@gobbletwo</code>	211, 314
<code>\@ifpackageloaded</code>	82, 84, 245
<code>\@ifundefined</code>	
<code>\@mainaux</code>	298, 304, 320
<code>\@nameuse</code>	129, 131
<code>\@ne</code>	418
<code>\@nil</code>	56, 68, 91, 93
<code>\@onelevel@sanitize</code>	462
<code>\@percentchar</code>	299, 321
<code>\@secondoftwo</code>	308
<code>\@sharp</code>	56, 65
<code>\@tempswafalse</code>	417

\@tempswattrue	421	\if@tempswa	424
\@toarrayheight	51, 62, 64, 96, 115, 217	\ifnum	349, 352, 420
\@undefined	336, 340, 348	\ifpdf	252
\@width	411	\ifx	72, 94, 99, 101, 194, 217, 229, 234, 340, 348, 351, 376, 381, 384, 448, 498
\\"	8, 10, 12, 26, 32, 37, 41, 94	\immediate	298, 304, 320
		\interrowfill	2, 156
		\interrowspace	2, 39, 148
		\interrowstart	2, 28, 33, 172
		\interrowstop	30, 36, 180
		K	
		\kern	484, 491
		L	
		\l	379, 381, 390
		M	
		\meaning	105
		\MessageBreak	108
		\multicolumn	10
		N	
		\NeedsTeXFormat	48
		\newcommand	152, 160, 172, 176, 180
		\newcounter	212
		\newenvironment	120, 127, 134, 141
		\noalign	9, 11, 149, 157, 173, 181
		\number	510
		\numexpr	440
		O	
		\on@line	265, 473
		P	
		\PackageError	103, 201, 255, 449, 464
		\PackageInfo	266, 474
		\pdflastxpos	282
		\pdflastypos	283
		\pdfsavepos	258, 273, 364, 400
		\ProcessOptions	192
		\protected	271, 328, 431, 434, 480
		\protected@write	274, 365, 401
		\providecommand	183
		\ProvidesPackage	49
		R	
		\renewcommand	226
		\RequirePackage	251
		\reserved@a	73, 75, 78
		S	
		\setbox	390
		\setlength	95, 114
		\space	258, 349, 352, 501, 510
		\special	458, 459
		\stepcounter	221, 362
		\strip@prefix	105
		T	
		\tabH@	327
		\tabH@setheight	91, 93
		\tabH@array@init	52, 59, 216
		\tabH@arrayrule	243, 246
		\tabH@aux@	295, 306

\tabH@aux@done	293, 296	\tabH@vspace@stop	
\tabH@aux@v	435, 437		167, 170, 181, 398, 507
\tabH@aux@vrule ...	277, 286, 314, 328	\tabular	122
\tabH@aux@vstart ...	287, 315, 369, 431	\tabularx	136
\tabH@aux@vstop ...	288, 316, 404, 434	\the .	70, 96, 115, 222, 282, 283, 363, 440
\tabH@current@vstart	432, 435	\toks@	54, 70
\tabH@currentrow	363, 369, 374		
\tabH@currenttab	214, 219,	U	
	222, 229, 231, 369, 374, 380, 504	\usepackage	3, 19, 20
\tabH@do@add	337, 347		
\tabH@do@filter	388, 416	V	
\tabH@do@set	385, 408, 425	\vcenter	56, 61
\tabH@driver	183,	\vfill	9, 11
	190, 448, 462, 463, 465, 475, 478	\vline	238
\tabH@driver@dvips	457	\vrule	411, 480, 489
\tabH@headerps	459, 515	\vspace	166
\tabH@interrowfill	158, 160		
\tabH@interrowspace	150, 152	W	
\tabH@interrowstart	174, 176	\wd	391
\tabH@lastxpos ...	275, 277, 282, 366, 370	\write	298, 304, 320
\tabH@lastypos ...	283, 367, 370, 402, 404		
\tabH@literalps	458, 485, 490, 504, 508	X	
\tabH@patch@@array	71, 80, 85	\x	56, 68, 335, 341, 349, 352,
\tabH@patch@array	70, 77		353, 375, 376, 410, 497, 499, 501
\tabH@setheight ...	90, 121, 128, 135, 142	Y	
\tabH@spread	101, 119	\y	336, 340, 348,
\tabH@temp	98,		378, 412, 496, 498, 499, 501, 504
	99, 101, 105, 111, 115, 186, 194	Z	
\tabH@to	99, 111, 118	\z@	387, 390, 391, 392, 393, 409
\tabH@vrule	231, 250, 271, 480	\zap@space	98
\tabH@vspace	153, 161, 164		
\tabH@vspace@start	165, 169, 177, 360, 494		