

The `ltshipout` documentation*

Frank Mittelbach, L^AT_EX Project Team

October 31, 2024

Contents

1	Introduction	2
1.1	Overloading the <code>\shipout</code> primitive	2
1.2	Provided hooks	3
1.3	Legacy L ^A T _E X commands	5
1.4	Special commands for use inside the hooks	5
1.5	Provided LuaT _E X callbacks	6
1.6	Information counters	6
1.7	Debugging shipout code	7
2	Emulating commands from other packages	7
2.1	Emulating <code>atbegshi</code>	7
2.2	Emulating <code>everyshi</code>	8
2.3	Emulating <code>atenddvi</code>	8
2.4	Emulating <code>everypage</code>	9
3	The Implementation	9
3.1	Debugging	9
3.2	Handling the end of job hook	22
4	Legacy L^AT_EX 2_c interfaces	25
5	Internal commands needed elsewhere	25
6	Package emulation for compatibility	27
6.1	Package <code>atenddvi</code> emulation	27
6.2	Package <code>atbegshi</code> emulation	27
6.3	Package <code>everyshi</code> emulation	29
Index	29	

*This file has version v1.0n dated 2024/10/22, © L^AT_EX Project.

1 Introduction

The code provides an interface to the `\shipout` primitive of T_EX which is called when a finished pages is finally “shipped out” to the target output file, e.g., the `.dvi` or `.pdf` file. A good portion of the code is based on ideas by Heiko Oberdiek implemented in his packages `atbegshi` and `atenddvi` even though the interfaces are somewhat different.¹

1.1 Overloading the `\shipout` primitive

`\shipout` With this implementation T_EX’s `shipout` primitive is no longer available for direct use. Instead `\shipout` is running some (complicated) code that picks up the box to be shipped out regardless of how that is done, i.e., as a constructed `\vbox` or `\hbox` or as a box register.

It then stores it in a named box register. This box can then be manipulated through a set of hooks after which it is shipped out for real.

Each `shipout` that actually happens (i.e., where the material is not discarded for one or the other reason) is recorded and the total number is available in a readonly variable and in a L^AT_EX counter.

`\RawShipout` This command implements a simplified `shipout` that bypasses the foreground and background hooks, e.g., only `shipout/firstpage` and `shipout/lastpage` are executed and the total `shipout` counters are incremented.

The command doesn’t use `\ShipoutBox` but its own private box register so that it can be used inside of `shipout` hooks to do some additional `shipout`s while already in the output routine with the current page being stored in `\ShipoutBox`. It does have access to `\ShipoutBox` if it is used in `shipout/before` (or `shipout/after`) and can use its content.

It is safe to use it in `shipout/before` or `shipout/after` but not necessarily in the other `shipout/...` hooks as they are intended for special processing.

`\ShipoutBox` `\l_shipout_box` This box register is called `\ShipoutBox` (alternatively available via the L3 name `\l_-\l_shipout_box`).

This box is a “local” box and assignments to it should be done only locally. Global assignments (as done by some packages with older code where this is box is known as 255) may work but they are conceptually wrong and may result in errors under certain circumstances.

During the execution of `shipout/before` this box contains the accumulated material for the page, but not yet any material added by other `shipout` hooks. During execution of `shipout/after`, i.e., after the `shipout` has happened, the box also contains any background or foreground material.

Material from the hooks `shipout/firstpage` or `shipout/lastpage` is not included (but only used during the actual `shipout`) to facilitate reuse of the box data (e.g., `shipout/firstpage` material should never be added to a later page of the output).

¹Heiko’s interfaces are emulated by the kernel code, if a document requests his packages, so older documents will continue to work.

```
\l_shipout_box_ht_dim  
\l_shipout_box_dp_dim  
\l_shipout_box_wd_dim  
\l_shipout_box_ht_plus_dp_dim
```

The shipout box dimensions are available in the L3 registers `\l_shipout_box_ht_dim`, etc. (there are no L^AT_EX 2_< names).² These variables can be used inside the hook code for `shipout/before`, `shipout/foreground` and `shipout/background` if needed.

1.2 Provided hooks

```
shipout/before  
shipout/after  
shipout/foreground  
shipout/background  
shipout/firstpage  
shipout/lastpage
```

The code for `\shipout` offers a number of hooks into which packages (or the user) can add code to support different use cases. These are:

shipout/before This hook is executed after the finished page has been stored in `\ShipoutBox / \l_shipout_box`. It can be used to alter that box content or to discard it completely (see `\DiscardShipoutBox` below).

You can use `\RawShipout` inside this hook for special use cases. It can make use of `\ShipoutBox` (which doesn't yet include the background and foreground material).

Note: It is not possible (or say advisable) to try and use this hook to typeset material with the intention to return it to main vertical list, it will go wrong and give unexpected results in many cases—for starters it will appear after the current page not before or it will vanish or the vertical spacing will be wrong!

shipout/background This hook adds a picture environment into the background of the page with the (0,0) coordinate in the top-left corner using a `\unitlength` of 1pt.

It should therefore only receive `\put` commands or other commands suitable in a `picture` environment and the vertical coordinate values would normally be negative.

Technically this is implemented by adding a zero-sized `\hbox` as the very first item into the `\ShipoutBox` containing that `picture` environment. Thus the rest of the box content will overprint what ever is typeset by that hook.

shipout/foreground This hook adds a picture environment into the foreground of the page with the (0,0) coordinate in the top-left corner using a `\unitlength` of 1pt.

Technically this is implemented by adding a zero-sized `\hbox` as the very last item into the `\ShipoutBox` and raising it up so that it still has its (0,0) point in the top-left corner. But being placed after the main box content it will be typeset later and thus overprints it (i.e., is in the foreground).

shipout This hook is executed after foreground and/or background material has been added, i.e., just in front of the actual shipout operation. Its purpose is to allow manipulation of the finalized box (stored in `\ShipoutBox`) with the extra material also in place (which is not yet the case in `shipout/before`).

It cannot be used to cancel the shipout operation via `\DiscardShipoutBox` (that has to happen in `shipout/before`, if desired!)

²Might need changing, but HO's version as strings is not really helpful I think).

shipout/firstpage The material from this hook is executed only once at the very beginning of the first output page that is shipped out (i.e., not discarded at the last minute). It should only contain `\special` or similar commands needed to direct post processors handling the `.dvi` or `.pdf` output.³

This hook is added to the very first page regardless of how it is shipped out (i.e., with `\shipout` or `\RawShipout`).

shipout/lastpage The corresponding hook to add `\specials` at the very end of the output file. It is only executed on the very last page of the output file — or rather on the page that L^AT_EX believes is the last one. Again it is executed regardless of the shipout method.

It may not be possible for L^AT_EX to correctly determine which page is the last one without several reruns. If this happens and the hook is non-empty then L^AT_EX will add an extra page to place the material and also request a rerun to get the correct placement sorted out.

shipout/after This hook is executed after a shipout has happened. If the shipout box is discarded this hook is not looked at.

You can use `\RawShipout` inside this hook for special use cases and the main `\ShipoutBox` is still available at this point (but in contrast to `shipout/before` it now includes the background and foreground material).

Note: Just like `shipout/before` this hook is not meant to be used for adding typeset material back to the main vertical list—it might vanish or the vertical spacing will be wrong!

As mentioned above the hook `shipout/before` is executed first and can manipulate the prepared shipout box stored in `\ShipoutBox` or set things up for use in `\write` during the actual shipout. It is even run if there was a `\DiscardShipoutBox` request in the document.

The other hooks (except `shipout` and `shipout/after`) are added inside hboxes to the box being shipped out in the following order:

<code>shipout/firstpage</code>	only on the first page
<code>shipout/background</code>	
<code>(boxed content of \ShipoutBox)</code>	
<code>shipout/foreground</code>	
<code>shipout/lastpage</code>	only on the last page

If any of the hooks has no code then the corresponding box is added at that point.

Once the (page) box has got the above extra content it can again be manipulated using the `shipout` hook and then is shipped out for real.

Once the (page) box has been shipped out the `shipout/after` hook is called (while you are still inside the output routine). It is not called if the shipout box was discarded.

In a document that doesn't produce pages, e.g., only makes `\typeouts`, none of the hooks are ever executed (as there is no `\shipout`) not even the `shipout/lastpage` hook.

If `\RawShipout` is used instead of `\shipout` then only the hooks `shipout/firstpage` and `shipout/lastpage` are executed (on the first or last page), all others are bypassed.

³In L^AT_EX 2_ε that was already existing, but implemented using a box register with the name `\@begindvibox`.

1.3 Legacy L^AT_EX commands

```
\AtBeginDvi \AtBeginDvi {<code>}
\AtEndDvi
```

\AtBeginDvi is the existing L^AT_EX 2_C interface to fill the `shipout/firstpage` hook. This is not really a good name as it is not just supporting `.dvi` but also `.pdf` output or `.xdv`.

\AtEndDvi is the counterpart that was not available in the kernel but only through the package `atenddvi`. It fills the `shipout/lastpage` hook.

Neither interface can set a code label but uses the current default label.

As these two wrappers have been available for a long time we continue offering them (but not enhancing them, e.g., by providing support for code labels).

For new code we strongly suggest using the high-level hook management commands directly instead of “randomly-named” wrappers. This will lead to code that is easier to understand and to maintain and it also allows you to set code labels if needed.

For this reason we do not provide any other “new” wrapper commands for the above hooks in the kernel, but only keep the existing ones for backward compatibility.

1.4 Special commands for use inside the hooks

```
\DiscardShipoutBox \AddToHookNext {shipout/before} {...\DiscardShipoutBox...}
\shipout_discard:
```

The \DiscardShipoutBox declaration (L3 name `\shipout_discard:`) requests that on the next shipout the page box is thrown away instead of being shipped to the `.dvi` or `.pdf` file.

Typical applications wouldn’t do this unconditionally, but have some processing logic that decides to use or not to use the page.

Note that if this declaration is used directly in the document it may depend on the placement to which page it applies, given that L^AT_EX output routine is called in an asynchronous manner! Thus normally one would use this only as part of the `shipout/before` code.

Todo: Once we have a new mark mechanism available we can improve on that and make sure that the declaration applies to the page that contains it — not done (yet)

\DiscardShipoutBox cannot be used in any of the `shipout/...` hooks other than `shipout/before`.

In the `atbegshi` package there are a number of additional commands for use inside the `shipout/before` hook. They should normally not be needed any more as one can instead simply add code to the hooks `shipout/before`, `shipout`, `shipout/background` or `shipout/foreground`.⁴ If `atbegshi` gets loaded then those commands become available as public functions with their original names as given below.

⁴If that assumption turns out to be wrong it would be trivial to change them to public functions (right now they are private).

1.5 Provided LuaTeX callbacks

pre_shipout_filter Under LuaTeX the `pre_shipout_filter` Lua callback is provided which gets called directly after the `shipout` hook, immediately before the shipout primitive gets invoked. The signature is

```
function(<node> head)
    return true
end
```

The `head` is the list node corresponding to the box to be shipped out. The return value should always be `true`.

1.6 Information counters

`\ ReadonlyShipoutCounter \ifnum\ ReadonlyShipoutCounter=...`
`\g_shipout_READONLY_int \int_use:N \g_shipout_READONLY_int % expl3 usage`

This integer holds the number of pages shipped out up to now (including the one to be shipped out when inside the output routine). More precisely, it is incremented only after it is clear that a page will be shipped out, i.e., after the `shipout/before` hook (because that might discard the page)! In contrast `shipout/after` sees the incremented value.

Just like with the `page` counter its value is only accurate within the output routine. In the body of the document it may be off by one as the output routine is called asynchronously!

Also important: it *must not* be set, only read. There are no provisions to prevent that restriction, but if you manipulate it, chaos will be the result. To emphasize this fact it is not provided as a `LATEX` counter but as a `TEX` counter (i.e., a command), so `\Alph{\ReadonlyShipoutCounter}` etc, would not work.

`totalpages`
`\g_shipout_totalpages_int \arabic{totalpages}`
`\int_use:N \g_shipout_totalpage_int % expl3 usage`

In contrast to `\ReadonlyShipoutCounter`, the `totalpages` counter is a `LATEX` counter and incremented for each shipout attempt including those pages that are discarded for one or the other reason. Again `shipout/before` sees the counter before it is incremented. In contrast `shipout/after` sees the incremented value.

Furthermore, while it is incremented for each page, its value is never used by `LATEX`. It can therefore be freely reset or changed by user code, for example, to additionally count a number of pages that are not build by `LATEX` but are added in a later part of the process, e.g., cover pages or picture pages made externally.

Important: as this is a page-related counter its value is only reliable inside the output routine!

`\PreviousTotalPages \PreviousTotalPages`

Command that expands to the number of total pages from the previous run. If there was no previous run or if used in the preamble it expands to 0. Note that this is a command and not a counter, so in order to display the number in, say, Roman numerals you have to assign its value to a counter and then use `\Roman` on that counter.

1.7 Debugging shipout code

```
\DebugShipoutsOn          \DebugShipoutsOn
\DebugShipoutsOff         \DebugShipoutsOff
\shipout_debug_on:        \shipout_debug_on:
\shipout_debug_off:       \shipout_debug_off:
```

Turn the debugging of shipout code on or off. This displays changes made to the shipout data structures.

Todo: This needs some rationalizing and may not stay this way.

2 Emulating commands from other packages

The packages in this section are no longer necessary, but as they are used by other packages, they are emulated when they are explicitly loaded with `\usepackage` or `\RequirePackage`.

Please note that the emulation only happens if the package is explicitly requested, i.e., the commands documented below are not automatically available in the L^AT_EX kernel! If you write a new package we suggest to use the appropriate kernel hooks directly instead of loading the emulation.

2.1 Emulating `atbegshi`

```
\AtBeginShipoutUpperLeft      \AddToHook {shipout/before} {...\AtBeginShipoutUpperLeft{\langle code\rangle}...}
\AtBeginShipoutUpperLeftForeground
```

This adds a `picture` environment into the background of the shipout box expecting `\langle code\rangle` to contain `picture` commands. The same effect can be obtained by simply using kernel features as follows:

```
\AddToHook{shipout/background}{\langle code\rangle}
```

There is one technical difference: if `\AtBeginShipoutUpperLeft` is used several times each invocation is put into its own box inside the shipout box whereas all `\langle code\rangle` going into `shipout/background` ends up all in the same box in the order it is added or sorted based on the rules for the hook chunks.

`\AtBeginShipoutUpperLeftForeground` is similar with the difference that the `picture` environment is placed in the foreground. To model it with the kernel functions use the hook `shipout/foreground` instead.

```
\AtBeginShipoutAddToBox      \AddToHook {shipout/before} {...\AtBeginShipoutAddToBox{\langle code\rangle}...}
\AtBeginShipoutAddToBoxForeground
```

These work like `\AtBeginShipoutUpperLeft` and `\AtBeginShipoutUpperLeftForeground` with the difference that `\langle code\rangle` is directly placed into an `\hbox` inside the shipout box and not surrounded by a `picture` environment.

To emulate them using `shipout/background` or `shipout/foreground` you may have to wrap `\langle code\rangle` into a `\put` statement but if the code is not doing any typesetting just adding it to the hook should be sufficient.

`\AtBeginShipoutBox` This is the name of the shipout box as `atbegshi` knows it.

\AtBeginShipoutOriginalShipout

This is the name of the `\shipout` primitive as `atbegshi` knows it. This bypasses all the mechanisms set up by the L^AT_EX kernel and there are various scenarios in which it can therefore fail. It should only be used to run existing legacy `atbegshi` code but not in newly developed applications.

The kernel alternative is `\RawShipout` which is integrated with the L^AT_EX mechanisms and updates, for example, the `_READONLYSHIPOUTCOUNTER` counter. Please use `\RawShipout` for new code if you want to bypass the before, foreground and background hooks.

\AtBeginShipoutInit	By default <code>atbegshi</code> delayed its action until <code>\begin{document}</code> . This command was forcing it in an earlier place. With the new concept it does nothing.
----------------------------	--

\AtBeginShipout	<code>\AtBeginShipout{\langle code \rangle} \equiv \AddToHook{shipout/before}{\langle code \rangle}</code>
\AtBeginShipoutNext	<code>\AtBeginShipoutNext{\langle code \rangle} \equiv \AddToHookNext{shipout/before}{\langle code \rangle}</code>

This is equivalent to filling the `shipout/before` hook by either using `\AddToHook` or `\AddToHookNext`, respectively.

\AtBeginShipoutFirst	The <code>atbegshi</code> names for <code>\AtBeginDvi</code> and <code>\DiscardShipoutBox</code> .
\AtBeginShipoutDiscard	

2.2 Emulating `everyshi`

The `everyshi` package is providing commands to run arbitrary code just before the shipout starts. One point of difference: in the new shipout hooks the page is available as `\ShipoutBox` for inspection of change, one should not manipulate box 255 directly inside `shipout/before`, so old code doing this would change to use `\ShipoutBox` instead of 255 or `\@ccnv`.

\EveryShipout	<code>\EveryShipout{\langle code \rangle} \equiv \AddToHook{shipout/before}{\langle code \rangle}</code>
\AtNextShipout	<code>\AtNextShipout{\langle code \rangle} \equiv \AddToHookNext{shipout/before}{\langle code \rangle}</code>

However, most use cases for `everyshi` are attempts to put some picture or text into the background or foreground of the page and that can be done today simply by using the `shipout/background` and `shipout/foreground` hooks without any need to coding.

2.3 Emulating `atenddvi`

The `atenddvi` package implemented only a single command: `\AtEndDvi` and that is now available out of the box so the emulation makes the package a no-op.

2.4 Emulating `everypage`

This package patched the original `\@begindvi` hook and replaced it with its own version. Its functionality is now covered by the hooks offered by the kernel so that there is no need for such patching any longer.

```
\AddEverypageHook \AddEverypageHook{\code} ≡  
    \AddToHook{shipout/background}{\put(1in,-1in){\code}}
```

`\AddEverypageHook` is adding something into the background of every page at a position of 1in to the right and 1in down from the top left corner of the page. By using the kernel hook directly you can put your material directly to the right place, i.e., use other coordinates in the `\put` statement above.

```
\AddThispageHook \AddThispageHook{\code} ≡  
    \AddToHookNext{shipout/background}{\put(1in,-1in){\code}}
```

The `\AddThispageHook` wrapper is similar but uses `\AddToHookNext`.

3 The Implementation

```
1 <@@=shipout>
```

At the moment the whole module rolls back in one go, but if we make any modifications in later releases this will then need splitting.

```
2 <*2ekernel | latexrelease>  
3 <latexrelease> \IncludeInRelease{2020/10/01}%  
4 <latexrelease>           {\shipout}{Hook management (shipout)}%  
5 \ExplSyntaxOn
```

3.1 Debugging

`\g__shipout_debug_bool` Holds the current debugging state.

```
6 \bool_new:N \g__shipout_debug_bool
```

(End of definition for `\g__shipout_debug_bool`.)

```
\shipout_debug_on: Turns debugging on and off by redefining \__shipout_debug:n.  
\shipout_debug_off:  
  \__shipout_debug:n  
\__shipout_debug_gset:  
  \__shipout_debug_gset:  
  \cs_new_eq:NN \__shipout_debug:n \use_none:n  
  \cs_new_protected:Npn \shipout_debug_on:  
  {  
    \bool_gset_true:N \g__shipout_debug_bool  
    \__shipout_debug_gset:  
  }  
  \cs_new_protected:Npn \shipout_debug_off:  
  {  
    \bool_gset_false:N \g__shipout_debug_bool  
    \__shipout_debug_gset:  
  }  
  \cs_new_protected:Npn \__shipout_debug_gset:  
  {  
    \cs_gset_protected:Npx \__shipout_debug:n ##1  
    { \bool_if:NT \g__shipout_debug_bool {##1} }  
  }
```

(End of definition for `\shipout_debug_on`: and others. These functions are documented on page 7.)

\ShipoutBox The box filled with the page to be shipped out (both L³ and L^AT_EX 2_& name).

```
23 \box_new:N \l_shipout_box
24 \cs_set_eq:NN \ShipoutBox \l_shipout_box
```

(End of definition for `\ShipoutBox` and `\l_shipout_box`. These functions are documented on page 2.)

\l__shipout_raw_box The `\RawShipout` gets its own box but it is internal as there is no hook manipulation for it.

```
25 \box_new:N \l__shipout_raw_box
```

(End of definition for `\l__shipout_raw_box`.)

__shipout_finalize_box: For LuaT_EX invoke the `pre_shipout_filter` callback.

```
26 \sys_if_engine_luatex:TF
27 {
28     \newprotectedluacmd \__shipout_finalize_box:
29     \exp_args:Nx \everyjob {
30         \exp_not:V \everyjob
31         \exp_not:N \lua_now:n {
32             luatexbase.create_callback('pre_shipout_filter', 'list')
33             local~call, getbox, setbox = luatexbase.call_callback, tex.getbox, tex.setbox~
34             lua.get_functions_table()[\the\allocationnumber] = function()
35                 local~head = getbox(\the\l_shipout_box)
36                 local~result = call('pre_shipout_filter', head)
37                 if~not (result == head) then~
38                     setbox(\the\l_shipout_box, result~or~nil)
39                 end~
40             end
41         }
42     }
43 }
44 \cs_set_eq:NN \__shipout_finalize_box: \scan_stop:
45 }
```

(End of definition for `__shipout_finalize_box`.)

__shipout_execute: This is going to be the code run by `\shipout`. The code follows closely the ideas from atbegshi, so not documenting that here for now.

```
46 \cs_set_protected:Npn \__shipout_execute: {
47     \tl_set:Nx \l__shipout_group_level_tl
48     { \int_value:w \tex_currentgrouplevel:D }
49     \tex_afterassignment:D \__shipout_execute_test_level:
50     \tex_setbox:D \l_shipout_box
51 }
```

(End of definition for `__shipout_execute`.)

\shipout Overloading the `\shipout` primitive:

```
52 \cs_gset_eq:NN \shipout \__shipout_execute:
```

(End of definition for `\shipout`. This function is documented on page 2.)

\l__shipout_group_level_tl Helper token list to record the group level at which __shipout_execute: is encountered.

```

53  \tl_new:N \l__shipout_group_level_tl

```

(End of definition for \l__shipout_group_level_tl.)

__shipout_execute_test_level: If the group level has changed then we are still constructing \l_shipout_box and to continue we need to wait until the current group has finished, hence the \tex_aftergroup:D.

```

54  \cs_new:Npn \_\_shipout_execute_test_level: {
55    \int_compare:nNnT
56      \l__shipout_group_level_tl < \tex_currentgrouplevel:D
57      \tex_aftergroup:D \_\_shipout_execute_cont:
58  }

```

(End of definition for __shipout_execute_test_level:.)

__shipout_execute_cont: This does the actual shipout running several hooks as part of it. The code for them is passed as argument #2 to #4 to __shipout_execute_main_cont:Nnnn; the first argument is the box to be shipped out.

```

59  \cs_new:Npn \_\_shipout_execute_cont: {
60    \_\_shipout_execute_main_cont:Nnnn
61    \l\_shipout_box
62    { \hook_use:n {shipout/before} }
63    { \hook_if_empty:nF {shipout/foreground}
64      { \_\_shipout_add_foreground_picture:n
65        { \hook_use:n {shipout/foreground} } }

```

If the user hook for the background (shipout/background) has no code, there might still code in the kernel hook so we need to test for this too. We only test for the @kernel@before@shipout@background though. If the @kernel@after@shipout@background needs executing even if the user hook is empty then we can add another test (or the kernel could put something into the before hook).

```

66    \bool_lazy_and:nnF
67      { \hook_if_empty_p:n {shipout/background} }
68      { \tl_if_empty_p:N @kernel@before@shipout@background }
69      { \_\_shipout_add_background_picture:n
70        { @kernel@before@shipout@background
71          \hook_use:n {shipout/background}
72          @kernel@after@shipout@background }
73      }
74    }
75    { \hook_use:n {shipout/after} }
76  }

```

(End of definition for __shipout_execute_cont:.)

__shipout_execute_main_cont:Nnnn When we have reached this point the shipout box has been processed and is available in \l_shipout_box and ready for real ship out (unless it gets discarded during the process).

The three arguments hold hook code that is executed just before the actual shipout (#1), within the shipout adding background and foreground material (#2) and after the shipout has happened (#3). These are passed as arguments because the same code without those hooks is also used when doing a “raw” shipout implemented by \RawShipout. The only hook that is always executed is that for the very last page, i.e., shipout/lastpage.

First we quickly check if it is void (can't happen in the standard L^AT_EX output routine but `\shipout` might be called from a package that has some special processing logic). If it is void we aren't shipping anything out and processing ends.⁵

```
77 \cs_new:Npn \__shipout_execute_main_cont:Nnnn #1#2#3#4 {
78   \box_if_empty:NTF #1
79     { \@latex@warning@no@line{ Ignoring~ void~ shipout~ box } }
80 }
```

Otherwise we assume that we will ship something and prepare for final adjustments (in particular setting the state of `\protect` while we are running the hook code). We also save the current `\protect` state to restore it later.

```
81 %      \bool_gset_false:N \g__shipout_discard_bool % setting this would disable
82 %                                         % \DiscardShipoutBox on doc-level
83 \cs_set_eq:NN \__shipout_saved_protect: \protect
84 \set@typeset@protect
```

We also store the current shipout box dimension in registers, so that they can be used in the hook code.⁶

```
85 \__shipout_get_box_size:N #1
```

Then we execute the `shipout/before` hook (or nothing in case of `\RawShipout`).

```
86 #2
```

In `\g_shipout_totalpages_int` we count all shipout attempts so we increment that counter already here (the other one is incremented later when we know for sure that we do a `\shipout`).

We increment it after running the above hook so that the values for `\g_shipout_totalpages_int` and `\g_shipout_READONLY_int` are in sync while the hook is executed (in the case that totalpages isn't manually altered or through discarding pages that is).

```
87 \int_gincr:N \g_shipout_totalpages_int
```

The above hook might contain code that requests the page to be discarded so we now test for it.

```
88 \bool_if:NTF \g__shipout_discard_bool
89   { \@latex@info@no@line{Completed~ page~ discarded}}
90   \bool_gset_false:N \g__shipout_discard_bool
```

As we are discarding the page box and not shipping anything out, we need to do some house cleaning and reset T_EX's deadcycles so that it doesn't complain about too many calls to the OR without any shipout.

```
91 \tex_deadcycles:D \c_zero_int
```

Todo: In atbegshi the box was dropped but is that actually needed? Or the resetting of `\protect` to its kernel value?

```
92 %
93 %      \group_begin:
94 %        \box_set_eq_drop:NN #1 #1
95 %      \group_end:
96 %      \cs_set_eq:NN \protect \exp_not:N
97 }
```

⁵In that case we don't reset the deadcycles, that would be up to the OR processing logic to do.

⁶This is not really necessary as the code could access them via `\box_ht:N`, etc., but it is perhaps convenient.

Even if there was no explicit request to discard the box it is possible that the code for the hook `shipout/before` has voided the box (by mistake or deliberately). We therefore test once more but this time make it a warning, because the best practice way is to use the request mechanism.

```

97   { \box_if_empty:NTF #1
98     { \@latex@warning@no@line { Ignoring~ void~ shipout~ box.
99       \MessageBreak The~ shipout~ box~ was~ voided~ by~ hook~ code }
100    }

```

Finally, if the box is still non-empty we are nearly ready to ship it out. First we increment the total page counter so that we can later test if we have reached the final page according to our available information.⁷

```

101   {
102     \int_gincr:N \g_shipout_READONLY_int
103     \__shipout_debug:n {
104       \typeout{Absolute~ page~ == \int_use:N \g_shipout_READONLY_int
105         \space (target:~ \@abspage@last)}
106     }

```

Then we store the box sizes again (as they may have changed) and then look at the hooks `shipout/foreground` and `shipout/background`. If either or both are non-empty we add a `picture` environment to the box (in the foreground and/or in the background) and execute the hook code inside that environment.

```
107   \__shipout_get_box_size:N #1
```

The first hook we run is the `shipout/firstpage` hook. This is only done once, then the `__shipout_run_firstpage_hook:` command redefines itself to do nothing. If the hook contains `\specials` for integration at the top of the page they will be temporarily stored in a safe place and added later with `__shipout_add_firstpage_specials:`.

```
108   \__shipout_run_firstpage_hook:
```

Run the hooks for background and foreground or, if this is called by `\RawShipout`, copy the box `\l__shipout_raw_box` to `\l_shipout_box` so that `firstpage` and `lastpage` material gets added if necessary (that is always done to `\l_shipout_box`).

```
109   #3
```

We then run `__shipout_add_firstpage_specials:` that adds the content of the hook `shipout/firstpage` to the start of the first page (if non-empty). It is then redefined to do nothing on later pages.

```
110   \__shipout_add_firstpage_specials:
```

Then we check if we have to add the `shipout/lastpage` hook or the corresponding kernel hook because we have reached the last page. This test will be false for all but one (and hopefully the correct) page.

```

111   \int_compare:nNnT \@abspage@last = \g_shipout_READONLY_int
112     { \bool_lazy_and:nnF
113       { \hook_if_empty_p:n {shipout/lastpage} }
114       { \tl_if_empty_p:N \@kernel@after@shipout@lastpage }
115     } { \__shipout_debug:n { \typeout{Executing~ lastpage~ hook~
116       on~ page~ \int_use:N \g_shipout_READONLY_int } }
117       \__shipout_add_foreground_box:n
118       { \UseHook{shipout/lastpage}
119         \@kernel@after@shipout@lastpage }

```

⁷Doing that earlier would be wrong because we might end up with the last page counted but discarded and then we have no place to add the final objects into the output file.

We record that we have handled the `shipout/lastpage` hook but only if we really did.

```

120           \bool_gset_true:N \g__shipout_lastpage_handled_bool
121       }
122   }
123   \hook_use:n {shipout}
124   \__shipout_finalize_box:
```

Finally we run the actual TeX primitive for shipout. As that will expand delayed `\write` statements inside the page in which protected commands should not expand we first change `\protect` to the appropriate definition for that case.

```

125   \cs_set_eq:NN \protect \exp_not:N
126   \tex_shipout:D \box_use:N \l_shipout_box
```

The `\l_shipout_box` may contain the firstpage material if this was the very first shipout. That makes it unsuitable for reuse in another shipout, so as a safety measure the next command resets `\l_shipout_box` to its earlier state if that is necessary. On later pages this is then a no-op.

```
127   \__shipout_drop_firstpage_specials:
```

The `shipout/after` hook (if in #4) needs to run with `\protected` commands again being executed, because that hook will “typeset” material added at the top of the next page.

```

128   \set@typeset@protect
129   #4
130   }
131 }
```

Restore the value of `\protect` in case `\shipout` is called outside of the output routine (where it is automatically restored because of the implicit group).

```

132   \cs_set_eq:NN \protect \__shipout_saved_protect:
133   }
134 }
```

(End of definition for `__shipout_execute_main_cont:Nnnn`.)

`__shipout_execute_raw:` This implements the “raw” shipout which bypasses the before, foreground, background and after hooks. It follows the same pattern than `__shipout_execute_raw:` except that it finally calls `__shipout_execute_main_cont:Nnnn` with three empty arguments instead of the hook code.

```

135 \cs_set_protected:Npn \__shipout_execute_raw: {
136   \tl_set:Nx \l__shipout_group_level_tl
137   { \int_value:w \tex_currentgrouplevel:D }
138   \tex_afterassignment:D \__shipout_execute_test_level_raw:
139   \tex_setbox:D \l__shipout_raw_box
140 }
141 \cs_new:Npn \__shipout_execute_test_level_raw: {
142   \int_compare:nNnT
143     \l__shipout_group_level_tl < \tex_currentgrouplevel:D
144     \tex_aftergroup:D \__shipout_execute_nohooks_cont:
145 }
```

Well, not totally empty arguments, we add some debugging if we are actually doing a shipout.

```

146 \cs_new:Npn \__shipout_execute_nohooks_cont: {
147   \__shipout_execute_main_cont:Nnnn \l__shipout_raw_box
148   {} { \__shipout_debug:n{ \typeout{Doing~ raw~ shipout~ ...} }
149     \box_set_eq:NN \l_shipout_box \l__shipout_raw_box } {}
150 }

(End of definition for \__shipout_execute_raw: and \__shipout_execute_test_level_raw:.)
```

\RawShipout The interface name for raw shipout.

```
151 \cs_gset_eq:NN \RawShipout \__shipout_execute_raw:
```

(End of definition for \RawShipout. This function is documented on page 2.)

__shipout_saved_protect: Remember the current \protect state.

```
152 \cs_new_eq:NN \__shipout_saved_protect: \protect
```

(End of definition for __shipout_saved_protect:.)

shipout/before Declaring all hooks for the shipout code.

```

153 \hook_new:n{shipout/before}
154 \hook_new:n{shipout}
155 \hook_new:n{shipout/after}
156 \hook_new:n{shipout/foreground}
157 \hook_new:n{shipout/background}
158 \hook_new:n{shipout/firstpage}
159 \hook_new:n{shipout/lastpage}
```

(End of definition for shipout/before and others. These functions are documented on page 3.)

And here are the internal kernel hooks going before or after the public ones where needed.

```

160 \let\@kernel@after@shipout@lastpage\@empty
161 \let\@kernel@before@shipout@background\@empty
162 \let\@kernel@after@shipout@background\@empty
```

(End of definition for \@kernel@after@shipout@lastpage, \@kernel@before@shipout@background, and \@kernel@after@shipout@background. These functions are documented on page ??.)

__shipout_run_firstpage_hook:

There are three commands to handle the **shipout/firstpage** hook: **__shipout_run_firstpage_hook:**, **__shipout_add_firstpage_specials:** and **__shipout_drop_firstpage_specials:**.

That hook is supposed to contain \specials and similar material to be placed at the very beginning of the output page and so it needs careful placing to avoid that anything else gets in front of it. And this means we have to wait with this until other hooks such as **shipout/background** have added their bits. It is also important that such \specials show up only on the very first page, so if this page gets saved before \shipout for later reuse, we have to make sure that they aren't in the saved version.

In addition the hook may also contain code to be executed "first", e.g., visible from code in **shipout/background** and this conflicts with adding the \specials late.

Therefore the processing is split into different parts: **__shipout_run_firstpage_hook:** is done early and checks if there is any material in the hook.

```

163 \cs_new:Npn \__shipout_run_firstpage_hook: {
164   \hook_if_empty:nTF {shipout/firstpage}
```

If not then we define the other two commands to do nothing.

```

165      {
166          \cs_gset_eq:NN \__shipout_add_firstpage_specials: \prg_do_nothing:
167          \cs_gset_eq:NN \__shipout_drop_firstpage_specials: \prg_do_nothing:
168      }

```

If there is material we execute inside a box, which means any `\special` will end up in that box and any other code is executed and can have side effects (as long as they are global).

```

169      {
170          \hbox_set:Nn \l__shipout_firstpage_box { \UseHook{shipout/firstpage} }
171      }

```

Once we are here we change the definition to do nothing next time and we also change the command used to implement `\AtBeginDvi` to become a warning and not add further material to a hook that is never used again.

```

172  \cs_gset_eq:NN \__shipout_run_firstpage_hook: \prg_do_nothing:
173  \cs_gset:Npn \__shipout_add_firstpage_material:Nn ##1 ##2 {
174      @latex@warning{ First~ page~ is~ already~ shipped~ out,~ ignoring
175          \MessageBreak \string##1 }
176  }
177 }

```

(End of definition for `__shipout_run_firstpage_hook:`)

`__shipout_add_firstpage_specials:` The `__shipout_add_firstpage_specials:` then adds the `\specials` stored in `\l__shipout_firstpage_box` to the page to be shipped out when the time is ready. Note that if there was no material in the `shipout/firstpage` hook then this command gets redefined to do nothing. But for most documents there is something, e.g., some PostScript header, or some meta data declaration, etc. so by default we assume there is something to do.

`\cs_new:Npn __shipout_add_firstpage_specials: {`

First we make a copy of the `\l_shipout_box` that we can restore it later on.

```
179  \box_set_eq:NN \l__shipout_raw_box \l_shipout_box
```

Adding something to the beginning means adding it to the background as that layer is done first in the output.

```
180  \__shipout_add_background_box:n { \hbox_unpack_drop:N \l__shipout_firstpage_box }
```

After the actual shipout `__shipout_drop_firstpage_specials:` is run to restore the earlier content of `\l_shipout_box` and then redefines itself again to do nothing.

As a final act we change the definition to do nothing next time.

```

181  \cs_gset_eq:NN \__shipout_add_firstpage_specials: \prg_do_nothing:
182 }

```

The `__shipout_drop_firstpage_specials:` is run after the shipout has occurred but before the `shipout/afterpage` hook is executed. That is the point where we have to restore the `\ShipoutBox` to its state without the `shipout/firstpage` material.

```

183  \cs_new:Npn \__shipout_drop_firstpage_specials: {
184      \box_set_eq:NN \l_shipout_box \l__shipout_raw_box

```

If there was no such material then `__shipout_run_firstpage_hook:` will have changed the definition to a no-op already. Otherwise this is what we do here.

```

185  \cs_gset_eq:NN \__shipout_drop_firstpage_specials: \prg_do_nothing:
186 }

```

(End of definition for `__shipout_add_firstpage_specials`: and `__shipout_drop_firstpage_specials`.)

`\l__shipout_firstpage_box` The box to hold any firstpage `\specials`.

187 `\box_new:N \l__shipout_firstpage_box`

(End of definition for `\l__shipout_firstpage_box`.)

`\g__shipout_lastpage_handled_bool` A boolean to signal if we have already handled the `shipout/lastpage` hook.

188 `\bool_new:N \g__shipout_lastpage_handled_bool`

(End of definition for `\g__shipout_lastpage_handled_bool`.)

`__shipout_add_firstpage_material:Nn` This command adds material to the `shipout/firstpage` hook. It is used in `\AtBeginDvi`, etc. The first argument is the command through which it is called. Initially this is ignored but once we are passed the first page it can be used to generate a warning message mentioning the right user command.

189 `\cs_new:Npn __shipout_add_firstpage_material:Nn #1#2 {`
190 `\AddToHook{shipout/firstpage}{#2}`
191 `}`

(End of definition for `__shipout_add_firstpage_material:Nn`.)

`__shipout_get_box_size:N` Store the box dimensions in dimen registers.

Todo: This could/should perhaps be generalized to set height depth and width given an arbitrary box.

192 `\cs_new:Npn __shipout_get_box_size:N #1 {`
193 `\dim_set:Nn \l_shipout_box_ht_dim { \box_ht:N #1 }`
194 `\dim_set:Nn \l_shipout_box_dp_dim { \box_dp:N #1 }`
195 `\dim_set:Nn \l_shipout_box_wd_dim { \box_wd:N #1 }`
196 `\dim_set:Nn \l_shipout_box_ht_plus_dp_dim`
197 `{ \l_shipout_box_ht_dim + \l_shipout_box_dp_dim }`
198 `}`

(End of definition for `__shipout_get_box_size:N`.)

`\l_shipout_box_ht_dim` And here are the variables set by `__shipout_get_box_size:N`.

`\l_shipout_box_dp_dim`
`\l_shipout_box_wd_dim`
`\l_shipout_box_ht_plus_dp_dim`

199 `\dim_new:N \l_shipout_box_ht_dim`
200 `\dim_new:N \l_shipout_box_dp_dim`
201 `\dim_new:N \l_shipout_box_wd_dim`
202 `\dim_new:N \l_shipout_box_ht_plus_dp_dim`

(End of definition for `\l_shipout_box_ht_dim` and others. These functions are documented on page 3.)

`\g__shipout_discard_bool` Indicate whether or not the current page box should be discarded

203 `\bool_new:N \g__shipout_discard_bool`

(End of definition for `\g__shipout_discard_bool`.)

`\l__shipout_tmp_box` We need a box for the background and foreground material and a token register to remember badness settings as we disable them during the buildup below.

204 `\box_new:N \l__shipout_tmp_box`
205 `\tl_new:N \l__shipout_saved_badness_tl`

(End of definition for `\l__shipout_tmp_box` and `\l__shipout_saved_badness_tl`.)

_shipout_add_background_box:n In standard L^AT_EX the shipout box is always a \vbox but here we are allow for other usage as well, in case some package has its own output routine.

```
206 \cs_new:Npn \_shipout_add_background_box:n #1
207 { \_shipout_get_box_size:N \l_shipout_box
```

But we start testing for a vertical box as that should be the normal case.

```
208 \box_if_vertical:NTF \l_shipout_box
209 {
```

Save current values of \vfuzz and \vbadness then change them to allow box manipulations without warnings.

```
210 \tl_set:Nx \l__shipout_saved_badness_t1
211 { \vfuzz=\the\vfuzz\relax
212 \vbadness=\the\vbadness\relax }
213 \vfuzz=\c_max_dim
214 \vbadness=\c_max_int
```

Then we reconstruct \l_shipout_box ...

```
215 \vbox_set_to_ht:Nnn \l_shipout_box \l_shipout_box_ht_plus_dp_dim
216 {
```

... the material in #1 is placed into a horizontal box with zero dimensions.

```
217 \hbox_set:Nn \l__shipout_tmp_box
218 { \l__shipout_saved_badness_t1 #1 }
219 \box_set_wd:Nn \l__shipout_tmp_box \c_zero_dim
220 \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim
221 \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim
```

The we typeset that box followed by whatever was in \l_shipout_box before (unpacked).

```
222 \skip_zero:N \baselineskip
223 \skip_zero:N \lineskip
224 \skip_zero:N \lineskiplimit
225 \box_use:N \l__shipout_tmp_box
226 \vbox_unpack:N \l_shipout_box
```

The \kern ensures that the box has no depth which is afterwards explicitly corrected.

```
227 \kern \c_zero_dim
228 }
229 \box_set_ht:Nn \l_shipout_box \l_shipout_box_ht_dim
230 \box_set_dp:Nn \l_shipout_box \l_shipout_box_dp_dim
```

Todo: The whole boxing maneuver looks a bit like overkill to me, but for the moment I leave.

```
231 \l__shipout_saved_badness_t1
232 }
233 {
```

A horizontal box is handled in a similar way. The last case would be a void box in which case we do nothing hence the missing F branch.

```
234 \box_if_horizontal:NT \l_shipout_box
235 {
236 \tl_set:Nx \l__shipout_saved_badness_t1
237 { \hfuzz=\the\hfuzz\relax
238 \hbadness=\the\hbadness\relax }
239 \hfuzz=\c_max_dim
```

```

240     \hbadness=\c_max_int
241     \hbox_set_to_wd:Nnn \l_shipout_box \l_shipout_box_wd_dim
242     {
243         \hbox_set:Nn \l_shipout_tmp_box
244         { \l_shipout_saved_badness_tl #1 }
245         \box_set_wd:Nn \l_shipout_tmp_box \c_zero_dim
246         \box_set_ht:Nn \l_shipout_tmp_box \c_zero_dim
247         \box_set_dp:Nn \l_shipout_tmp_box \c_zero_dim
248         \box_move_up:nn
249             \l_shipout_box_ht_dim
250             { \box_use:N \l_shipout_tmp_box }
251             \hbox_unpack:N \l_shipout_box
252         }
253         \l_shipout_saved_badness_tl
254     }
255 }
256 }

(End of definition for \__shipout_add_background_box:n.)
```

__shipout_add_foreground_box:n Foreground boxes are done in the same way, only the order and placement of boxes has to be done differently.

```

257 \cs_new:Npn \__shipout_add_foreground_box:n #1
258 {
259     \box_if_vertical:NTF \l_shipout_box
260     {
261         \tl_set:Nx \l_shipout_saved_badness_tl
262         { \vfuzz=\the\vfuzz\relax
263             \vbadness=\the\vbadness\relax }
264         \vfuzz=\c_max_dim
265         \vbadness=\c_max_int
266         \vbox_set_to_ht:Nnn \l_shipout_box \l_shipout_box_ht_plus_dp_dim
267         {
268             \hbox_set:Nn \l_shipout_tmp_box
269             { \l_shipout_saved_badness_tl #1 }
270             \box_set_wd:Nn \l_shipout_tmp_box \c_zero_dim
271             \box_set_ht:Nn \l_shipout_tmp_box \c_zero_dim
272             \box_set_dp:Nn \l_shipout_tmp_box \c_zero_dim
273             \skip_zero:N \baselineskip
274             \skip_zero:N \lineskip
275             \skip_zero:N \lineskiplimit
276             \vbox_unpack:N \l_shipout_box
277             \kern -\l_shipout_box_ht_plus_dp_dim
278             \box_use:N \l_shipout_tmp_box
279             \kern \l_shipout_box_ht_plus_dp_dim
280         }
281         \l_shipout_saved_badness_tl
282         \box_set_ht:Nn \l_shipout_box \l_shipout_box_ht_dim
283         \box_set_dp:Nn \l_shipout_box \l_shipout_box_dp_dim
284     }
285     {
286         \box_if_horizontal:NT \l_shipout_box
287         {
288             \tl_set:Nx \l_shipout_saved_badness_tl
```

```

289 { \hfuzz=\the\hfuzz\relax
290   \hbadness=\the\hbadness\relax }
291 \hfuzz=\c_max_dim
292 \hbadness=\c_max_int
293 \hbox_set_to_wd:Nnn \l_shipout_box \l_shipout_box_wd_dim
294 {
295   \hbox_unpack:N \l_shipout_box
296   \kern -\box_wd:N \l_shipout_box
297   \hbox_set:Nn \l__shipout_tmp_box
298   { \l__shipout_saved_badness_t1 #1 }
299   \box_set_wd:Nn \l__shipout_tmp_box \c_zero_dim
300   \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim
301   \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim
302   \box_move_up:nn { \box_ht:N \l_shipout_box }
303   { \box_use:N \l__shipout_tmp_box }
304   \kern \box_wd:N \l_shipout_box
305 }%
306 \l__shipout_saved_badness_t1
307 }
308 }
309 }
```

(End of definition for `__shipout_add_foreground_box:n`.)

`__shipout_init_page_origins:`

`\c__shipout_horigin_tl`

`\c__shipout_vorigin_tl`

Two constants holding the offset of the top-left with respect to the media box.

Setting the constants this way is courtesy of Bruno.

We delay setting the constants to the last possible place as there might be updates in the preamble or even in the `begindocument` hook that affects their setup.

```

310 \cs_new:Npn \__shipout_init_page_origins: {
311   \tl_const:Nx \c__shipout_horigin_tl
312   {
313     \cs_if_exist_use:NTF \pdfvariable { horigin }
314     { \cs_if_exist_use:NF \pdfhorigin { 1in } }
315   }
316   \tl_const:Nx \c__shipout_vorigin_tl
317   {
318     \cs_if_exist_use:NTF \pdfvariable { vorigin }
319     { \cs_if_exist_use:NF \pdfvorigin { 1in } }
320   }
321 }
```

After the constants have been set there is no need to execute this command again, in fact it would raise an error, so we redefine it to do nothing.

```

321 \cs_gset_eq:NN \__shipout_init_page_origins: \prg_do_nothing:
322 }
```

(End of definition for `__shipout_init_page_origins:, \c__shipout_horigin_tl, and \c__shipout_vorigin_tl.`)

`__shipout_picture_overlay:n` Put the argument into a `picture` environment that doesn't take up any size and uses `1pt` for `\unitlength`.

Todo: Could perhaps be generalized as it might be useful elsewhere. For now it is not.

```

323 \cs_new:Npn \__shipout_picture_overlay:n #1 {
```

The very first time this is executed we have to initialize (and freeze) the origins.

```
324     \__shipout_init_page_origins:  
325         \kern -\c__shipout_horigin_tl \scan_stop:  
326         \vbox_to_zero:n {  
327             \kern -\c__shipout_vorigin_tl \scan_stop:  
328             \unitlength 1pt \scan_stop:
```

This mimics a simple zero-sized picture environment. The `\hss` is need in case there is horizontal material (without using `\put` with a positive width).

```
329     \hbox_set_to_wd:Nnn \l__shipout_tmp_box \c_zero_dim  
330         { \ignorespaces #1 \hss }  
331     \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim  
332     \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim  
333     \box_use:N \l__shipout_tmp_box  
334     \tex_vss:D  
335     }  
336 }
```

(End of definition for `__shipout_picture_overlay:n`.)

`__shipout_add_background_picture:n` Put a `picture` env in the background of the shipout box with its reference point in the top-left corner.

```
337 \cs_new:Npn \__shipout_add_background_picture:n #1 {  
338     \__shipout_add_background_box:n { \__shipout_picture_overlay:n {#1} }  
339 }
```

(End of definition for `__shipout_add_background_picture:n`.)

`__shipout_add_foreground_picture:n` Put a `picture` env in the foreground of the shipout box with its reference point in the top-left corner.

```
340 \cs_new:Npn \__shipout_add_foreground_picture:n #1 {  
341     \__shipout_add_foreground_box:n { \__shipout_picture_overlay:n {#1} }  
342 }
```

(End of definition for `__shipout_add_foreground_picture:n`.)

\shipout_discard: Request that the next shipout box should be discarded. At the moment this is just setting a boolean, but we may want to augment this behavior that the position of the call is taken into account (in case L^AT_EX looks ahead and is not using the position for on the next page).

```
343 \cs_new_protected:Npn \shipout_discard: {  
344     \bool_gset_true:N \g__shipout_discard_bool  
345 }
```

(End of definition for `\shipout_discard:`. This function is documented on page 5.)

3.2 Handling the end of job hook

At the moment this is partly solved by using the existing hooks. But rather than putting the code into these hooks it should be moved to the right place directly as we shouldn't prefill hooks with material unless it needs to interact with other code.

`\g_shipout_READONLY_int
\ ReadonlyShipoutCounter`

We count every shipout activity that makes a page (but not those that are discarded) in order to know how many pages got produced.

346 `\int_new:N \g_shipout_READONLY_int`

For $\text{\LaTeX} 2_{\varepsilon}$ it is available as a command (i.e., a \TeX counter only).

347 `\cs_new_eq:NN \ ReadonlyShipoutCounter \g_shipout_READONLY_int`

(End of definition for `\g_shipout_READONLY_int` and `\ ReadonlyShipoutCounter`. These functions are documented on page 6.)

`\g_shipout_totalpages_int
\c@totalpages`

We count every shipout attempt (even those that are discarded) in this counter. It is not used in the code but may get used in user code.

348 `\int_new:N \g_shipout_totalpages_int`

For $\text{\LaTeX} 2_{\varepsilon}$ this is offered as a \LaTeX counter so can be easily typeset inside the output routine to display things like “ $\backslash\thepage/\thetotalpages$ ”, etc.

349 `\cs_new_eq:NN \c@totalpages \g_shipout_totalpages_int`

350 `\cs_new:Npn \thetotalpages { \arabic{totalpages} }`

(End of definition for `\g_shipout_totalpages_int` and `\c@totalpages`. These functions are documented on page 6.)

`\@abspage@last`

In `\@abspage@last` record the number of pages from the last run. This is written to the `.aux` and this way made available to the next run. In case there is no `.aux` file or the statement is missing from it we initialize it with the largest possible number in \TeX . We use this as the default because then we are inserting the `shipout/lastpage` on the last page (or after the last page) but not on page 1 for a multipage document.

351 `\xdef\@abspage@last{\number\maxdimen}`

(End of definition for `\@abspage@last`. This function is documented on page ??.)

`\enddocument`

Instead of using the hooks `enddocument` and `enddocument/afterlastpage` we add this code to private kernel hooks to be 100% sure when it is executed and to avoid cluttering the hooks with data that is always there.

Inside `\enddocument` there is a `\clearpage`. Just before that we execute this code here. There is a good chance that we are on the last page. Therefore, if we don't know the value from the last run, we assume that the current page is the right one. So we set `\@abspage@last` and as a result the next shipout will run the `shipout/lastpage` code. Of course, if there are floats that still need a placement this guess will be wrong but then rerunning the document will give us the correct value next time around.

`\@kernel@after@enddocument`

352 `\g@addto@macro \@kernel@after@enddocument {`
353 `\int_compare:nNnT \@abspage@last = \maxdimen`
354 `{`

We use $\text{\LaTeX} 2_{\varepsilon}$ coding as `\@abspage@last` is not an L3 name.

355 `\xdef\@abspage@last{ \int_eval:n { \g_shipout_READONLY_int + 1 } }`
356 `}`
357 `}`

Once the `\clearpage` has done its work inside `\enddocument` we know for sure how many pages this document has, so we record that in the `.aux` file for the next run.

```
358 \g@addto@macro \@kernel@after@enddocument@afterlastpage {
```

There is one special case: If no output is produced then there is no point in a) recording the number as 0 will never match the page number of a real page and b) adding an extra page to ran the `shipout/lastpage` is pointless as well (as it would remain forever). So we test for this and run the code only if there have been pages.

```
359 \int_compare:nNnF \g_shipout_READONLY_int = 0
360 {
```

This ends up in the `.aux` so we use L^AT_EX 2 _{ε} names here.

Todo: This needs an interface for `\nofiles` in `expl3`, doesn't at the moment!

```
361 \if@filesw
362     \iow_now:Nx \c@auxout {
363         \gdef\string\c@abspos@last {\int_use:N \g_shipout_READONLY_int}}
364     \fi
```

But we may have guessed wrongly earlier and have run it too early or we still have to run the `shipout/lastpage` even though there is no page to place it into. If that is the case we make a trivial extra page and put it there. This temporary page will then vanish again on the next run but helps to keep pdf viewers happy. In either case we should put out an appropriate “rerun” warning.

```
365 \bool_if:NTF \g__shipout_lastpage_handled_bool
366 {
```

If the hook was already executed, we have to test if that total shipouts match the shipouts from last run (because that corresponds to the page it was executed). If not we output a warning.

```
367 \int_compare:nNnF \c@abspos@last = \g_shipout_READONLY_int
368 {
369     \@latex@warning@no@line{Hook~'shipout/lastpage'~executed~
370     on~wrong~page~(\c@abspos@last\space not~
371     \int_use:N\g_shipout_READONLY_int).\MessageBreak
372     Rerun~to~correct~this}%
373 }
374 }
375 {
```

If the hook was not run, we need to add an extra page and place it there. However, making this extra page in case the hook is actually empty would be forcing a rerun without any reason, so we check that condition and also check if `\@kernel@after@shipout@lastpage` contains any code. If both are empty we omit the page generation.

```
376 \bool_lazy_and:nnF
377 { \hook_if_empty_p:n {shipout/lastpage} }
378 { \tl_if_empty_p:N \@kernel@after@shipout@lastpage }
379 {
380     \tex_shipout:D\vbox to\textheight
381     {
382         \hbox:n { \UseHook{shipout/lastpage}
383             \@kernel@after@shipout@lastpage }
```

This extra page could be totally empty except for the hook content, but to help the user understanding why it is there we put some text into it.

```
384          \_\_shipout\_excuse\_extra\_page:  
385          \null  
386      }
```

At this point we also signal to L^AT_EX's endgame that a rerun is necessary so that an appropriate message can be shown on the terminal. We do this by simply defining a command used as a flag and tested in `\enddocument`.

```
387          \cs_gset_eq:NN \c@extra@page@added \relax  
388      }  
389      }  
390  }
```

(End of definition for `\enddocument`, `\@kernel@after@enddocument`, and `\@kernel@after@enddocument@afterlastpage`. These functions are documented on page ??.)

`__shipout_excuse_extra_page:` Say mea culpa ...

```
392 \cs_new:Npn \_\_shipout\_excuse\_extra\_page: {  
393     \vfil  
394     \begin{center}  
395         \bfseries Temporary~ page!  
396     \end{center}  
397     \LaTeX{} was~ unable~ to~ guess~ the~ total~ number~ of~ pages~  
398     correctly.~ ~ As~ there~ was~ some~ unprocessed~ data~ that~  
399     should~ have~ been~ added~ to~ the~ final~ page~ this~ extra~  
400     page~ has~ been~ added~ to~ receive~ it.  
401     \par  
402     If~ you~ rerun~ the~ document~ (without~ altering~ it)~ this~  
403     surplus~ page~ will~ go~ away,~ because~ \LaTeX{} now~ knows~  
404     how~ many~ pages~ to~ expect~ for~ this~ document.  
405     \vfil  
406 }
```

(End of definition for `__shipout_excuse_extra_page:..`)

\PreviousTotalPages In the preamble before the aux file was read `\PreviousTotalPages` is always zero.

`\@kernel@before@begindocument` `\def\PreviousTotalPages{0}`

In the aux file there should be an update for `\@abs@page@last` recording the number of pages from the previous run. If not that macro holds the value of `\maxdimen`. So we test for it and update `\PreviousTotalPages` if there was a real value. This should happen just before the `begindocument` hook is executed so that the value can be used inside that hook.

```
408 \g@addto@macro\@kernel@before@begindocument  
409   {\ifnum\@abs@page@last<\maxdimen  
410     \xdef\PreviousTotalPages{\@abs@page@last}\fi}
```

(End of definition for `\PreviousTotalPages` and `\@kernel@before@begindocument`. These functions are documented on page 6.)

4 Legacy L^AT_EX 2 _{ϵ} interfaces

`\DiscardShipoutBox`

Request that the next shipout box is to be discarded.

411 `\cs_new_eq:NN \DiscardShipoutBox \shipout_discard:`

(End of definition for `\DiscardShipoutBox`. This function is documented on page 5.)

`\AtBeginDvi`

If we roll forward from an earlier kernel `\AtBeginDvi` is defined so we better not use `\cs_new_protected:Npn` here.

412 `\cs_set_protected:Npn \AtBeginDvi`

413 `{__shipout_add_firstpage_material:Nn \AtBeginDvi}`

(End of definition for `\AtBeginDvi`. This function is documented on page 5.)

`\DebugShipoutsOn`

`\DebugShipoutsOff`

414 `\cs_new_eq:NN \DebugShipoutsOn \shipout_debug_on:`

415 `\cs_new_eq:NN \DebugShipoutsOff \shipout_debug_off:`

(End of definition for `\DebugShipoutsOn` and `\DebugShipoutsOff`. These functions are documented on page 7.)

5 Internal commands needed elsewhere

These internal commands use double and triple @ signs so we need to stop getting them translated to the module name.

416 `(@@=)`

Some internals needed elsewhere.

417 `\cs_set_eq:NN @expl@@@shipout@add@firstpage@material@@Nn`

418 `__shipout_add_firstpage_material:Nn`

419 `\cs_set_eq:NN @expl@@@shipout@add@background@box@@n`

420 `__shipout_add_background_box:n`

421 `\cs_set_eq:NN @expl@@@shipout@add@foreground@box@@n`

422 `__shipout_add_foreground_box:n`

423 `\cs_set_eq:NN @expl@@@shipout@add@background@picture@@n`

424 `__shipout_add_background_picture:n`

425 `\cs_set_eq:NN @expl@@@shipout@add@foreground@picture@@n`

426 `__shipout_add_foreground_picture:n`

(End of definition for `@expl@@@shipout@add@firstpage@material@@Nn` and others. These functions are documented on page ??.)

427 `\ExplSyntaxOff`

428 `⟨/2ekernel | latexrelease⟩`

429 `⟨latexrelease⟩\EndIncludeInRelease`

Rolling back here doesn't undefine the interface commands as they may be used in packages without rollback functionality. So we just make them do nothing which may or may not work depending on the code usage.

430 `⟨latexrelease⟩\IncludeInRelease{0000/00/00}%`

431 `⟨latexrelease⟩ {\shipout}{Hook management (shipout)}%`

432 `⟨latexrelease⟩`

If we roll forward then `\tex_shipout:D` may not be defined in which case `\shipout` does have its original definition and so we must not `\let` it to something else which is `\relax!`

```

433 <latexrelease>\ifcsname tex_shipout:D\endcsname
434 <latexrelease>\expandafter\let\expandafter\shipout
435 <latexrelease>                                \csname tex_shipout:D\endcsname
436 <latexrelease>\fi
437 <latexrelease>
438 <latexrelease>\let \RawShipout\@undefined
439 <latexrelease>\let \ShipoutBox\@undefined
440 <latexrelease>\let \ ReadonlyShipoutCounter \@undefined
441 <latexrelease>\let \c@totalpages \@undefined
442 <latexrelease>\let \thetotalpages \@undefined
443 <latexrelease>
444 <latexrelease>\let \DiscardShipoutBox \@undefined
445 <latexrelease>\let \DebugShipoutsOn \@undefined
446 <latexrelease>\let \DebugShipoutsOff \@undefined
447 <latexrelease>
448 <latexrelease>\DeclareRobustCommand \AtBeginDvi [1]{%
449 <latexrelease>  \global \setbox \begindvibox
450 <latexrelease>    \vbox{\unvbox \begindvibox #1}%
451 <latexrelease>}
452 <latexrelease>
453 <latexrelease>\let \AtBeginShipout \@undefined
454 <latexrelease>\let \AtBeginShipoutNext \@undefined
455 <latexrelease>
456 <latexrelease>\let \AtBeginShipoutFirst \@undefined
457 <latexrelease>
458 <latexrelease>\let \ShipoutBoxHeight \@undefined
459 <latexrelease>\let \ShipoutBoxDepth \@undefined
460 <latexrelease>\let \ShipoutBoxWidth \@undefined
461 <latexrelease>
```

We do not undo a substitution when rolling back. As the file support gets undone the underlying data is no longer used (and sufficiently obscure that it should not interfere with existing commands) and properly removing it would mean we need to make the `\undeclare@...` and its support macros available in all earlier kernel releases which is pointless (and actually worse).

```

462 <latexrelease>
463 <latexrelease>\let \AtEndDvi \@undefined
```

We do not reenable a disabled package load when rolling back. As the file support gets undone the underlying data is no longer checked (and sufficiently obscure that it should not interfere with existing commands) and properly removing it would mean we need to make the `\reenable@package@load` command available in all earlier kernel releases which is pointless (and actually worse).

```

464 \%reenable@package@load{atenddvi}
465 <latexrelease>
466 <latexrelease>\EndIncludeInRelease
467 <*2ekernel>
```

6 Package emulation for compatibility

6.1 Package **atenddvi** emulation

\AtEndDvi This package has only one public command, so simulating it is easy and actually sensible to provide as part of the kernel.

```
468 </2ekernel>
469 {*2ekernel | latexrelease}
470 <latexrelease>\IncludeInRelease{2020/10/01}%
471 <latexrelease>          {\AtEndDvi}{atenddvi emulation}%
472 \ExplSyntaxOn
473 \cs_new_protected:Npn \AtEndDvi #1 {\AddToHook{shipout/lastpage}{#1}}
474 \ExplSyntaxOff
```

As the package is integrate we prevent loading (no need to roll that back):

```
475 \disable@package@load{atenddvi}
476   {\PackageWarning{atenddvi}
477     {Functionality of this package is already\MessageBreak
478      provided by LaTeX.\MessageBreak\MessageBreak
479      It is there no longer necessary to load it\MessageBreak
480      and you can safely remove it.\MessageBreak
481      Found on}}
482 </2ekernel | latexrelease>
483 <latexrelease>\EndIncludeInRelease
484 <latexrelease>\IncludeInRelease{0000/00/00}%
485 <latexrelease>          {\AtEndDvi}{atenddvi emulation}%
486 <latexrelease>\let \AtEndDvi \undefined
487 <latexrelease>\EndIncludeInRelease
488 {*2ekernel}
```

(End of definition for \AtEndDvi. This function is documented on page 5.)

```
489 </2ekernel>
```

6.2 Package **atbegshi** emulation

```
490 {*atbegshi-ltx}
491 \ProvidesPackage{atbegshi-ltx}
492 [2021/01/10 v1.0c
493   Emulation of the original atbegshi^^Jpackage with kernel methods]
```

\AtBeginShipoutBox

```
494 \let \AtBeginShipoutBox \ShipoutBox
```

(End of definition for \AtBeginShipoutBox. This function is documented on page 7.)

\AtBeginShipoutInit Compatibility only, we aren't delaying ...

```
495 \let \AtBeginShipoutInit \empty
```

(End of definition for \AtBeginShipoutInit. This function is documented on page 8.)

\AtBeginShipout Filling hooks

\AtBeginShipoutNext

```
496 \protected\long\def\AtBeginShipout      #1{\AddToHook{shipout/before}{#1}}
497 \protected\long\def\AtBeginShipoutNext #1{\AddToHookNext{shipout/before}{#1}}
```

(End of definition for `\AtBeginShipout` and `\AtBeginShipoutNext`. These functions are documented on page 8.)

\AtBeginShipoutFirst Slightly more complex as we need to know the name of the command under which the `shipout/firstpage` hook is filled.

```
498 \protected \def \AtBeginShipoutFirst
499   {\@expl@@@shipout@add@firstpage@material@@Nn \AtBeginShipoutFirst}
```

(End of definition for `\AtBeginShipoutFirst`. This function is documented on page 8.)

\AtBeginShipoutDiscard Just a different name.

```
500 \let \AtBeginShipoutDiscard \DiscardShipoutBox
```

(End of definition for `\AtBeginShipoutDiscard`. This function is documented on page 8.)

\AtBeginShipoutAddToBox We don't expose them.

```
501 \let \AtBeginShipoutAddToBox
502   \@expl@@@shipout@add@background@box@@n
503 \let \AtBeginShipoutAddToBoxForeground
504   \@expl@@@shipout@add@foreground@box@@n
505 \let \AtBeginShipoutUpperLeft
506   \@expl@@@shipout@add@background@picture@@n
507 \let \AtBeginShipoutUpperLeftForeground
508   \@expl@@@shipout@add@foreground@picture@@n
```

(End of definition for `\AtBeginShipoutAddToBox` and others. These functions are documented on page 7.)

\AtBeginShipoutOriginalShipout This offers the raw `\shipout` primitive of the engine. A page shipped out with this is not counted by `\ ReadonlyShipoutCounter` counter and thus the mechanism to place `\specials` at the very end of the output might fail, etc. It should therefore not be used in new applications but is only provided to allow running legacy code. For new code use the commands provided by the kernel instead.

```
509 \ExplSyntaxOn
510 \cs_new_eq:NN \AtBeginShipoutOriginalShipout \tex_shipout:D
```

(End of definition for `\AtBeginShipoutOriginalShipout`. This function is documented on page 8.)

\ShipoutBoxHeight This is somewhat different from the original in `atbegshi` where `\ShipoutBoxHeight` etc. only holds the `\the\ht<box>` value. This may has some implications in some use cases and if that is a problem then it might need changing.

```
511 \cs_new:Npn \ShipoutBoxHeight { \dim_use:N \l_shipout_box_ht_dim }
512 \cs_new:Npn \ShipoutBoxDepth { \dim_use:N \l_shipout_box_dp_dim }
513 \cs_new:Npn \ShipoutBoxWidth { \dim_use:N \l_shipout_box_wd_dim }
514 \ExplSyntaxOff
```

(End of definition for `\ShipoutBoxHeight`, `\ShipoutBoxWidth`, and `\ShipoutBoxDepth`. These functions are documented on page ??.)

```
515 </atbegshi-ltx>
```

If the package is requested we substitute the one above:

```
516 <2ekernel>
517 \declare@file@substitution{atbegshi.sty}{atbegshi-ltx.sty}
518 </2ekernel>
```

6.3 Package **everyshi** emulation

This is now directly handled in that package so emulation is not necessary any more.

Rather important :-)

519 ⟨@@=⟩

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

A	
\AddEverypageHook 9
\AddThispageHook 9
\AddToHook 190, 473, 496, 9
\AddToHookNext 497, 9
\allocationnumber 34
\Alph 6
\arabic 350, 6
\AtBeginDvi 412, 448, 16
\AtBeginShipout 453, 496, 8
\AtBeginShipoutAddToBox 501, 7
\AtBeginShipoutAddToBoxForeground 501, 7
\AtBeginShipoutBox 494, 7
\AtBeginShipoutDiscard 500, 8
\AtBeginShipoutFirst 456, 498, 8
\AtBeginShipoutInit 495, 8
\AtBeginShipoutNext 454, 496, 8
\AtBeginShipoutOriginalShipout 509, 8
\AtBeginShipoutUpperLeft 501, 7
\AtBeginShipoutUpperLeftForeground 501, 7
\AtEndDvi 463, 468, 8
\AtNextShipout 8
B	
\baselineskip 222, 273
\begin 394
\bfseries 395
bool commands:	
\bool_gset_false:N 15, 81, 90
\bool_gset_true:N 10, 120, 344
\bool_if:NTF 21, 88, 365
\bool_lazy_and:nnTF 66, 112, 376
\bool_new:N 6, 188, 203
box commands:	
\box_dp:N 194
\box_ht:N 193, 302, 12
\box_if_empty:NTF 78, 97
\box_if_horizontal:NTF 234, 286
C	
\clearpage 23
cs commands:	
\cs_gset:Npn 173
\cs_gset_eq:NN 52, 151, 166, 167, 172, 181, 185, 321, 387
\cs_gset_protected:Npx 20
\cs_if_exist_use:NTF	313, 314, 318, 319
\cs_new:Npn	54, 59, 77, 141, 146, 163, 178, 183, 189, 192, 206, 257, 310, 323, 337, 340, 350, 392, 511, 512, 513
\cs_new_eq:NN 7, 152, 347, 349, 411, 414, 415, 510
\cs_new_protected:Npn 8, 13, 18, 343, 473, 25
\cs_set_eq:NN 24, 44, 83, 95, 125, 132, 417, 419, 421, 423, 425
\cs_set_protected:Npn 46, 135, 412
\csname 435
D	
\DebugShipoutsOff 414, 446, 7
\DebugShipoutsOn 414, 445, 7
\DeclareRobustCommand 448
\def 407, 496, 497, 498
dim commands:	
\dim_new:N 199, 200, 201, 202
\dim_set:Nn 193, 194, 195, 196

\dim_use:N	511, 512, 513
\c_max_dim	213, 239, 264, 291
\c_zero_dim	219, 220, 221, 227, 245, 246, 247, 270, 271, 272, 299, 300, 301, 329, 331, 332
\DiscardShipoutBox	82, 411, 444, 500, 5
E	
\end	396
\endcsname	433, 435
\enddocument	352, 22
\EndIncludeInRelease	429, 466, 483, 487
\everyjob	29, 30
\EveryShipout	8
exp commands:	
\exp_args:Nx	29
\exp_not:N	31, 95, 125
\exp_not:n	30
\expandafter	434
\ExplSyntaxOff	427, 474, 514
\ExplSyntaxOn	5, 472, 509
F	
\fi	364, 410, 436
G	
\gdef	363
\global	449
group commands:	
\group_begin:	92
\group_end:	94
H	
\hbadness	238, 240, 290, 292
\hbox	3
hbox commands:	
\hbox:n	382
\hbox_set:Nn	170, 217, 243, 268, 297
\hbox_set_to_wd:Nnn	241, 293, 329
\hbox_unpack:N	251, 295
\hbox_unpack_drop:N	180
\hfuzz	237, 239, 289, 291
hook commands:	
\hook_if_empty:nTF	63, 164
\hook_if_empty_p:n	67, 113, 377
\hook_new:n	153, 154, 155, 156, 157, 158, 159
\hook_use:n	62, 65, 71, 75, 123
\hss	330, 21
I	
\ifcsname	433
\ifnum	409, 6
\ignorespaces	330
\IncludeInRelease	3, 430, 470, 484
int commands:	
\int_compare:nNnTF	55, 111, 142, 353, 359, 367
\int_eval:n	355
\int_gincr:N	87, 102
\int_new:N	346, 348
\int_use:N	104, 116, 363, 371, 6
\int_value:w	48, 137
\c_max_int	214, 240, 265, 292
\c_zero_int	91
iow commands:	
\iow_now:Nn	362
K	
\kern	227, 277, 279, 296, 304, 325, 327, 18
L	
\LaTeX	397, 403
\let	160, 161, 162, 434, 438, 439, 440, 441, 442, 444, 445, 446, 453, 454, 456, 458, 459, 460, 463, 486, 494, 495, 500, 501, 503, 505, 507, 26
\lineskip	223, 274
\lineskiplimit	224, 275
\long	496, 497
lua commands:	
\lua_now:n	31
M	
\maxdimen	351, 353, 409, 24
\MessageBreak	99, 175, 371, 477, 478, 479, 480
N	
\newprotectedluacmd	28
\nofiles	23
\null	385
\number	351
P	
\PackageWarning	476
\par	401
\pdfhorigin	314
\pdfvariable	313, 318
\pdfvorigin	319
pre commands:	
\pre_shipout_filter	6
\PreviousTotalPages	407, 6
prg commands:	
\prg_do_nothing:	166, 167, 172, 181, 185, 321
\protect	83, 95, 125, 132, 152, 15
\protected	496, 497, 498
\ProvidesPackage	491
\put	9

R

\RawShipout 151, 438, 13
 \ ReadonlyShipoutCounter 346, 440, 8
 \relax 211, 212,
 237, 238, 262, 263, 289, 290, 387, 26
 \RequirePackage 7
 \Roman 6

S

scan commands:
 \scan_stop: 44, 325, 327, 328
 \setbox 449
 \shipout 4, 52, 431, 434, 4
 shipout 153
 shipout commands:
 \l_shipout_box
 23, 35, 38, 50, 61, 126, 149, 179,
 184, 207, 208, 215, 226, 229, 230,
 234, 241, 251, 259, 266, 276, 282,
 283, 286, 293, 295, 296, 302, 304, 2
 \l_shipout_box_dp_dim
 194, 197, 199, 230, 283, 512, 3
 \l_shipout_box_ht_dim
 193, 197, 199, 229, 249, 282, 511, 3
 \l_shipout_box_ht_plus_dp_dim
 196, 199, 215, 266, 277, 279, 3
 \l_shipout_box_wd_dim
 195, 199, 241, 293, 513, 3
 \shipout_debug_off: 7, 13, 415, 7
 \shipout_debug_on: 7, 8, 414, 7
 \shipout_discard: 343, 343, 411, 5
 \g_shipout_READONLY_int
 102, 104, 111,
 116, 346, 355, 359, 363, 367, 371, 6
 \g_shipout_TOTALPAGE_int 6
 \g_shipout_TOTALPAGES_int 87, 348, 12
 shipout internal commands:
 __shipout_add_background_box:n
 180, 206, 206, 338, 420
 __shipout_add_background_-_picture:n 69, 337, 337, 424
 __shipout_add_firstpage_-_material:Nn 173, 189, 189, 413, 418
 __shipout_add_firstpage_-_specials: 110, 166, 178, 178, 181, 13
 __shipout_add_foreground_box:n
 117, 257, 257, 341, 422
 __shipout_add_foreground_-_picture:n 64, 340, 340, 426
 __shipout_debug:n
 7, 7, 20, 103, 115, 148, 9
 \g__shipout_DEBUG_bool 6, 10, 15, 21
 __shipout_DEBUG_gset: 7, 11, 16, 18

\g__shipout_discard_bool
 81, 88, 90, 203, 344
 __shipout_drop_firstpage_-_specials: 127, 167, 178, 183, 185, 16
 __shipout_excuse_extra_page:
 384, 392, 392
 __shipout_execute: 46, 46, 52, 11
 __shipout_execute_cont: 57, 59, 59
 __shipout_execute_main_cont:Nnn
 60, 77, 77, 147, 14
 __shipout_execute_nohooks_cont:
 144, 146
 __shipout_execute_raw:
 135, 135, 151, 14
 __shipout_execute_test_level:
 49, 54, 54
 __shipout_execute_test_level_-_raw: 135, 138, 141
 __shipout_finalize_box:
 26, 28, 44, 124
 \l__shipout_firstpage_box
 170, 180, 187, 16
 __shipout_get_box_size:N
 85, 107, 192, 192, 207, 17
 \l__shipout_group_level_t1
 47, 53, 56, 136, 143
 \c__shipout_horigin_t1 310, 325
 __shipout_init_page_origins:
 310, 310, 321, 324
 \g__shipout_lastpage_handled_-_bool 120, 188, 365
 __shipout_picture_overlay:n
 323, 323, 338, 341
 \l__shipout_raw_box
 25, 139, 147, 149, 179, 184, 13
 __shipout_run_firstpage_hook:
 108, 163, 163, 172, 15
 \l__shipout_saved_badness_t1
 204, 210, 218, 231, 236,
 244, 253, 261, 269, 281, 288, 298, 306
 __shipout_saved_protect:
 83, 132, 152, 152
 \l__shipout_TMP_box 204, 217, 219,
 220, 221, 225, 243, 245, 246, 247,
 250, 268, 270, 271, 272, 278, 297,
 299, 300, 301, 303, 329, 331, 332, 333
 \c__shipout_vorigin_t1 310, 327
 shipout/after 153, 3
 shipout/background 153, 3
 shipout/before 153, 3
 shipout/firstpage 153, 3
 shipout/foreground 153, 3
 shipout/lastpage 153, 3
 \ShipoutBox 23, 439, 494, 3

\ShipoutBoxDepth	459, 511	\g@addto@macro	352, 358 , 408
\ShipoutBoxHeight	458, 511 , 28	\if@filesw	361
\ShipoutBoxWidth	460, 511	\reenable@package@load	464, 26
skip commands:		\set@typeset@protect	84, 128
\skip_zero:N	222, 223 , 224 , 273 , 274 , 275	\undeclare@...	26
\space	105, 370	tex commands:	
\special	17	\tex_afterassignment:D	49, 138
\string	175, 363	\tex_aftergroup:D	57, 144 , 11
sys commands:		\tex_currentgrouplevel:D	
\sys_if_engine_luatex:TF	26	...	48, 56 , 137 , 143
T			
TEX and L ^A T _E X 2 _E commands:		\tex_deadcycles:D	91
@abspage@last	105, 111 , 351 , 353, 355 , 363 , 367 , 370 , 409 , 410 , 22	\tex_setbox:D	50, 139
@auxout	362	\tex_shipout:D	126, 380 , 510
@begindvi	9	\tex_vss:D	334
@begindvibox	449, 450 , 4	texheight	380
@cclv	8	\textheight	380
@empty	160, 161 , 162 , 495	\the	34, 35 , 38 , 211, 212 , 237 , 238 , 262 , 263 , 289 , 290
@expl@@@shipout@add@background@box@on	417, 502	\thepage	22
@expl@@@shipout@add@background@picture@on	417, 506	\thetotalpages	350, 442 , 22
@expl@@@shipout@add@firstpage@material@on	417, 499	tl commands:	
@expl@@@shipout@add@foreground@box@on	417, 504	\tl_const:Nn	311, 316
@expl@@@shipout@add@foreground@picture@on	417, 508	\tl_if_empty_p:N	68, 114 , 378
@extra@page@added	387	\tl_new:N	53, 205
@kernel@after@enddocument	352	\tl_set:Nn	47, 136 , 210 , 236 , 261 , 288
@kernel@after@enddocument@afterlastpage	358	totalpages	6
@kernel@after@shipout@background	72, 160 , 11	\typeout	104, 115 , 148 , 4
U			
@kernel@after@shipout@lastpage	114, 119 , 160 , 378 , 383 , 23	\unitlength	328, 3
@kernel@before@begindocument	407	\unvbox	450
@kernel@before@shipout@background	68, 70 , 160 , 11	use commands:	
@latex@info@no@line	89	\use_none:n	7
@latex@warning	174	\usehook	118, 170 , 382
@latex@warning@no@line	79, 98 , 369	\usepackage	7
@undefined	438,		
439, 440 , 441 , 442 , 444 , 445 , 446 ,	V		
453, 454 , 456 , 458 , 459 , 460 , 463 , 486	\badness	212, 214 , 263 , 265 , 18	
@c@totalpages	348, 441	\vbox	380, 450 , 2
declare@file@substitution	517	vbox commands:	
:disable@package@load	475	\vbox_set_to_ht:Nnn	215, 266
W			
		\vbox_to_zero:n	326
		\vbox_unpack:N	226, 276
		\vfuzz	393, 405
		\vfuzz	211, 213 , 262 , 264 , 18
X			
		\write	4
		\xdef	351, 355 , 410