

The `flags` package

Heiko Oberdiek*

2016/05/16 v0.5

Abstract

Package `flags` allows the setting and clearing of flags in bit fields and converts the bit field into a decimal number. Currently the bit field is limited to 31 bits.

Contents

1 Documentation	1
1.1 User interface	2
1.2 Requirements	2
1.3 ToDo	2
2 Implementation	2
3 Installation	5
3.1 Download	5
3.2 Bundle installation	5
3.3 Package installation	6
3.4 Refresh file name databases	6
3.5 Some details for the interested	6
4 History	6
[2007/02/18 v0.1]	6
[2007/03/07 v0.2]	7
[2007/03/31 v0.3]	7
[2007/09/30 v0.4]	7
[2016/05/16 v0.5]	7
5 Index	7

1 Documentation

A new powerful package `bitset` is written by me and supersedes this package:

- The bit range is not restricted to 31 bits, only index numbers are objected to \TeX 's number limit.
- Many more operations are available.
- No dependency of $\varepsilon\text{-}\text{\TeX}$.

Therefore I consider this package as obsolete and have stopped the development of this package.

*Please report any issues at <https://github.com/ho-tex/oberdiek/issues>

1.1 User interface

Flag positions are one-based, thus the flag position must be a positive integer.
Currently supported range: 1..31

```
\resetflags {\<fname>}
```

The bit field $\langle fname \rangle$ is cleared. Currently is is also used for initialization, because a `\newflags` macro is not implemented.

```
\setflag {\<fname>} {\<position>}
```

The flag at bit position $\langle position \rangle$ is set in the bit field $\langle fname \rangle$.

```
\clearflag {\<fname>} {\<position>}
```

The flag at bit position $\langle position \rangle$ is cleared in the bit field $\langle fname \rangle$.

```
\printflags {\<fname>}
```

The bit field $\langle fname \rangle$ is converted to a decimal number. The macro is expandible.

```
\extractflag {\<fname>} {\<position>}
```

Extracts the flag setting at bit position $\langle position \rangle$. `\extractflag` expands to 1 if the flag is set and 0 otherwise.

```
\queryflag {\<fname>} {\<position>} {\<set part>} {\<clear part>}
```

It is a wrapper for `\extractflag`. $\langle set part \rangle$ is called if `\extractflag` returns 1. Otherwise $\langle clear part \rangle$ is executed.

Example. See package `bookmark`. It uses package flags for its font style options.

1.2 Requirements

- ε -`TEX` (`\numexpr`)

1.3 ToDo

- Named positions.
- Setting positions by a key-value interface.
- Support for more than 31 bits while maintaining expandibility of `\printflags`.
- Eventually `\newflags`, `\newflagstype`.

2 Implementation

```
1 {*package}
2 \NeedsTeXFormat{LaTeX2e}
3 \ProvidesPackage{flags}%
4 [2016/05/16 v0.5 Setting/clearing of flags in bit fields (HO)]%
5 \begingroup\expandafter\expandafter\expandafter\endgroup
```

```

6 \expandafter\ifx\csname numexpr\endcsname\relax
7   \PackageError{flags}{%
8     Missing e-TeX, package loading aborted%
9   }{%
10   This packages makes heavy use of \string\numexpr.%%
11 }{%
12 \expandafter\endinput
13 \fi

\resetflags
14 \newcommand*{\resetflags}[1]{%
15   \expandafter\let\csname flags@#1\endcsname\empty
16 }

\printflags Macro \printflags converts the bit field into a decimal number.
17 \newcommand*{\printflags}[1]{%
18   \expandafter\@printflags\csname flags@#1\endcsname
19 }
20 \def\@printflags#1{%
21   \expandafter\@firstofone\expandafter{%
22     \number\numexpr
23     \ifx#1\empty
24       0%
25     \else
26       \expandafter\@@printflags#1%
27     \fi
28   }%
29 }
30 \def\@@printflags#1#2\fi{%
31   \fi
32   #1%
33   \ifx\\#2\\%
34   \else
35     +2*\numexpr\expandafter\@@printflags#2%
36   \fi
37 }

\setflag
38 \newcommand*{\setflag}[2]{%
39   \ifnum#2>\z@
40     \expandafter\@setflag\csname flags@#1\expandafter\endcsname
41     \expandafter{\romannumeral\number\numexpr#2-1\relax000}%
42   \else
43     \PackageError{flags}{Position must be a positive number}\@ehc
44   \fi
45 }
46 \def\@setflag#1#2{%
47   \ifx#1\relax
48     \let#1\empty
49   \fi
50   \edef#1{%
51     \expandafter\@@setflag\expandafter{\#1}{#2}%
52   }%
53 }
54 \def\@@setflag#1#2{%
55   \ifx\\#1\\%
56     \FLAGS@zero#2\relax
57     1%
58   \else
59     \ifx\\#2\\%
60       1\@gobble#1%
61     \else
62       \@@@setflag#1|#2%

```

```

63      \fi
64  \fi
65 }
66 \def\@@setflag#1#2|#3#4\fi\fi{%
67   \fi\fi
68   #1%
69   \@@setflag{#2}{#4}%
70 }

\clearflag
71 \newcommand*{\clearflag}[2]{%
72   \ifnum#2>\z@
73     \expandafter\@clearflag\csname flags@#1\expandafter\endcsname
74     \expandafter{\romannumeral\number\numexpr#2-1\relax000}%
75   \else
76     \PackageError{flags}{Position must be a positive number}\@ehc
77   \fi
78 }
79 \def\@clearflag#1#2{%
80   \ifx#1\relax
81     \let#1\empty
82   \fi
83   \edef#1{%
84     \expandafter\@@clearflag\expandafter{#1}{#2}%
85   }%
86 }
87 \def\@@clearflag#1#2{%
88   \ifx\#1\%
89   \else
90     \ifx\#2\%
91       \gobble#1%
92     \else
93       \@@@clearflag#1|#2%
94     \fi
95   \fi
96 }
97 \def\@@@clearflag#1#2|#3#4\fi\fi{%
98   \fi\fi
99   #1%
100  \@@@clearflag{#2}{#4}%
101 }

\def\FLAGS@zero#1{%
102   \ifx#1\relax
103   \else
104     0%
105   \expandafter\FLAGS@zero
106   \fi
107 }
108 }

\queryflag
109 \newcommand*{\queryflag}[2]{%
110   \ifnum\extractflag{#1}{#2}=\@ne
111     \expandafter\@firstoftwo
112   \else
113     \expandafter\@secondoftwo
114   \fi
115 }

\extractflag
116 \newcommand*{\extractflag}[1]{%
117   \expandafter\@extractflag\csname flags@#1\endcsname
118 }

```

```

119 \def\@extractflag#1#2{%
120   \ifx#1\undefined
121     %
122   \else
123     \ifx#1\relax
124       %
125     \else
126       \ifx#1\empty
127         %
128       \else
129         \expandafter\expandafter\expandafter\@extractflag
130         \expandafter\expandafter\expandafter{%
131           \expandafter#1\expandafter
132           }\expandafter{%
133             \romannumeral\number\numexpr#2-1\relax000%
134           }%
135         \fi
136       \fi
137     \fi
138 }
139 \def\@extractflag#1#2{%
140   \ifx\#1\%
141     %
142   \else
143     \ifx\#2\%
144       \car#1\@nil
145     \else
146       \@@extractflag#1#2%
147     \fi
148   \fi
149 }
150 \def\@@extractflag#1#2|#3#4\fi\fi{%
151   \fi\fi
152   \@@extractflag{#2}{#4}%
153 }

154 </package>

```

3 Installation

3.1 Download

Package. This package is available on CTAN¹:

[CTAN:macros/latex/contrib/oberdiek/flags.dtx](#) The source file.

[CTAN:macros/latex/contrib/oberdiek/flags.pdf](#) Documentation.

Bundle. All the packages of the bundle ‘oberdiek’ are also available in a TDS compliant ZIP archive. There the packages are already unpacked and the documentation files are generated. The files and directories obey the TDS standard.

[CTAN:install/macros/latex/contrib/oberdiek.tds.zip](#)

TDS refers to the standard “A Directory Structure for TeX Files” ([CTAN:pkg/tds](#)). Directories with `texmf` in their name are usually organized this way.

3.2 Bundle installation

Unpacking. Unpack the `oberdiek.tds.zip` in the TDS tree (also known as `texmf` tree) of your choice. Example (linux):

¹[CTAN:pkg/flags](#)

```
unzip oberdiek.tds.zip -d ~/texmf
```

3.3 Package installation

Unpacking. The `.dtx` file is a self-extracting `docstrip` archive. The files are extracted by running the `.dtx` through plain `TeX`:

```
tex flags.dtx
```

TDS. Now the different files must be moved into the different directories in your installation TDS tree (also known as `texmf` tree):

```
flags.sty → tex/latex/oberdiek/flags.sty  
flags.pdf → doc/latex/oberdiek/flags.pdf  
flags.dtx → source/latex/oberdiek/flags.dtx
```

If you have a `docstrip.cfg` that configures and enables `docstrip`'s TDS installing feature, then some files can already be in the right place, see the documentation of `docstrip`.

3.4 Refresh file name databases

If your `TeX` distribution (`TeX Live`, `MiKTeX`, ...) relies on file name databases, you must refresh these. For example, `TeX Live` users run `texhash` or `mktexlsr`.

3.5 Some details for the interested

Unpacking with L^AT_EX. The `.dtx` chooses its action depending on the format:

plain TeX: Run `docstrip` and extract the files.

L^AT_EX: Generate the documentation.

If you insist on using L^AT_EX for `docstrip` (really, `docstrip` does not need L^AT_EX), then inform the autodetect routine about your intention:

```
latex \let\install=y\input{flags.dtx}
```

Do not forget to quote the argument according to the demands of your shell.

Generating the documentation. You can use both the `.dtx` or the `.drv` to generate the documentation. The process can be configured by the configuration file `ltxdoc.cfg`. For instance, put this line into this file, if you want to have A4 as paper format:

```
\PassOptionsToClass{a4paper}{article}
```

An example follows how to generate the documentation with pdfL^AT_EX:

```
pdflatex flags.dtx  
makeindex -s gind.ist flags.idx  
pdflatex flags.dtx  
makeindex -s gind.ist flags.idx  
pdflatex flags.dtx
```

4 History

[2007/02/18 v0.1]

- First version.

[2007/03/07 v0.2]

- Raise an error if ε -TeX is not detected.

[2007/03/31 v0.3]

- \backslash queryflag and \backslash extractflag added.
- Raise an error if position is not positive in case of \backslash setflag and \backslash clearflag.

[2007/09/30 v0.4]

- Package is deprecated because of new more powerful package `bitset`.

[2016/05/16 v0.5]

- Documentation updates.

5 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; plain numbers refer to the code lines where the entry is used.

Symbols	F
\backslash @@@clearflag 93, 97	\backslash FLAGS@zero 56, 102, 106
\backslash @@@extractflag 146, 150	
\backslash @@@setflag 62, 66	I
\backslash @@clearflag 84, 87, 100	\backslash ifnum 39, 72, 110
\backslash @@extractflag 129, 139, 152	\backslash ifx 6, 23, 33, 47, 55, 59, 80,
\backslash @@printflags 26, 30, 35	88, 90, 103, 120, 123, 126, 140, 143
\backslash @@setflag 51, 54, 69	
\backslash @car 144	N
\backslash @clearflag 73, 79	\backslash NeedsTeXFormat 2
\backslash @ehc 43, 76	\backslash newcommand 14, 17, 38, 71, 109, 116
\backslash @empty 15, 23, 48, 81, 126	\backslash number 22, 41, 74, 133
\backslash @extractflag 117, 119	\backslash numexpr 10, 22, 35, 41, 74, 133
\backslash @firstofone 21	
\backslash @firstoftwo 111	P
\backslash @gobble 60, 91	\backslash PackageError 7, 43, 76
\backslash @ne 110	\backslash printflags 2, 17
\backslash @nil 144	\backslash ProvidesPackage 3
\backslash @printflags 18, 20	
\backslash @secondoftwo 113	Q
\backslash @setflag 40, 46	\backslash queryflag 2, 109
\backslash @undefined 120	
$\backslash\backslash$ 33, 55, 59, 88, 90, 140, 143	R
	\backslash resetflags 2, 14
C	\backslash romannumeral 41, 74, 133
\backslash clearflag 2, 71	
\backslash csname 6, 15, 18, 40, 73, 117	S
	\backslash setflag 2, 38
E	
\backslash endcsname 6, 15, 18, 40, 73, 117	Z
\backslash endinput 12	\backslash z@ 39, 72
\backslash extractflag 2, 110, 116	